Form 3160-5 (August 2007)

(Instructions on page 2)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

HOBER DED

FEB 06 2013

FORM APPROVED OMB No. 1004-0137

Expires: July 31, 2010 5. Lease Serial No. NM-40450

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter-an abandoned well. Use Form 3160-3 (APD) for such proposals.

NM-40450
6. If Indian, Allottee or Tribe Name

abaridoried weil.	JSE FOIIII 3 100-3 (A	PD) for such pr	oposais.—				
SUBMIT IN TRIPLICATE – Other instructions on page 2.				7. If Unit of CA/Agreement, Name and/or No.			
1. Type of Well				8. Well Name and No.			
Oil Well Gas Well Other  2. Name of Operator				Uncle Sam 13 B Federal #1			
DEVON ENERGY PRODUCTION COMPANY, LP				9. API Well No. 30-025-30837			
<ol> <li>Address</li> <li>West Sheridan Avenue, Oklahoma City, OK</li> </ol>	3b. Phone No. (include area code) 405-552-4615		10. Field and Pool or Exploratory Area CORBIN;DELAWARE,WEST				
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 785 FNL & 1980 FWL; SEC 13-T18S-R32E				11. Country or Parish, State Lea, NM			
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDICATE	NATURE OF NOT	ICE, REPORT OR OTHE	ER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize Alter Casing	Deepen Fracture Tree		oduction (Start/Resume)	Water Shut-Off Well Integrity		
Subsequent Report	Casing Repair	New Constru	=	complete	Other		
Final Abandonment Notice	Change Plans Convert to Injection	✓ Plug and Ab ☐ Plug Back	_	mporarily Abandon iter Disposal			
testing has been completed. Final Adetermined that the site is ready for Wellbore Plugged & Abandoned: Wolf 1. MIRU plugging rig. 2. POOH w/rods and 2-7/8" tubing 3. Set CIBP @ 4,950'. Circulate w/g 4. Spot 25 sx cement @ 2,657'. Tag 5. Spot 25 sx cement @ 1,437'. Tag 6. Perfed sqz holes in 5-1/2" casing 7. Cut wellhead off and set dry hole of Accepted as to plugging of the Liability under bond is retained Surface restoration is complete.	elled mud.Test casing to ged TOC @ 2,355'. ged TOC @ 1,156'. @ 500'. Pumped 160 sx marker. Wellbore plugged well bore. d until	1/22/13 400 psi. Ok. Spot 2 cement inside/out on	5 sx cement on CIE 5-1/2" casing to su 22/13.	ACCEPTEI  ACCEPTEI  FEB  BUP: AU OF	D FOR RECORD		
14. I hereby certify that the foregoing is true and correct.  Name (Printed/Typed)  Ronnie Slack  Title			Operations Technician				
Signature Round &	Yack	Date	1/25/1	3			
	THIS SPACE	FOR FEDERAL	OR STATE OF	FICE USE			
Approved by			Title	l <sub>D</sub>	ate		
Conditions of approval, if any, are attached that the applicant holds legal or equitable tit entitle the applicant to conduct orterations the	Office	ŢD.					
Title 18 U.S.C. Section 1001 and Title 43 U. fictitious or fraudulent statements or repres			owingly and willfully	to make to any department	or agency of the United States any false,		

