Form 3160-5 (March 2012)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Hobbs

FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2014

HOBBS C Expires. Colors St. Lease Serial No.
SHL: LC0618763A BHL: LC061873B

FEB 2 6 4019 Indian, Allottee or Tribe Name SUNDRY NOTICES AND REPORTS ON WELLS

		o ariii or to re-entei PD) for such propo					
SUBMIT IN TRIPLICATE – Other instructions on page 2.				ID If Unit of CA/Agreement, Name and/or No.			
I. Type of Well				Cotton Draw Unit NMNM 70928X			
Oil Well Gas Well Other				8. Well Name and No. Cotton Draw Unit 157H			
2. Name of Operator Devon Energy Production Company, L.P.				9. API Well No. 30-025-40584			
			(include area code) 10. Field and Pool or Exploratory Area				
333 W. Sheridan Avenue Oklahoma City, Oklahoma 73102 405-228-42				Paduca, Delaware			
4. Location of Well (Foolage, Sec., T., R., M., or Survey Description) 330' FSL & 660' FWL, Sec 18, T25S-R32E, Unit M				11. County or Parish, Lea County, NM	State		
12. CHEC	K THE APPROPRIATE BO	DX(ES) TO INDICATE NA	TURE OF NOTIC	E, REPORT OR OTH	ER DATA		
TYPE OF SUBMISSION	ION						
Notice of Intent	Acidize Deepen Production (Start/Resume)		Water Shut-Off	Water Shut-Off			
Notice of finetic	Alter Casing	Fracture Treat	Recla	amation	Well Integrity		
✓ Subsequent Report	Casing Repair	New Construction	Reco	mplete	✓ Other		
V Subsequent Report	Change Plans	Plug and Abandon	n 🔲 Tem	oorarily Abandon			
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Wate	r Disposal	Spud Repo	<u>irt</u>	
testing has been completed. Final determined that the site is ready for 10/19/12: MIRU. Spud well @ 06:3 cf/sx. Disp w/118 bbls FW. Circ 25 10/21/12: Test 13-3/8" casing to 12 10/24/12: TD 12-1/4" hole @ 4350' LTC csg & set @ 4350'. Lead w/10 1.37 cf/sx; displ w/326 bbls FW. Circ of BOP test; CK manifold 250 psi L 10/25/12: Test casing to 1500 psi ft 10/27/12: Gyro got stuck in hole. N Drill cement to KOP. KOP is @ 75 11/09/12: TD 8-3/4" production hole lead w/350 sx Cl H, Yld 2.3 cf/sx, 2r casing to 5000 psi. (Good Test). 11/10/12 RDMO. Release Rig @ 2	r final inspection.) 30 hrs. TD 17-1/2" hole @ 8 sx to surf. WOC. Test 10 psi and held for 30 mi . Notified NMOCD. RIH 00 sx CI C, yld 1.73 sf/sx rc 200 sx to surf. RD cmt & 5000 psi; held 10 min. or 30 minutes, (Good Tes lot able to recover fish. L 87'. Drill to TD. e @ 12,737'. CHC. RIH nd Lead w/350 sxCl H, Yl	788'. RIH w/19 jts 13-3/ Annular 250 psi L 3500 p nutes. (Good Test). w/98 jts 9-5/8" 40# J-55 . Tail w/300 sx CI C, yld: equip, notified NMOCD Test annular to 2500 psi lst). Continue drilling aheac ength of fish 30.91', top o w/159 jts 5-1/2" 17# HCP- d 2.01 cf/sx. Tail w/1,425	8" 48# H-40 ST si H, 10 mins, g H & 250 psi L. l. f fish @ 7669'.	C csg & set @ 788'. cod per NMOCD. TIH & set kick off plu ts 5-1/2" HCP 110 B	Lead w/956 sx Cl "C" of the state of the sta	omt, yld: 1.35 ent @ 7082'. CHC. 1st	
Patti Riechers			Title Regulatory Specialist				
Signature Patti A	lehers	Date 02	/11/2013	200707	TO TOO DEC	1000	
		FOR FEDERAL OF	R STATE OF	FICE USE	LUTUITAL	ן עאטן	
Approved by		<u> </u>				i l	
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		Tr	. 1		D-D 0 0010		
Conditions of approval, if any, are attache that the applicant holds legal or equitable entitle the applicant to conduct operations	title to those rights in the subj		1/1/	fo	113 to 2 3 2013		
Title 18 U.S.C. Section 1001 and Title 43 fictitious or fraudulent statements or repr			ngly and willfully		ent or/agency/of the United SRAD FIFLD OFFICE	Eştates any false	
(Instructions on page 2)	as to any matter v	BC.		1	PROFIELD UFFILE	=======================================	