Submit I Copy To Appropriate District State of New Mexico	Form C-103
Office District I – (575) 393-6161 Energy, Minerals and Natural Resource	,
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
811 S. First St., Artesia, NM 88210	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460 MAR 07 2013 Santa Fe, NM 87505	STATE S FEE
1220 S. St. Francis Dr., Santa Fe, NM	6. State Oil & Gas Lease No. VB-1169
87505 SUNDRY NOTICES CANDEREPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Hemlock BSH State
PROPOSALS.)	8. Well Number 2H
1. Type of Well: Oil Well Gas Well Other 2. Name of Operator Image: Comparison of Com	9. OGRID Number
Yates Petroleum Corporation	025575
 Address of Operator 105 South Fourth Street, Artesia, NM 88210 	10. Pool name or Wildcat Triple X; Bone Spring
4. Well Location	
Unit Letter D : 220 feet from the North line an	
Unit Letter <u>A</u> <u>330</u> feet from the <u>South</u> line an	
Section 32 Township 23S Range 11. Elevation (Show whether DR, RKB, RT,	33E NMPM Lea County GR, etc.) Symplex (a) Symplex (a)
3671'GR	
12. Check Appropriate Box to Indicate Nature of I	Notice Report or Other Data
	· · · · ·
	SUBSEQUENT REPORT OF: AL WORK
	CEMENT JOB
_	
	Production casing
13. Describe proposed or completed operations. (Clearly state all pertinent de	etails, and give pertinent dates, including estimated date
	etails, and give pertinent dates, including estimated date
 Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 	etails, and give pertinent dates, including estimated date
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 	etails, and give pertinent dates, including estimated date
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 	etails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 	etails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemed 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1%
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 1.87, wt 13). 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 3.87, wt 13). 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (ystage 3 with 250 sx 36:65:6 Poz "H" + 0.2% PF13 + 0.2% PF133 + 6% PF20 + 0.1 PF46 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). 	etails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% /ld 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx S + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5%
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). Spud Date: 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% //d 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx 6 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5%
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% //d 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx 6 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5%
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (stage 3 with 250 sx 36:65:6 Poz "H" + 0.2% PF13 + 0.2% PF133 + 6% PF20 + 0.1 PF46 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). Spud Date: 	tails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% //d 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx 6 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5%
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (stage 3 with 250 sx 36:65:6 Poz "H" + 0.2% PF13 + 0.2% PF133 + 6% PF20 + 0.1 PF46 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). Spud Date: 	2/26/13 2/26/13 2/26/13
13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Cemerer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cemerer PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF606 + 0.2% PF800 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 Spud Date: 1/26/13 Rig Release Date: I hereby certify that the information above is true and complete to the best of my k SIGNATURE Title Lengulatory Rep Type or print name Tina Huerta E-mail address: tinah@yatespetit	etails, and give pertinent dates, including estimated date tiple Completions: Attach wellbore diagram of d 10,490'. External casing packer at 6961'. Crossover F13 + 30% PF151 + 0.2% PF153 + 5% PF174 + ented stage 2 with 770 sx PVL + 0.55% PF13 + 0.1% Vd 1.48, wt 13). Circulated 114 sx to pit. Cemented 25#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% 2/26/13 nowledge and belief. porting Supervisor DATE March 5, 2013 pHONE: 575-748-4168
 13. Describe proposed or completed operations. (Clearly state all pertinent de of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Mul proposed completion or recompletion. 2/14/13 – Drilled to 10,673' KOP and continued to drill directionally. 2/18/13 – Drilled to 11,387' and reduced hole to 8-1/2" and continued drilling. 2/22/13 – Reached TD 8-1/2" hole to 15,693' at 6:00 PM. 2/24/13 – Set 5-1/2" 17# P-110 BTC casing at 15,688'. DV/stage tool at 6959' and at 10,492'. Float collar at 15,641'. Cemented stage 1 with 850 sx PVL + 0.55% P 0.25#/sx PF46 + 0.7% PF606 + 0.2% PF79 + 0.2% PF800 (yld 1.87, wt 13). Ceme PF153 + 5% PF174 + 1.3% PF44 + 0.25#/sx PF46 + 0.5% PF13 + 6% PF20 + 0.1 PF46 (yld 2.06 wt 12.6). Tailed in with 150 sx PVL + 0.55% PF13 + 0.1% PF153 PF606 + 0.2% PF800 (yld 1.48, wt 13). Spud Date: 1/26/13 Rig Release Date: I hereby certify that the information above if true and complete to the best of my k SIGNATURE Tina Huerta E-mail address: tinah@yatespetf 	2/26/13 2/26/13 2/26/13 PHONE:

MAR 19 2013