Submit 1 Copy To Appropriate District	State of New Mexico		Form C	
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Re	sources WELL AP	Revised August 1	, 2011
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	HOEBS OCD	20.025.41	,	
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVI	SION	Type of Lease	
District III - (505) 334-6178	MAY 01 2018220 South St. Francis D	r. STA	ATE FEE	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505		il & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM	DECEIVED	VO-3900/	VB-1384	
87505 SUNDRY NO	TICES AND REPORTS ON WELLS	7. Lease N	Vame or Unit Agreement Na	me
(DO NOT USE THIS FORM FOR PRO	POSALS TO DRILL OR TO DEEPEN OR PLUG BAC	K TO A Belfast BS	L State Com	
DIFFERENT RESERVOIR. USE "APF PROPOSALS.)	PLICATION FOR PERMIT" (FORM C-101) FOR SUC	8. Well N	umber /	
1. Type of Well: Oil Well	Gas Well Other	1Y		
2. Name of Operator		9. OGRID	Number /	
Yates Petroleum Corporation		025575		
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210			10. Pool name or Wildcat Berry; Bone Spring, North	
h	, NM 88210	Berry, Bor	e Spring, North	/
4. Well Location Unit Letter Lot 13:	2750 feet from the South lin	e and 660 fe	eet from the West	line
Unit Letter Lot 4				line
		34E NMPM	Lea County	
Section 6	Township 21S Range 11. Elevation (Show whether DR, RKB,		Lea County 7	
	3740°GR			4
12. Checl	k Appropriate Box to Indicate Nature	of Notice, Report or	Other Data	
NOTICE OF	INTENTION TO:	SUBSEQUEN	T REPORT OF:	
PERFORM REMEDIAL WORK		EDIAL WORK	☐ ALTERING CASING	
TEMPORARILY ABANDON [☐ CHANGE PLANS ☐ COM	MENCE DRILLING OPN	S. PANDA	
PULL OR ALTER CASING	☐ MULTIPLE COMPL ☐ CAS	NG/CEMENT JOB		
DOWNHOLE COMMINGLE [
OTHER:	□ отн	ER: Spud and surface ca	asing	\bowtie
	mpleted operations. (Clearly state all pertine		ent dates, including estimate	
13. Describe proposed or cor of starting any proposed	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For	nt details, and give pertin	ent dates, including estimate	
13. Describe proposed or co	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For	nt details, and give pertin	ent dates, including estimate	
13. Describe proposed or cor of starting any proposed proposed completion or	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion.	nt details, and give pertin Multiple Completions: A	ent dates, including estimate Attach wellbore diagram of	
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12:	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented von PM.	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su	ent dates, including estimate Attach wellbore diagram of urface.	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented volume of 20 at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailor	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good.	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v. 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tails ested casing to 1200 psi for 30 min, good.	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or co- of starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx PI 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good.	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement	ent dates, including estimate Attach wellbore diagram of urface. ted with 780 sx Class "C" +	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12:4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented v 00 PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good.	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement in with 200 sx Class "C	ent dates, including estimate Attach wellbore diagram of arface. The second of the se	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12:4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented voo PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good. Rig Release Date:	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement in with 200 sx Class "C	ent dates, including estimate Attach wellbore diagram of arface. The second of the se	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12:4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented voo PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good. Rig Release Date:	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement in with 200 sx Class "Completions of the completion o	ent dates, including estimate Attach wellbore diagram of arface. ted with 780 sx Class "C" + C" Neat cement (yld 1.33, w	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12:4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. T	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented voo PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed rested casing to 1200 psi for 30 min, good. Rig Release Date:	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement in with 200 sx Class "Completions of the completion o	ent dates, including estimate Attach wellbore diagram of arface. The second of the se	ed date
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. Thereby certify that the information of the start o	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented von PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed ested casing to 1200 psi for 30 min, good. Rig Release Date: TITLE Regulatory	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement of in with 200 sx Class "Compliance Supervisor."	ent dates, including estimate Attach wellbore diagram of arface. ted with 780 sx Class "C" + C" Neat cement (yld 1.33, w	2% t
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. The spud Date: Spud Date: 4/17 I hereby certify that the information of the start of th	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented von PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed ested casing to 1200 psi for 30 min, good. Rig Release Date: TITLE Regulatory Huerta E-mail address: tinah@y	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement of in with 200 sx Class "Compliance Supervisor atespetroleum.com"	ent dates, including estimate Attach wellbore diagram of Attach wellbore diagram of arface. The second sec	2% t
13. Describe proposed or coof starting any proposed proposed completion or 4/17/13 – Spudded well at 8:00 A 4/22/13 – Resumed drilling at 12: 4/24/13 – TD 17-1/2" hole to 189 PF001 + 4% PF20 + 0.125#/sx Pl 14.8). Circulated 258 sx to pit. Thereby certify that the information of the start o	mpleted operations. (Clearly state all pertine work). SEE RULE 19.15.7.14 NMAC. For recompletion. M. Set 80' of 20" conductor and cemented von PM. 2' at 12:30 PM. Set 13-3/8" 48# J-55 ST&C F29 + 0.4#/sx PF46 (yld 1.98, wt 12.9). Tailed ested casing to 1200 psi for 30 min, good. Rig Release Date: TITLE Regulatory Huerta E-mail address: tinah@y	nt details, and give pertin Multiple Completions: A with 30 yds redi-mix to su casing at 1890'. Cement of in with 200 sx Class "Compliance Supervisor."	ent dates, including estimate Attach wellbore diagram of Attach wellbore diagram of arface. Ted with 780 sx Class "C" + C" Neat cement (yld 1.33, w	2% t