State of New Mexico Energy Minerals and Natural Resources

Form C-144 CLEZ July 21, 2008

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240

District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

Department

For closed-loop systems that only use above ground steel tanks or haut-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.

y 3/PAFIAFA	
Closed-Loop System	n Permit or Closure Plan Application
	haul-off bins and propose to implement waste removal for closure)
Type of	action: Permit Closure
	per individual closed-loop system request. For any application request other than for a off bins and propose to implement waste removal for closure, please submit a Form C-144.
nvironment. Nor does approval relieve the operator of its responsibili	rator of liability should operations result in pollution of surface water, ground water or the ty to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Cimarex Energy Co.	OGRID#: 162683
Address: 600 N. Marienfeld St., Ste. 600; Midland, TX 79701	
Facility or well name: Mescalero 30 Federal 6	
	OCD Permit Number: P1-86273
U/L or Qtr/Qtr F Section 30 Township 19S R	
Center of Proposed Design: Latitude 32° 37' 29.20"	Longitude <u>103° 35′ 52.84</u> NAD: □1927 ⊠ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust of	r Indian Allotment
2.    Closed-loop System: Subsection H of 19.15.17.11 NMAC   Operation: Drilling a new well   Workover or Drilling (App   Above Ground Steel Tanks or   Haul-off Bins	plies to activities which require prior approval of a permit or notice of intent)
3.	
Signs: Subsection C of 19.15.17.11 NMAC	n, and antigramati talanhana munhaga
☐ 12"x 24", 2" lettering, providing Operator's name, site locatio Signed in compliance with 19.15.3.103 NMAC	n, and emergency telephone numbers
organical in compinance with 17.13.3.103 Taking	
<ul> <li>attached.</li> <li>Design Plan - based upon the appropriate requirements of I</li> <li>Operating and Maintenance Plan - based upon the appropri</li> </ul>	e application. Please indicate, by a check mark in the box, that the documents are
	I Number:
	T Number:
s. Waste Removal Closure For Closed-loop Systems That Utilize	Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC)  posal of liquids, drilling fluids and drill cuttings. Use attachment if more than two
Disposal Facility Name: CRY R36D	Disposal Facility Permit Number: 12-9166 WM-DI-DOC
Disposal Facility Name:	Disposal Facility Permit Number:
	ciated activities occur on or in areas that will not be used for future service and operations?
Required for impacted areas which will not be used for future ser  Soil Backfill and Cover Design Specifications based upo Re-vegetation Plan - based upon the appropriate requireme Site Reclamation Plan - based upon the appropriate require	on the appropriate requirements of Subsection H of 19.15.17.13 NMAC nts of Subsection I of 19.15.17.13 NMAC
6. Operator Application Certification:	
	on is true, accurate and complete to the best of my knowledge and belief

Chloe Alexander

e-mail address: <u>cdalexander@cimarex.com</u>

Name (Print):

Signature:

Title: Regulatory Admin Assistant

Date: 5.23.2013

7. OCD Approval: Permit Application (including closure plan) Closure Plan (only)		
OCD Representative Signature:	Approval Date -23-2013	
Title:	Approval Date 5-23-2013  OCD Permit Number: P1-D6273	
8.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.  The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:		
9. <u>Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:</u> Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.		
Disposal Facility Name:	Disposal Facility Permit Number:	
Disposal Facility Name:	Disposal Facility Permit Number:	
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?  Yes (If yes, please demonstrate compliance to the items below)  No		
Required for impacted areas which will not be used for future service and operations:  Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique		
Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	

# Cimarex Energy Co. of Colorado - Closed-Loop System Design Plan

- Equipment List Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 or 2 Centrifuges (depending on well depth)

- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

# **Operation and Maintenance**

The Cimarex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

## Closure Plan

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).



# Closed Loop with Drying Auger and Dewatering System

