

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

HOBBS OCD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

MAY 22 2013

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-41121
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-3900/VB-1384
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Belfast BSL State Com
4. Well Location Unit Letter Lot 13 : 2750 feet from the South line and 660 feet from the West line Unit Letter Lot 4 : 330 feet from the North line and 660 feet from the West line Section 6 Township 21S Range 34E NMPM Lea County		8. Well Number 1Y
		9. OGRID Number 025575
		10. Pool name or Wildcat Berry; Bone Spring, North
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3740'GR		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/29/13 - TD 12-1/4" hole to 5868'.

4/30/13 - Set 9-5/8" 36#, 40# HCK-55 J-55 LT&C casing at 5868'. Cemented stage 1 with 380 sx 35:65 Poz "C" + 0.2% PF13 + 6% PF20 + 0.125#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx PF46 (yld 1.92, wt 12.9). Tailed in with 200 sx Class "C" + 0.2% PF13 (yld 1.33, wt 14.8). Cemented stage 2 with 1295 sx 35:65 Poz "C" + 0.2% PF13 + 6% PF20 + 0.125#/sx PF29 + 3#/sx PF42 + 5% PF44 + 0.25#/sx PF46 (yld 1.92, wt 12.9). Tailed in with 100 sx Class "C" + 0.2% PF13 (yld 1.33, wt 14.8). Circulated 351 sx to pit. Tested casing to 1500 psi for 30 min, good. WOC 38 hrs 15 min. Reduced hole to 8-3/4" and resumed drilling.


Spud Date:

4/17/13

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

Regulatory Compliance Supervisor

DATE

May 16, 2013

Type or print name

Tina Huerta

E-mail address:

tinah@yatespetroleum.com

PHONE:

575-748-4168

For State Use Only

APPROVED BY:



TITLE

Petroleum Engineer

DATE

MAY 30 2013

Conditions of Approval (if any):

MAY 30 2013