

HOBBS OCD

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

JUN 25 2013
 State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

RECEIVED
 OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-041-20950
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Marshall & Winston Inc.		6. State Oil & Gas Lease No.
3. Address of Operator POB 50880, Midland, TX 79710-0880		7. Lease Name or Unit Agreement Name Hometown 13
4. Well Location Unit Letter M : 380 feet from the south line and 330 feet from the west line Section 13 Township 6 S Range 34 E NMPM 23 County Roosevelt		8. Well Number 1H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4292' GR		9. OGRID Number 14187
		10. Pool name or Wildcat Kizer San Andres

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: Intent to P&A, ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

THE 9.625" surface casing is set at ³⁴²²4322', with cement circulated to surface. A 5.5" string was run from TD of 8600' to surface with cement circulated to surface and included the pilot hole. Each plug shall have 9.5ppg salt gel mud laden fluid placed to fill void between plugs.

Plug No.01: ¹²⁵530 sx from ^{4200'}8600' to 100' above shoe to 3200', WOC & Tag.
 Plug No.02: 30 sx, 100' min., Anhydrite Plug from 1925' to 1820'. WOC & Tag.
 Plug No.03: 60' surface plug. WOC.

Attachments: Hole Schematics, (I.e. Before and After) and a

Spud Date: 05/20/2012

Rig Release Date: 06/15/2012

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vernon D. Dyer Agent (Marshall & Winston) TITLE Vdyeroil@cableone.net DATE 06/17/2013
 Type or print name Vernon D. Dyer E-mail address: Vdyeroil@cableone.net PHONE: (505) 420-0355
 For State Use Only

APPROVED BY: Mary E. Brown TITLE Compliance Officer DATE 6/27/2013
 Conditions of Approval (if any)

Oil Conservation Division - Hobbs office: **Must be Notified 24 hours prior** to the beginning of Plugging Operations begin.

JUN 27 2013

Plugging Schematic, before and after

Hometown 13 #1H 20-041-20950

Sec 13-M, T-6-S, R-34-E, Rosebud, Co. 4, NM

Marshall + Winston Inc - Operator

