

OCD Hobbs
HOBBS OCD

13-37

Form 3160-3
(February 2005)

JUL 23 2013

FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NM 14492
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name ---
2. Name of Operator BTA Oil Producers, LLC		7. If Unit or CA Agreement, Name and No. ---
3a. Address 104 S. Pecos Midland, TX 79701	3b. Phone No. (include area code) (432) 682-3753	8. Lease Name and Well No. 8105 JV-H Mesa #3H
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 265' FSL & 205' FWL SWSW Sec. 1 At proposed prod. zone 330' FNL & 430' FWL NWNW Sec. 1		9. API Well No. 30-025-41290
10. Field and Pool, or Exploratory Jennings; Upper Bone Spring Shale		11. Sec., T. R. M. or Blk. and Survey or Area Sec. 1, T26S-R32E
12. Distance in miles and direction from nearest town or post office* 25 miles west from Jal, NM		12. County or Parish Lea
13. State NM		
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 205'	16. No. of acres in lease 1960	17. Spacing Unit dedicated to this well 160 acres
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 11314' BHL to BHL	19. Proposed Depth 14,119' MD 9,540' TVD	20. BLM/BIA Bond No. on file NM1195 NMB000849
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3280' GL	22. Approximate date work will start* 06/15/2013	23. Estimated duration 45 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the BLM.

25. Signature <i>Pam Inskeep</i>	Name (Printed/Typed) Pam Inskeep	Date 01/02/2013
----------------------------------	-------------------------------------	--------------------

Title
Regulatory Administrator

Approved by (Signature) */s/George MacDonell*

Name (Printed/Typed)

Date JUL 16 2013

Title
FIELD MANAGER

Office

CARLSBAD FIELD OFFICE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on page 2)

Carlsbad Controlled Water Basin

OPERATOR WILL BE USING A CLOSED-LOOP SYSTEM

Approval Subject to General Requirements
& Special Stipulations Attached

Ks
07/26/13

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

JUL 31 2013

APPLICATION FOR DRILLING

HOBBS OCD

BTA OIL PRODUCERS, LLC

8105 JV-P Mesa #3H

265' FSL & 205' FWL

JUL 23 2013

UL -M-, Sec. 1, T26S, R32E Surface

330' FNL & 430' FWL

RECEIVED

UL -D-, Sec. 1, T26S, R32E Bottom

Lea County, New Mexico

In conjunction with Form 3160-3, Application for Permit to Drill, BTA Oil Producers submits the following 10 items for pertinent information in accordance with BLM requirements:

1. Geologic surface formation is Quaternary.
2. Top of geologic markers & depths of anticipated fresh water, oil or gas:

Anhydrite	708'	
Top of Salt	1,348'	
Base of Salt	4,438'	
Delaware	4,698'	Oil
Bell Canyon	4,738'	Oil
Cherry Canyon	5,958'	Oil
Brushy Canyon	7,248'	Oil
Bone Spring	8,913'	Oil
Avalon Target 1	9,618'	Oil

No other formations are expected to yield oil, gas, or fresh water in measurable volumes. Depth to fresh water, in this area, is 175'. The surface fresh water sands will be protected by setting 13-3/8" csg at 750' cemented back to surface.

All shows of fresh water and minerals will be reported and protected. A sample will be taken of any water flows and furnished to the BLM, Division of Minerals. All oil and gas shows will be adequately tested for commercial possibilities, reported and protected.

3. Proposed Casing and Cementing Program:

<u>Hole Size</u>	<u>OD Casing</u>	<u>Setting From</u>	<u>Depth to</u>	<u>Weight</u>	<u>Grade</u>	<u>Joint</u>
17-1/2"	13-3/8"	0'	750' 780'	54.5#	J55	STC
12-1/4"	9-5/8"	0'	4,650'	40#	J55	LTC
8-3/4"	5-1/2"	0'	14,119'	20#	P110	LTC

Minimum Casing Design Factors:

Collapse	1.125
Burst	1.0
Tensile	1.8

Depending upon availability at the time that the casing is run, equivalent weights and grades may be substituted. All casing will be new.

JUL 23 2013

RECEIVED

4. Cement Program:

I. Surface Casing:

- Lead: 500 sx ExtendaCem-CZ.
 - Yield 1.68 ft³/sk
- Tail: 340 sx HalCem – C with 2% Calcium Chloride.
 - Yield 1.35 ft³/sk
- Cement circulated to surface. 100% Excess.

II. Intermediate Casing:

- Lead: 1,320 sx EconoCem – HCL with 5 lbm/sk Kol-Seal and 5% Salt.
 - Yield 1.89 ft³/sk
- Tail: 250 sx HalCem – C.
 - Yield 1.33 ft³/sk
- Cement circulated to surface. 100% excess.

III. Production Casing:

- Lead: 1,730 sx VersaCem – PBSH2 with 0.5% Halad (R)-344, 0.3% CFR-3, 1 lbm/sk Salt, 0.4% HR-601.
 - Yield 1.61 ft³/sk
- Tail: 485 sx SoluCem – H with 0.25 lbm/sk D-Air 5000, 0.75% HR-601.
 - Yield 2.63 ft³/sk.
 - Weight 15.0 lbm/gal.
 - Top of Tail Cement: 9,574' MD.
- Cement calculated to tie back 500 ft into intermediate casing. 50% Excess above KOP, 10% excess TD to KOP.

Note: All casing strings will be pressure tested to 0.22 psi/ft. of setting depth or 1500 psi (whichever is greater) after cementing and prior to drillout.

5. Pressure Control Equipment:

The 13-5/8" blowout preventer equipment (BOP) shown in Exhibit A will consist of a (5M system) double ram type (5000 psi WP) preventor and a bag-type (Hydril) preventor (5000 psi WP). Will be hydraulically operated and the ram type preventor will be equipped with blind rams on top and 4-1/2" drill pipe rams on bottom. The BOP's will be installed on the 13-3/8" casing and utilized continuously until TD is reached. All BOP's and associated equipment will be tested as per BLM drilling Operations Order No. 2.

Pipe rams will be operated and checked each 24-hour period and each time the drill pipe is out of the hole. These functional tests will be documented on the daily driller's log. A 2" kill line and 3" choke line will be incorporated in the drilling spool below the ram-type BOP. Other accessory BOP equipment will include a Kelly cock, floor safety valve, choke lines, and choke manifold having a 5000 psi WP rating.

Drilling Plan
8105 JV-P Mesa #3H

JUL 23 2013

RECEIVED

6. Mud Program:

See CWA
Surface to 750'^{780'}: 8.5 to 8.8 ppg fresh water spud with 35 to 45 sec/1000 cc viscosity.
750' to 4,650': Brine water. Will use lime for pH control in range 10 to 11. Will sweep hole with gel slugs as required for hole cleaning. Mud wt = 10 ppg.
4,650' to TD: 8.6 to 9.2 ppg controlled brine water. Will use lime for pH control in range of 10 to 11. Will sweep hole with salt gel slugs and polymer sweeps as required for hole cleaning.

Will use paper for seepage losses. Will adjust fluid weight as required using brine water.

7. Auxiliary Equipment:

- a) Upper Kelly cock valve with handle available.
- b) Lower Kelly cock valve with handle available.
- c) Safety valves and subs to fit all drill string connections in use.
- d) Monitoring of mud system will be mechanical.

8. Testing Logging and Coring Program:

Drill Stem Tests will be based on geological sample shows.

Open electrical logging program will be:

- i. KOP (9,035') to Surface: Gamma Ray/Compensated Neutron
- ii. KOP to Intermediate Csg: Dual Laterolog, Gamma Ray, Compensated Neutron, Density.
- iii. No coring program is planned.
- iv. Tie in GR and Gyro from KOP (9,035') to Surface. GR from 9,035' to TD. 10' samples from surface csg to TD.

Specific intervals will be targeted based on evaluation and geological sample shows.

9. Potential Hazards:

No abnormal pressures or temperatures are anticipated. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Estimated BHP: 4,130 psi. Estimated BHT: 170° F. No H₂S is anticipated to be encountered.

10. Anticipated Starting Date and Duration of Operations:

Anticipated start date will be as soon as possible after BLM approval and as soon as a rig is available. Move in operations and drilling is expected to take 45 days.

Note: BLM onsite was conducted on 10/12/2012. Trishia Bad Bear was the representative present for the consultation meeting with the surveying crew, BTA Drilling Manager Nick Eaton, and Consultant Vern Dyer.

HOBBS OCD

JUL 23 2013

RECEIVED

BTA Oil Producers


Lea County, NM
Sec 1, T26S, R32E
8105 JV-P Mesa #3H

Wellbore #1

Plan: Design #1

DDC Well Planning Report

14 November, 2012



DDC

Well Planning Report



Database: EDM 5000.1 Single User Db
Company: BTA Oil Producers
Project: Lea County, NM
Site: Sec 1, T26S, R32E
Well: 8105 JV-P Mesa
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well 8105 JV-P Mesa
TVD Reference: WELL @ 3280.0usft (Original Well Elev)
MD Reference: WELL @ 3280.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

HOBBS OCD

JUL 23 2013

Project	Lea County, NM	System Datum:	Mean Sea Level
Map System:	US State Plane 1927 (Exact solution)		
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

RECEIVED

Site	Sec 1, T26S, R32E
Site Position:	
From:	Map
Position Uncertainty:	0.0 usft
Northing:	388,292.70 usft
Easting:	716,059.40 usft
Slot Radius:	13-3/16 "
Latitude:	32° 3' 56.206 N
Longitude:	103° 38' 9.118 W
Grid Convergence:	0.37 °

Well	8105 JV-P Mesa
Well Position	
+N/-S	0.0 usft
+E/-W	0.0 usft
Position Uncertainty	0.0 usft
Northing:	388,292.70 usft
Easting:	716,059.40 usft
Wellhead Elevation:	
Latitude:	32° 3' 56.206 N
Longitude:	103° 38' 9.118 W
Ground Level:	3,280.0 usft

Wellbore	Wellbore #1
Magnetics	
Model Name	IGRF2010
Sample Date	11/14/2012
Declination (°)	7.43
Dip Angle (°)	59.99
Field Strength (nT)	48,373

Design	Design #1
Audit Notes:	
Version:	
Phase:	PLAN
Tie On Depth:	0.0
Vertical Section:	
Depth From (TVD) (usft)	0.0
+N/-S (usft)	0.0
+E/-W (usft)	0.0
Direction (°)	1.14

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
9,035.0	0.00	0.00	9,035.0	0.0	0.0	0.00	0.00	0.00	0.00	
9,576.7	65.00	30.00	9,467.7	238.7	137.8	12.00	12.00	0.00	30.00	
9,905.5	90.00	358.42	9,540.1	544.3	210.7	12.00	7.60	-9.60	-55.49	
14,119.7	90.00	358.42	9,540.0	4,756.9	94.5	0.00	0.00	0.00	0.00	PBHL 8105 JV-P M

DDC

Well Planning Report



Database: EDM 5000.1 Single User Db
Company: BTA Oil Producers
Project: Lea County, NM
Site: Sec 1, T26S, R32E
Well: 8105 JV-P Mesa
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well 8105 JV-P Mesa
TVD Reference: WELL @ 3280.0usft (Original Well Elev)
MD Reference: WELL @ 3280.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

HOBBS OGD

JUL 23 2013

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
Build 12° / 100									
9,035.0	0.00	0.00	9,035.0	0.0	0.0	0.0	0.00	0.00	0.00
9,050.0	1.80	30.00	9,050.0	0.2	0.1	0.2	12.00	12.00	0.00
9,075.0	4.80	30.00	9,075.0	1.5	0.8	1.5	12.00	12.00	0.00
9,100.0	7.80	30.00	9,099.8	3.8	2.2	3.9	12.00	12.00	0.00
9,125.0	10.80	30.00	9,124.5	7.3	4.2	7.4	12.00	12.00	0.00
9,150.0	13.80	30.00	9,148.9	11.9	6.9	12.1	12.00	12.00	0.00
9,175.0	16.80	30.00	9,173.0	17.6	10.2	17.8	12.00	12.00	0.00
9,200.0	19.80	30.00	9,196.7	24.4	14.1	24.7	12.00	12.00	0.00
9,225.0	22.80	30.00	9,220.0	32.3	18.7	32.7	12.00	12.00	0.00
9,250.0	25.80	30.00	9,242.8	41.2	23.8	41.7	12.00	12.00	0.00
9,275.0	28.80	30.00	9,265.0	51.1	29.5	51.7	12.00	12.00	0.00
9,300.0	31.80	30.00	9,286.6	62.1	35.8	62.8	12.00	12.00	0.00
9,325.0	34.80	30.00	9,307.5	74.0	42.7	74.8	12.00	12.00	0.00
9,350.0	37.80	30.00	9,327.6	86.8	50.1	87.7	12.00	12.00	0.00
9,375.0	40.80	30.00	9,347.0	100.5	58.0	101.6	12.00	12.00	0.00
9,400.0	43.80	30.00	9,365.5	115.1	66.4	116.3	12.00	12.00	0.00
9,425.0	46.80	30.00	9,383.1	130.4	75.3	131.9	12.00	12.00	0.00
9,450.0	49.80	30.00	9,399.7	146.6	84.6	148.3	12.00	12.00	0.00
9,475.0	52.80	30.00	9,415.3	163.5	94.4	165.3	12.00	12.00	0.00
9,500.0	55.80	30.00	9,429.9	181.1	104.5	183.1	12.00	12.00	0.00
9,525.0	58.80	30.00	9,443.4	199.3	115.1	201.5	12.00	12.00	0.00
9,550.0	61.80	30.00	9,455.8	218.1	125.9	220.6	12.00	12.00	0.00
Build & Turn 12° / 100									
9,576.7	65.00	30.00	9,467.7	238.7	137.8	241.4	12.00	12.00	0.00
9,600.0	66.61	27.49	9,477.3	257.4	148.1	260.3	12.00	6.89	-10.77
9,625.0	68.37	24.86	9,486.9	278.1	158.3	281.2	12.00	7.06	-10.50
9,650.0	70.18	22.30	9,495.7	299.6	167.6	302.8	12.00	7.22	-10.25
9,675.0	72.02	19.80	9,503.8	321.6	176.1	325.1	12.00	7.37	-10.01
9,700.0	73.89	17.34	9,511.1	344.3	183.7	347.9	12.00	7.49	-9.81
9,725.0	75.79	14.94	9,517.7	367.5	190.4	371.2	12.00	7.60	-9.62
9,750.0	77.72	12.57	9,523.4	391.1	196.2	394.9	12.00	7.70	-9.46
9,775.0	79.66	10.24	9,528.3	415.1	201.0	419.0	12.00	7.78	-9.32
9,800.0	81.62	7.94	9,532.4	439.5	204.9	443.5	12.00	7.84	-9.21
9,825.0	83.59	5.66	9,535.6	464.1	207.9	468.1	12.00	7.89	-9.11
9,850.0	85.58	3.40	9,538.0	488.9	209.8	493.0	12.00	7.93	-9.04
9,875.0	87.57	1.15	9,539.4	513.8	210.8	517.9	12.00	7.96	-8.99
9,900.0	89.56	358.91	9,540.1	538.8	210.8	542.9	12.00	7.98	-8.97
EOC @ 90° Inc / 358.42° Azm / 9540' TVD									
9,905.5	90.00	358.42	9,540.1	544.3	210.7	548.4	12.00	7.98	-8.96
10,000.0	90.00	358.42	9,540.1	638.8	208.1	642.8	0.00	0.00	0.00
10,100.0	90.00	358.42	9,540.1	738.7	205.3	742.7	0.00	0.00	0.00
10,200.0	90.00	358.42	9,540.1	838.7	202.6	842.6	0.00	0.00	0.00
10,300.0	90.00	358.42	9,540.1	938.7	199.8	942.5	0.00	0.00	0.00
10,400.0	90.00	358.42	9,540.1	1,038.6	197.1	1,042.3	0.00	0.00	0.00
10,500.0	90.00	358.42	9,540.1	1,138.6	194.3	1,142.2	0.00	0.00	0.00
10,600.0	90.00	358.42	9,540.1	1,238.6	191.6	1,242.1	0.00	0.00	0.00
10,700.0	90.00	358.42	9,540.1	1,338.5	188.8	1,342.0	0.00	0.00	0.00
10,800.0	90.00	358.42	9,540.1	1,438.5	186.0	1,441.9	0.00	0.00	0.00
10,900.0	90.00	358.42	9,540.1	1,538.4	183.3	1,541.8	0.00	0.00	0.00
11,000.0	90.00	358.42	9,540.1	1,638.4	180.5	1,641.7	0.00	0.00	0.00
11,100.0	90.00	358.42	9,540.1	1,738.4	177.8	1,741.6	0.00	0.00	0.00
11,200.0	90.00	358.42	9,540.1	1,838.3	175.0	1,841.4	0.00	0.00	0.00

RECEIVED

DDC

Well Planning Report



Database: EDM 5000.1 Single User Db
Company: BTA Oil Producers
Project: Lea County, NM
Site: Sec 1, T26S, R32E
Well: 8105 JV-P Mesa
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well 8105 JV-P Mesa
TVD Reference: WELL @ 3280.0usft (Original Well Elev)
MD Reference: WELL @ 3280.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

JUL 23 2013

Planned Survey

RECEIVED

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
11,300.0	90.00	358.42	9,540.1	1,938.3	172.3	1,941.3	0.00	0.00	0.00
11,400.0	90.00	358.42	9,540.1	2,038.3	169.5	2,041.2	0.00	0.00	0.00
11,500.0	90.00	358.42	9,540.1	2,138.2	166.7	2,141.1	0.00	0.00	0.00
11,600.0	90.00	358.42	9,540.1	2,238.2	164.0	2,241.0	0.00	0.00	0.00
11,700.0	90.00	358.42	9,540.1	2,338.1	161.2	2,340.9	0.00	0.00	0.00
11,800.0	90.00	358.42	9,540.1	2,438.1	158.5	2,440.8	0.00	0.00	0.00
11,900.0	90.00	358.42	9,540.0	2,538.1	155.7	2,540.7	0.00	0.00	0.00
12,000.0	90.00	358.42	9,540.0	2,638.0	153.0	2,640.5	0.00	0.00	0.00
12,100.0	90.00	358.42	9,540.0	2,738.0	150.2	2,740.4	0.00	0.00	0.00
12,200.0	90.00	358.42	9,540.0	2,838.0	147.4	2,840.3	0.00	0.00	0.00
12,300.0	90.00	358.42	9,540.0	2,937.9	144.7	2,940.2	0.00	0.00	0.00
12,400.0	90.00	358.42	9,540.0	3,037.9	141.9	3,040.1	0.00	0.00	0.00
12,500.0	90.00	358.42	9,540.0	3,137.8	139.2	3,140.0	0.00	0.00	0.00
12,600.0	90.00	358.42	9,540.0	3,237.8	136.4	3,239.9	0.00	0.00	0.00
12,700.0	90.00	358.42	9,540.0	3,337.8	133.6	3,339.8	0.00	0.00	0.00
12,800.0	90.00	358.42	9,540.0	3,437.7	130.9	3,439.6	0.00	0.00	0.00
12,900.0	90.00	358.42	9,540.0	3,537.7	128.1	3,539.5	0.00	0.00	0.00
13,000.0	90.00	358.42	9,540.0	3,637.6	125.4	3,639.4	0.00	0.00	0.00
13,100.0	90.00	358.42	9,540.0	3,737.6	122.6	3,739.3	0.00	0.00	0.00
13,200.0	90.00	358.42	9,540.0	3,837.6	119.9	3,839.2	0.00	0.00	0.00
13,300.0	90.00	358.42	9,540.0	3,937.5	117.1	3,939.1	0.00	0.00	0.00
13,400.0	90.00	358.42	9,540.0	4,037.5	114.3	4,039.0	0.00	0.00	0.00
13,500.0	90.00	358.42	9,540.0	4,137.5	111.6	4,138.9	0.00	0.00	0.00
13,600.0	90.00	358.42	9,540.0	4,237.4	108.8	4,238.7	0.00	0.00	0.00
13,700.0	90.00	358.42	9,540.0	4,337.4	106.1	4,338.6	0.00	0.00	0.00
13,800.0	90.00	358.42	9,540.0	4,437.3	103.3	4,438.5	0.00	0.00	0.00
13,900.0	90.00	358.42	9,540.0	4,537.3	100.6	4,538.4	0.00	0.00	0.00
14,000.0	90.00	358.42	9,540.0	4,637.3	97.8	4,638.3	0.00	0.00	0.00
14,100.0	90.00	358.42	9,540.0	4,737.2	95.0	4,738.2	0.00	0.00	0.00
14,119.7	90.00	358.42	9,540.0	4,756.9	94.5	4,757.8	0.00	0.00	0.00

Design Targets

Target Name

- hit/miss target	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- Shape									
PBHL 8105 JV-P ME	0.00	0.00	9,540.0	4,756.9	94.5	393,049.60	716,153.90	32° 4' 43.273 N	103° 38' 7.662 W
- plan hits target center									
- Point									

Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
9,035.0	9,035.0	0.0	0.0	Build 12° / 100
9,576.7	9,467.7	238.7	137.8	Build & Turn 12° / 100
9,905.5	9,540.1	544.3	210.7	EOC @ 90° Inc / 358.42° Azm / 9540' TVD
14,119.7	9,540.0	4,756.9	94.5	TD @ 14120' MD / 9540' TVD


BTA Oil Producers, LLC

Lea County, NM

8105 JV-P Mesa #3H

Quote 120862

Design #1




The DIRECTIONAL DRILLING COMPANY

HOBBS, NM

JUL 23 2013

RECEIVED



BTA Oil Producers, LLC

Lea County, NM

8105 JV-P Mesa #3H



Quote 120862

Design #1

HOBBS OCD

JUL 23 2013

RECEIVED




Vertical Section at 1.14° (700 usft/in)

JUL 23 2013

RECEIVED

13-5/8" 5,000 PSI BOP

**BTA Oil Producers LLC**


8105 JV-P Mesa #3-H

265' FSL 205' FWL

1, 26S, 32E

Lea County, NM

To Steel Pits



SM CHOKE MANIFOLD EQUIPMENT


BTA Oil Producers LLC
8105 JV-P Mesa #3-H
265' FSL 205' FWL
1, 26S, 32E
Lea County, NM

HOBBS OCD

JUL 23 2013

RECEIVED

BTA Oil Producers LLC
8105 JV-P Mesa #3-H
265' FSL 205' FWL
1, 26S, 32E
Lea County, NM




Proposed Production Facility Layout

HOBBS OCD

JUL 23 2013



RECEIVED



Interim Reclamation

BTA

BTA Oil Producers, LLC
(Midland, Texas)

BTA JV-P 8105, Mesa #3H Facility Drawing

Revision

Unit Letter "M", Section 1, Township 26 North, Range 32 East
Lea County, New Mexico

0

06/14/2013

Scale: None
Drawn by: jeb

Date: 06/14/2013
Checked by: jeb

NOT DRAWN TO SCALE