

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

HOBBS OCD

AUG 01 2013

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.
30-025-35327

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-4826

7. Lease Name or Unit Agreement Name
North Papalotes BFP State

8. Well Number
1

9. OGRID Number
025575

10. Pool name or Wildcat
Morton; Permo Upper Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG-BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter A : 990 feet from the North line and 660 feet from the East line
Section 36 Township 14S Range 34E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4064' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Plugback and recomplete ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/2/13 - NU BOP. Released packer.

5/5/13 - RIH with 4.5" GR/JB to 12,600'. Set a 5-1/2" CIBP at 12,545'. Loaded casing with 58 bbls 2% KCL water. Tested to 1000 psi, held good. Made 2 runs with cement bailer to put 35' cement on top of CIBP. Perforated Permo Upper Penn 10,476'-10,530' (38).

5/6/13 - Spotted 5 bbls 15% NEFE acid across perfs. Acidized with 5000g 15% NEFE HCL and 45 ball sealers.

5/8/13 - Set 2-7/8" 6.4# L-80 tubing at 10,610'.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Reporting Supervisor DATE May 31, 2013

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE AUG 05 2013

Conditions of Approval (if any): PA Tres Papalotes Atoka (GAS) AUG 05 2013