

13-719

Form 3160-3
(March 2012)HOBBS OCD
AUG 05 2013

OCD Hobbs

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

RECEIVED


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM055149	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name	
2. Name of Operator OXY USA INC		7. If Unit or CA Agreement, Name and No.	
3a. Address P.O. BOX 4294 HOUSTON, TX 77210		8. Lease Name and Well No. CORBIN SOUTH FEDERAL #1	
3b. Phone No. (include area code) 713-513-6640		9. API Well No. 30-025-41315	
4. Location of Well (Report location clearly and in accordance with any State requirements.) At surface 830' FNL & 400' FWL At proposed prod. zone		10. Field and Pool, or Exploratory CORBIN; WOLFCAMP, SOUTH	
14. Distance in miles and direction from nearest town or post office* 37 MILES SOUTHEAST OF LOVINGTON, NM		11. Sec., T. R. M. or Blk. and Survey or Area D, SEC 9; T18S, R33E	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No. of acres in lease 280	17. Spacing Unit dedicated to this well 80	
18. Distance from proposed location* 400' to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth 11500' MD / 11500' TVD	20. BLM/BIA Bond No. on file ESB000226 / NMB000862	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3950.4' GL	22. Approximate date work will start* 01/02/2014	23. Estimated duration 20 DAYS	
24. Attachments			

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature 	Name (Printed/Typed) Jennifer Duarte (jennifer_duarte@oxy.com)	Date 04/22/2013
Title Regulatory Specialist		
Approved by (Signature) /s/George MacDonell	Name (Printed/Typed)	DATE AUG - 1 2013
Title FIELD MANAGER	Office CARLSBAD FIELD OFFICE	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

Capitan Controlled Water Basin

CONDITION OF APPROVAL: Approval for Drilling ONLY.
CANNOT produce without the OCD Santa Fe approval for
Non-Standard Location.

Approval Subject to General Requirements
& Special Stipulations Attached

AUG 13 2013

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

OXY USA Inc
Corbin South Federal #1
APD Data

OPERATOR NAME / NUMBER: OXY USA Inc

LEASE NAME / NUMBER: Corbin South Federal #1

STATE: NM **COUNTY:** Lea

SURFACE LOCATION: 830' FNL & 400' FWL, Sec 9, T18S, R33E

C-102 PLAT APPROX GR ELEV: 3950.4' **EST KB ELEV:** 3974.4' (24' KB)

1. **GEOLOGIC NAME OF SURFACE FORMATION**
 - a. Permian
2. **ESTIMATED TOPS OF GEOLOGICAL MARKERS & DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS**

Formation Tops	TV Depth To	Expected Fluid
Rustler	1505	--
Salado (T. Salt)	1613	--
Tansill (B. Salt)	2712	--
T. Yates	2970	--
T. Seven Rivers	3440	Poss Oil
T. Queen	4220	Poss Oil
Cherry Canyon	5139	Oil/Gas
Brushy Canyon	5694	Oil/Gas
T. BSPG1 Limestone	6630	Oil/Gas
T. BSPG 1st Sand	8215	Oil/Gas
T. BSPG2 Limestone	8655	Oil/Gas
T. BSPG 2nd Sand	8765	Oil/Gas
T. BSPG3 Limestone	9255	Oil/Gas
T. BSPG 3rd Sand	9415	Oil/Gas
T. Wolfcamp	9715	Oil/Gas
T. WFMP Upper Interval	10704	Oil/Gas
T. WFMP Lower Interval	11230	Oil/Gas
TD	11500	Oil/Gas

Fresh water may be encountered above the Rustler formation. Surface casing will be set below the top of the Rustler to protect it.

GREATEST PROJECTED TD 11500' MD/ 11500' TVD **OBJECTIVE:** Wolfcamp

3. CASING PROGRAM

Surface Casing: 13.375" casing set at ± 1535' MD/1535' TVD in a 17.5" hole filled with 8.90 ppg mud

Interval	Length	Wt	Gr	Cplg	Coll Rating (psi)	Burst Rating (psi)	Jt Str (M-lbs)	ID (in)	Drift (in)	SF Coll	SF Burst	SF Ten
0'- <u>150'</u>	<u>150'</u>											
0'-1535'	1535'	48	H-40	ST&C	770	1730	322	12.715	12.557	1.21	1.66	1.85

Intermediate Casing: 9.625" casing set at 3100' MD / 3100' TVD in a 12.25" hole filled with 10 ppg mud

Interval	Length	Wt	Gr	Cplg	Coll Rating (psi)	Burst Rating (psi)	Jt Str (M-lbs)	ID (in)	Drift (in)	SF Coll	SF Burst	SF Ten
0'- <u>2925'</u>	<u>2925'</u>											
0'-3100'	3100'	36	J-55	LT&C	2020	3520	453	8.84	8.75	1.35	1.29	2.14

Production Casing: 5.5" casing set at $\pm 11500'$ MD / 11500' TVD in a 8.75" hole filled with 9.0 ppg mud

Interval	Length	Wt	Gr	Cplg	Coll Rating (psi)	Burst Rating (psi)	Jt Str (M-lbs)	ID (in)	Drift (in)	SF Coll	SF Burst	SF Ten
0' - 11500'	11500'	17	L-80	BT&C	6290	7740	338	4.892	4.767	1.20	1.43	1.72

Note: All Casing is in new condition

Casing Design Assumptions:

Burst Loads

CSG Test (Surface)

- Internal: Displacement fluid + 70% CSG Burst rating
- External: Pore Pressure from section TD to surface

CSG Test (Intermediate)

- Internal: Displacement fluid + 70% CSG Burst rating
- External: Pore Pressure from the Intermediate hole TD to Surface CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface

CSG Test (Production)

- Internal: Displacement fluid + 80% CSG Burst rating
- External: Pore Pressure from the well TD the Intermediate CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface

Gas Kick (Surface/Intermediate)

- Internal: Gas Kick based on Pore Pressure or Fracture Gradient @ CSG shoe with a gas 0.115psi/ft Gas gradient to surface while drilling the next hole section (e.g. Gas kick while drilling the production hole section is a burst load used to design the intermediate CSG)
- External: Pore Pressure from section TD to previous CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface

Stimulation (Production)

- Internal: Displacement fluid + Max Frac treating pressure (not to exceed 80% CSG Burst rating)
- External: Pore Pressure from the well TD to the Intermediate CSG shoe and 8.5 ppg MWE to surface

Collapse Loads

Lost Circulation (Surface/Intermediate)

- Internal: Losses experienced while drilling the next hole section (e.g. losses while drilling the production hole section are used as a collapse load to design the intermediate CSG). After losses there will be a column of mud inside the CSG with an equivalent weight to the Pore Pressure of the lost circulation zone
- External: MW of the drilling mud that was in the hole when the CSG was run

Cementing (Surface/Intermediate/Production)

- Internal: Displacement Fluid
- External: Cement Slurries to TOC, MW to surface

Full Evacuation (Production)

- Internal: Atmospheric Pressure
- External: MW of the drilling mud that was in the hole when the CSG was run

Tension Loads

Running CSG (Surface/Intermediate/Production)

- Axial load of the buoyant weight of the string plus either 100 klb over-pull or string weight in air, whichever is less

Green Cement (Surface/Intermediate/Production)

- Axial load of the buoyant weight of the string plus the cement plug bump pressure (Final displacement + 500 psi)

Burst, Collapse and Tensile SF are calculated using Landmark's Stress Check (Casing Design) software.

4. CEMENT PROGRAM:

Surface Interval

Interval	Amount sx	Ft of Fill	Type	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Surface (TOC: 0' - 1535') <i>see COA</i>							
Lead: 0' - 1408' (165% Excess)	1520	1408	Premium Plus cement with 2% Calcium Chloride, 4% Bentonite, 0.125 lbm/sk Poly-E-Flake	9.18	13.5	1.75	589 psi
Tail: 1408' - 1535' (165 % Excess)	200	127	Premium Plus cement with 94 lbm/sk Premium Plus Cement, 2% Calcium Chloride	6.39	14.80	1.35	1608 psi

Intermediate Interval

Interval	Amount sx	Ft of Fill	Type	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Intermediate (TOC: 0' - 3100') <i>see COA</i>							
Lead: 0' - 2710' (105% Excess)	880	2710'	Light Premium Plus Cement, with 5% Salt, 3lb-sk Kol Seal, 0.125 lb/sk Poly-E-Flake	9.68	12.9	1.87	840 psi
Tail: 2710' - 3100' (105 % Excess)	200	390'	Premium Plus cement with 1% Calcium Chloride	6.36	14.80	1.34	2125 psi

Production Interval

Interval	Amount sx	Ft of Fill	Type	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Production (TOC: 2600' - 11500') <i>see COA</i> Single Stage							
Lead: 2600' - 6800' (100% Excess)	800	4200'	Premium Cement, 14.8 lb/sk Silicalite 50/50 Blend, 16 lb/sk Schotchlite HGS-6000, 2 lb/sk Kol-Seal, 0.5 lb/sk CFR-3, 0.15 lb/sk WG-17, 1 lb/sk Cal-Seal 60, 1.5 lb/sk Salt.	9.79	10.80	2.39	520 psi
Tail: 6800' - 11500' (50% Excess)	990	4700'	Super H Cement, 3 lbm/sk Kol-Seal, 3 lbm/sk Salt, 0.125 lbm/sk Poly-E-Flake, 0.2 % and HR-601, & 0.5% Halad-344, 0.4% CFR 3.	8.40	13.2	1.66	1750 psi

Cement Additives: *Bentonite (light weight additive), Calcium Chloride (accelerator), Halad-344 (low fluid loss control), HR-601 (retarder), Kol-Seal (lost circulation additive), Salt (salt), Poly-E-Flake (lost circulation additive), Silicalite (Additive Material), CFR-3 (Dispersant), Schotchlite HGS 6000 (Light Weight Additive), WG-17 (Gelling Agent), Cal-Seal 60 (Accelerator)

5. PRESSURE CONTROL EQUIPMENT

Surface: 1535'. None.

Intermediate and Production: 3100' -- 11500'. Intermediate and Production hole will be drilled with a 13-5/8" 10M three ram stack with a 5M annular preventer and a 5M Choke Manifold.

- See COA
- All BOP's and associated equipment will be tested in accordance with Onshore Order #2 (250/5000 psi on rams for 10 minutes each and 250/3500 for 10 minutes for annular preventer, equal to 70% of working pressure) with a third party BOP testing service before drilling out the surface casing shoe. A Multibowl wellhead system will be used in this well therefore the BOPE test will cover the test requirements for the Intermediate and Production sections.
 - The Surface and Intermediate casings strings will be tested to 70% of their burst rating for 30 minutes. This will also test the seals of the lock down pins that hold the pack-off in place in the Multibowl wellhead system.
 - Pipe rams will be function tested every 24 hours and blind rams will be tested each time the drill pipe is out of the hole. These functional tests will be documented on the daily driller's log. A 2" kill line and 3" choke line will be accommodated on the drilling spool below the ram-type BOP.
 - The BOPE test will be repeated within 21 days of the original test, on the first trip, if drilling the intermediate or production section takes more time than planned.
 - Other accessory BOP equipment will include a Kelly cock, floor safety valve, choke lines, and choke manifold having a 5000 psi working pressure rating and tested to 5000 psi.
 - The Operator also requests a variance to connect the BOP choke outlet to the choke manifold using a co-flex hose manufactured by Contitech Rubber Industrial KFT. It is a 3" ID x 35' flexible hose with a 10,000 psi working pressure. It has been tested to 15,000 psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps (certifications attached).
 - BOP & Choke manifold diagrams attached.
- See COA

6. MUD PROGRAM:

See COA

Depth	Mud Wt ppg	Vis Sec	Fluid Loss	Type System
0 - 1535' ^{1540'} 1535' ^{2425'}	8.4 - 8.9	32 - 34	NC	Fresh Water /Spud Mud
1535' - 3100'	10.0-10.2	28 - 29	NC	Brine Water
3100' - 8000'	8.6 - 8.8	28 - 29	NC	Fresh Water
8000' - TD'	9.0 - 9.2	40 - 50	8 - 15	Salt Gel/Duo Vis

Remarks: Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times.

Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal isolation.

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT

- A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor unobstructed and readily accessible at all times.

8. POTENTIAL HAZARDS:

- See COA
- H2S detection equipment will be in operation after drilling out the surface casing shoe until the production casing has been cemented. Breathing equipment will be on location from drilling out the surface shoe until production casing is cemented. If H2S is encountered the operator will comply with Onshore Order #6.

- b. No abnormal temperatures or pressures are anticipated. The highest anticipated pressure gradient is 0.46 psi/ft. Maximum anticipated bottom hole pressure is between 5300 and 5400 psi.
- c. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Adequate flare lines will be installed off the mud/gas separator where gas may be flared safely.

9. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS


Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as soon as possible after BLM approval and as soon as a rig will be available. Move in operations and drilling is expected to take 35 days. If production casing is run, then an additional 30 days will be needed to complete the well and construct surface facilities and/or lay flow lines in order to place well on production.

10. WIRELINE LOGGING / MUD LOGGING / LWD

- a. Run wireline – Triple Combo
 - 1. GR, Den, Neu, Res, Sonic from TD to base of intermediate casing.
 - 2. GR, Neutron from TD to surface
- b. Mud loggers to be rigged up from base of intermediate casing to TD

COMPANY PERSONNEL:

<u>Name</u>	<u>Title</u>	<u>Office Phone</u>	<u>Mobile Phone</u>
Carlos Mercado	Drilling Engineer	(713)366-5418	(281) 455-3481
Sebastian Millan	Drilling Engineer Supervisor	(713)350-4950	(832)528-3268
Roger Allen	Drilling Superintendent	(713)215-7617	(281)682-3919
Oscar Quintero	Drilling Manager	(713)985-6343	(713)689-4946



- LEGEND
- (1) 13 5/8 - 10M FLANGED END DATE VALVE
 - (2) 13 5/8 - 10M FLANGED END DATE VALVE WITH 13 5/8 - 10M DATE VALVE
 - (3) 13 5/8 - 10M FLANGED END DATE VALVE
 - (4) 13 5/8 - 10M FLANGED END DATE VALVE
 - (5) 13 5/8 - 10M FLANGED END DATE VALVE

SHAFTER ROLTED-COVER SPHERICAL
ANNULAR PREVENTER, (API 16A
MONOGRAVED, 13 5/8-10M W-3)
10M BOTTOM FLANGE + 3V
STUDDED TOP (WEIGHT = 14,200
LBS WITH SHAFTER API 16A HOT
OIL RESISTANT ACRYLONITRILE
ELEMENT)

CAMERON TWO DISK
RAM-TYPE PREVENTER (API 16A
MONOGRAVED, 13 5/8-10M
W-3) WITH 13 CAMERON PIPE
RAMS (CAMERON FRONT RAMS
+ TOP SEALS) IN TOP RAMS
AND CAMERON 15 SHEARING
BLIND RAMS IN BOTTOM RAMS.
BOTTOM FLANGE + STUDDED
TOP (WEIGHT = 21,100 LBS.
WITH RAMS)

13 5/8 - 10M W-3
CAMERON DRILLING SPONGE
(API 16A MONOGRAVED)
STAGGED TOP + FLANGED BOTTOM
WITH 13 5/8 - 10M W-3 FLANGED OUTLETS
(WEIGHT APPROXIMATELY 8,000 LBS)


SHEARER TWO DISK RAM-TYPE
PREVENTER (API 16A
MONOGRAVED, 13 5/8-10M W-3)
WITH 13 CAMERON PIPE RAMS
(CAMERON FRONT RAMS + TOP
SEALS) BOTTOM FLANGE +
STAGGED TOP
(WEIGHT = 14,200 LBS)

HAP FURNISHED
13 5/8" - 10M x 13 5/8" - 5M
ADAPTER SPOOL 2' - 0" LONG

13 5/8 - 10M BOP STACK WITH 13 5/8 - 5M ANNULAR

PROPRIETARY

THIS DRAWING AND THE LOGS AND INFORMATION PROVIDED
IN THIS DRAWING ARE PROPRIETARY AND ARE NOT TO BE
REPRODUCED, COPIED, OR TRANSMITTED IN ANY MANNER
WITHOUT THE WRITTEN CONSENT OF HELMERICH & PAYNE
INTERNATIONAL DRILLING CO.



ISSUED FOR
FABRICATION
December-18-2007
DRAFTSMAN
ENGINEER

API 16A MONOGRAVED + SHEARER DRIFT AND ROLL
STOP VALVE ELEMENTS ARE NOT SHOWN FOR
CLARITY


WEIGHTS + DIMENSIONS NOTED, ADAPTED FROM
OR CHECK CORRECT FITTING

HELMERICH & PAYNE
INTERNATIONAL DRILLING CO.


13 5/8" - 10M BOP 3 RAM STACK
FLEXRIGS

REV	DATE	DESCRIPTION	BY	CHK
1	12/18/07	ISSUED FOR FABRICATION	JRC	JRC
2	12/18/07	REVISIONS TO DRAWING	JRC	JRC
3	12/18/07	ADDED TO 13 5/8" - 10M BOP STACK	JRC	JRC
4	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
5	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
6	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
7	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
8	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
9	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC
10	12/18/07	ADDED 13 5/8" - 10M BOP STACK	JRC	JRC


FLEX3 STD CHOKE MANIFOLD (COMPREHENSIVE)




10M REMOTE KILL LINE SCHEMATIC




Choke Manifold – Gas Separator (Top View)



Choke Manifold – Gas Separator (Side View)



Gas Separator Routing **Flex III Rigs**





Coflex Hose Certification



Fluid Technology

Quality Document

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE				CERT. N°: 746	
PURCHASER: Phoenix Beattie Co.			P.O. N°: 002491		
CONTITECH ORDER N°: 412638		HOSE TYPE: 3" ID Choke and Kill Hose			
HOSE SERIAL N°: 52777		NOMINAL / ACTUAL LENGTH: 10,67 m			
W.P. 68,96 MPa 10000 psi		T.P. 103,4 MPa 15000 psi		Duration: 60 ~ min.	
Pressure test with water at ambient temperature					
See attachment. (1 page)					
↑ 10 mm = 10 Min. → 10 mm = 25 MPa					
COUPLINGS					
Type	Serial N°		Quality	Heat N°	
3" coupling with 4 1/16" Flange end	917 913		AISI 4130	T7998A	
			AISI 4130	26984	
INFOCHIP INSTALLED				API Spec 16 C Temperature rate: "B"	
All metal parts are flawless					
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.					
Date:	Inspector		Quality Control		
04. April. 2008			 ContiTech Rubber Industrial Kft. Quality Control Dept. (1) 		

Coflex Hose Certification

Form No 100/12

**Phoenix Beattie Corp**

11535 Brittmoore Park Drive
Houston, TX 77041
Tel: (832) 327-0141
Fax: (832) 327-0148
E-mail: mail@phoenixbeattie.com
www.phoenixbeattie.com

Delivery Note

Customer Order Number	370-369-001	Delivery Note Number	003078	Page	1
Customer / Invoice Address HELMERICH & PAYNE INT'L DRILLING CO 1437 SOUTH BOULDER TULSA, OK 74129		Delivery / Address HELMERICH & PAYNE IDC ATTN: JOE STEPHENSON - RIG 370 13609 INDUSTRIAL ROAD HOUSTON, TX 77015			

Customer Acc No	Phoenix Beattie Contract Manager	Phoenix Beattie Reference	Date
H01	JJL	006330	05/23/2008

Item No	Beattie Part Number / Description	Qty Ordered	Qty Sent	Qty To Follow
1	HP10CK3A-35-4F1 3" 10K 16C C&K HOSE x 35ft OAL CW 4.1/16" API SPEC FLANGE E/ End 1: 4.1/16" 10Kpsi API Spec 6A Type 6BX Flange End 2: 4.1/16" 10Kpsi API Spec 6A Type 6BX Flange c/w BX155 Standard ring groove at each end Suitable for H2S Service Working pressure: 10,000psi Test pressure: 15,000psi Standard: API 16C Full specification Armor Guarding: Included Fire Rating: Not Included Temperature rating: -20 Deg C to +100 Deg C	1	1	0
2	SECK3-HPF3 LIFTING & SAFETY EQUIPMENT TO SUIT HP10CK3-35-F1 2 x 160mm ID Safety Clamps 2 x 244mm ID Lifting Collars & element C's 2 x 7ft Stainless Steel wire rope 3/4" OD 4 x 7.75t Shackles	1	1	0
3	SC725-200CS SAFETY CLAMP 200MM 7.25T C/S GALVANISED	1	1	0

Continued...

All goods remain the property of Phoenix Beattie until paid for in full. Any damage or shortage on this delivery must be advised within 5 days. Returns may be subject to a handling charge.

Coflex Hose Certification

Form No 100/12



Phoenix Beattie Corp

11535 Brittonmore Park Drive
Houston, TX 77041
Tel: (832) 327-0141
Fax: (832) 327-0148
E-mail: es11@phoenixbeattie.com
www.phoenixbeattie.com

Delivery Note

Customer Order Number	370-369-001	Delivery Note Number	003078	Page	2
Customer / Invoice Address HELMERICH & PAYNE INT'L DRILLING CO 1437 SOUTH BOULDER TULSA, OK 74119		Delivery / Address HELMERICH & PAYNE IDC ATTN: JOE STEPHENSON - RIG 370 13609 INDUSTRIAL ROAD HOUSTON, TX 77015			

Customer Acc No	Phoenix Beattie Contract Manager	Phoenix Beattie Reference	Date
H01	JJL	006330	05/23/2008

Item No	Beattie Part Number / Description	Qty Ordered	Qty Sent	Qty To Follow
4	SC725-132CS SAFETY CLAMP 132MM 7.25T C/S GALVANIZED C/W BOLTS	1	1	0
5	00CERT-HYDRO HYDROSTATIC PRESSURE TEST CERTIFICATE	1	1	0
6	00CERT-LOAD LOAD TEST CERTIFICATES	1	1	0
7	00FREIGHT INBOUND / OUTBOUND FREIGHT PRE-PAY & ADD TO FINAL INVOICE NOTE: MATERIAL MUST BE ACCOMPANIED BY PAPERWORK INCLUDING THE PURCHASE ORDER, RIG NUMBER TO ENSURE PROPER PAYMENT	1	1	0

Phoenix Beattie Inspection Signature :

Received In Good Condition : Signature

Print Name

Date

All goods remain the property of Phoenix Beattie until paid for in full. Any damage or shortage on this delivery must be advised within 5 days.
Returns may be subject to a handling charge.

Coflex Hose Certification

Page: 1/1

15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

ContiTech Rubber
Industrial Kft.
Quality Control Dept.
(1)

[illegible]

05/23/09

Coflex Hose Certification


CERTIFICATE OF CONFORMITY

Supplier : CONTITECH RUBBER INDUSTRIAL KFT.
Equipment : 6 pcs. Choke and Kill Hose with installed couplings
Type : 3" x 10,67 m WP: 10000 psi
Supplier File Number : 412638
Date of Shipment : April. 2008
Customer : Phoenix Beattie Co.
Customer P.o. : 002491
Referenced Standards
/ Codes / Specifications : API Spec 16 C
Serial No.: 52754,52755,52776,52777,52778,52782

STATEMENT OF CONFORMITY

We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.

COUNTRY OF ORIGIN HUNGARY/EU

Signed : 


Position: Q.C. Manager

ContiTech Rubber
Industrial Kft.
Quality Control Dept.
(1)

Date: 04. April. 2008


Closed Loop
System

Dewat



OXY FLEX III PAD (SCOMI Closed Loop System)

Level Area-No Caliche-For Offices and Living Quarters



100 ft

75'

40'

SCOMI OILTOOLS DEWATERING SYSTEM

POLYMER TANK

SCOMI OILTOOLS DE-1000

PUMP 3 x 2

CHL RULLOFF BOX

PUMP 3 x 2

[illegible]

[illegible]

***Any leak of the steel tanks, lines or pumps shall be reported to the NMOCD and repaired within 48 hours.**