

Cementer: Fill in shaded areas.  
Operator: Fill in other items.

RAILROAD COMMISSION OF TEXAS  
Oil and Gas Division

Form W-15  
Cementing Report  
Rev. 4/1/83  
483-045

1. Operator's Name (As shown on Form P-5, Organization Report) <i>VF Petroleum Inc.</i>	2. RRC Operator No.	3. RRC District No.	4. County of Well Site <i>Lea</i>
5. Field Name (Wildcat or exactly as shown on RRC records)		6. API No. <i>30-025-42/35175</i>	7. Drilling Permit No.
8. Lease Name <i>Angel 13 State</i>	9. Rule 37 Case No.	10. Oil Lease/Gas ID No.	11. Well No. <i>2</i>

CASING CEMENTING DATA:		SURFACE CASING	INTER-MEDIATE CASING	PRODUCTION CASING		MULTI-STAGE CEMENTING PROCESS	
				Single String	Multiple Parallel Strings	Tool	Shoe
12. Cementing Date							
13. •Drilled hole size							
•Est. % wash or hole enlargement							
14. Size of casing (in. O.D.)							
15. Top of liner (ft.)							
16. Setting depth (ft.)							
17. Number of centralizers used							
18. Hrs. waiting on cement before drill-out							
1st Slurry	19. API cement used: No. of sacks ▶						
	Class ▶						
	Additives ▶						
2nd Slurry	No. of sacks ▶						
	Class ▶						
	Additives ▶						
3rd Slurry	No. of sacks ▶						
	Class ▶						
	Additives ▶						
1st	20. Slurry pumped: Volume (cu. ft.) ▶						
	Height (ft.) ▶						
2nd	Volume (cu. ft.) ▶						
	Height (ft.) ▶						
3rd	Volume (cu. ft.) ▶						
	Height (ft.) ▶						
Total	Volume (cu. ft.) ▶						
	Height (ft.) ▶						
21. Was cement circulated to ground surface (or bottom of cellar) outside casing?							
22. Remarks							

OVER

CEMENTING TO PLUG AND ABANDON	PLUG # 1	PLUG # 2	PLUG # 3	PLUG # 4	PLUG # 5	PLUG # 6	PLUG # 7	PLUG # 8
23. Cementing date	4-19-12	4-19-12						
24. Size of hole or pipe plugged (in.)	5 1/2"	5 1/2"						
25. Depth to bottom of tubing or drill pipe (ft.)	CIBP 6990'	CIBP 4750'						
26. Sacks of cement used (each plug)	3	3						
27. Slurry volume pumped (cu. ft.)								
28. Calculated top of plug (ft.)	6955'	4715'						
29. Measured top of plug, if tagged (ft.)								
30. Slurry wt. (lbs/gal)								
31. Type cement								

CEMENTER'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that the cementing of casing and/or the placing of cement plugs in this well as shown in the report was performed by me or under my supervision, and that the cementing data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers cementing data only.

Jerry Lee Pres  
Name and title of cementer's representative

Apollon Perforators Inc.  
Cementing Company

[Signature]  
Signature

P.O. Box 12940  
Address

Odessa Tx 79768  
City

TX 79768  
State Zip Code

432-563-0891  
Tel. Area Code Number

APR 124, 2012  
Date: mo. day yr.

OPERATOR'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that I have knowledge of the well data and information presented in this report, and that data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers all well data.

Wayne Luna  
Typed or printed name of operator's representative

Production Superintendent  
Title

[Signature]  
Signature

P.O. Box 1889  
Address

Midland, TX 79702  
City, State, Zip Code

432-683-3344  
Tel. Area Code Number

07/26/12  
Date: mo. day yr.

### Instructions to Form W-15, Cementing Report

**IMPORTANT:** Operators and cementing companies must comply with the requirements of the Commission's Statewide Rules 8 (Water Protection), 13 (Casing, Cementing, Drilling, and Completion), and 14 (Well Plugging). For offshore operations, see the requirements of Rule 13 (c).

**A. What to file.** An operator should file an original and one copy of the completed Form W-15 for each cementing company used on a well. The cementing of different casing strings on a well by one cementing company may be reported on one form. Form W-15 should be filed with the following:

- An initial oil or gas completion report, Form W-2 or G-1, as required by Statewide or special field rules;
- Form W-4, Application for Multiple Completion, if the well is a multiple parallel casing completion; and
- Form W-3, Plugging Record, unless the W-3 is signed by the cementing company representative. When reporting dry holes, operators must complete Form W-15, in addition to Form W-3, to show any casing cemented in the hole.

**B. Where to file.** The appropriate Commission District Office for the county in which the well is located.

**C. Surface casing.** An operator must set and cement sufficient surface casing to protect all usable-quality water strata, as defined by the Texas Department of Water Resources, Austin. Before drilling a well in any field or area in which no field rules are in effect or in which surface casing requirements are not specified in the applicable rules, an operator must obtain a letter from the Department of Water Resources stating the protection depth. Surface casing should not be set deeper than 200 feet below the specified depth without prior approval from the Commission.

**D. Centralizers.** Surface casing must be centralized at the shoe, above and below a stage collar or diverting tool, if run, and through usable-quality water zones. In nondeviated holes, a centralizer must be placed every fourth joint from the cement shoe to the ground surface or to the bottom of the cellar. All centralizers must meet API specifications.

**E. Exceptions and alternative casing programs.** The District Director may grant an exception to the requirements of Statewide Rule 13. In a written application, an operator must state the reason for the requested exception and outline an alternate program for casing and cementing through the protection depth for strata containing usable-quality water. The District Director may approve, modify, or reject a proposed program. An operator must obtain approval of any exception before beginning casing and cementing operations.

**F. Intermediate and production casing.** For specific technical requirements, operators should consult Statewide Rule 13 (b) (3) and (4).

**G. Plugging and abandoning.** Cement plugs must be placed in the wellbore as required by Statewide Rule 14. The District Director may require additional cement plugs. For onshore or inland wells, a 10-foot cement plug must be placed in the top of the well, and the casing must be cut off three feet below the ground surface. All cement plugs, except the top plug, must have sufficient slurry volume to fill 100 feet of hole, plus ten percent for each 1,000 feet of depth from the ground surface to the bottom of the plug.

To plug and abandon a well, operators must use only cementers approved by the Director of Field Operations. Cementing companies, service companies, or operators can qualify as approved cementers by demonstrating that they are able to mix and pump cement in compliance with Commission rules and regulations.

04/18/12 PO: Cont TOH.  
WP: Rig repair.

04/19/12 PO: RU Apollo Perf.  
WP: Fin TOH w/tbg. LD extra tbg. SWI. SDFN.  
EDC: \$2,000. ECC: \$7,000.

04/20/12 PO: Run bttm log.  
WP: RU Apollo perf. Set CIBP @ 6,990'. Make 2 bailer runs. Dump 35' of cmt on top of CIBP. Set CIBP @ 4,750'. Dump 35' of cmt on top of CIBP. TIH w/tbg open end. Circ wellbore w/2% KCl wtr. TOH. SWI. SDFN.  
EDC: \$5,500. ECC: \$12,500.

04/21/12 PO: SDFW.  
WP: Run GR/CCL/CBL from 4,700' to TOC @ 2,900'. Had add'l cmt 2,120' - 1,920'. Perf 4,554' - 4,562.5' w/2 0.41 jet shot per ft using 4" disposable gun. Total 16 holes. RD Apollo. RU tbg testers. TIH w/3 jts 2 7/8" tbg for tail pipe. Arrow set 1-x pkr plus 4,355' 2 7/8" EUE N-80 tbg. Test tbg to 9,000# psi on TIH. RD tbg testers. Set pkr @ 4,355' w/10,000# compression. Bttm of tail pipe @ 4,450'. Swb well 1 hr. Rec 24 bbls wtr. IFL surf. FFL tbg dry. Swbg depth 4,355'. SWI. SDFN & Weekend.  
EDC: \$30,000. ECC: \$42,500.

04/22/12 PO: SDFW.  
WP: SDFW.

04/23/12 PO: SITP 0#. Swbg.  
WP: SDFW.