Form 3160-5 (March 2012)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Hobbs

FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2014

5. Lease Serial No.

	·	HOBBS OCE	MMNM06531A
	OTICES AND REPORTS ON W		6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to drill or to re-enter an 7 2013 abandoned well. Use Form 3160-3 (APD) for such proposals.			3
SUBMIT IN TRIPLICATE – Other instructions on page 2.			7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well RECEIVED			MM70976B LEA UNIT BONE SPRING
☐ Oil Well ☐ Gas Well ☐ Other			8. Well Name and No LEA UNIT #31H
2. Name of Operator LEGACY RESERVES OPERATING LP			9. API Well No. 30-025-40699
3a. Address 3b. Phone No. (include area code)			10. Field and Pool or Exploratory Area
PO BOX 10848 MIDLAND, TX 79	. 1		LEA; BONE SPRING
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)			11. County or Parish, State
46' FSL & 1916' FWL, SEC. 12, T-20-S, R-34-E			LEA CO., NM
12. CHEC	K THE APPROPRIATE BOX(ES) TO IND	ICATE NATURE OF NO	FICE, REPORT OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF A	CTION
Notice of Intent	Acidize Deep	_	oduction (Start/Resume) Water Shut-Off
_		=	eclamation Well Integrity
Subsequent Report			ecomplete Other
			emporarily Abandon Doiling
Final Abandonment Notice	Convert to Injection Plug	Back W	ater Disposal
testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) SPUDDED THE LEA UNIT #31H ON 06/21/2013. DRILLED 16" HOLE TO 1761'. SET 13 3/8", 54.5#, J-55 SURFACE CASING AT 1761' AND CEMENTED WITH 1,075 SX CLASS "C" CEMENT WITH ADDITIVES TO SURFACE. CIRCULATED 289 SX CEMENT AT SURFACE. WAITED ON CEMENT 8 HOURS. NIPPLED UP CASING HEAD AND BOP EQUIPMENT. SUCCESSFULLY TESTED BOP EQUIPMENT. DRILLED 12 1/4" HOLE TO 5449'. SET 9 5/8", 40#, J-55 AND N-80 INTERMEDIATE CASING (BOTTOM 1575' IS N-80) AND CEMENTED WITH 350 SX 35/65/4 POZ CLASS "C" WITH ADDITIVES AND 200 SX CLASS "C" NEAT THRU SHOE AT 5449'. CIRCULATED 250 SX CEMENT TO SURFACE THRU DV TOOL AT 3823'. CEMENTED SECOND STAGE THRU DV TOOL AT 3823' WITH 1,675 SX 35/65/4 POZ CLASS "C" WITH ADDITIVES AND 661 SX CLASS "C" NEAT. CIRCULATED 237 SX CEMENT TO SURFACE. NIPPLED UP "B" SECTION CASING HEAD AND BOP EQUIPMENT. SUCCESSFULLY TESTED BOP EQUIPMENT. DRILLING AHEAD WITH 8 3/4" BIT. UPDATE: DRILLED 8 3/4" HOLE TO 11,230'. RAN OPEN HOLE LOGS AND GYROSCOPIC DIRECTION SURVEY. PLUGGED BACK THE 8 3/4" HOLE TO 10,170' WITH 520 SX CLASS "H" CEMENT WITH ADDITIVES. DRILLED CEMENT 10,170'-10,445'. SET WHIPSTOCK AND SIDE-TRACKED 8 3/4" HOLE AT 10,428'. DRILLED 8 3/4" HORIZONTAL LATERAL HOLE TO 13,744'. CURRENTLY DRILLING AHEAD.			
14. I hereby certify that the foregoing is t	rue and correct. Name (Printed/Typed)		
BLAIN LEWIS		Title SENIOR ENGIN	EER
Signature Plaint Jewis		Date 08/13/2013	ACCEPTED FOR RECORD
THIS SPACE FOR FEDERAL OR STATE OFFICE USE			
Approved by			AUG 2 4 2013
		Title /	Marco Place
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would			
that the applicant holds legal or equitable t entitle the applicant to conduct operations		ould Office	BUREAU OF LAND MANAGEMENT
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false.			
	,	3-7	- 1 _ / /

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.