

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720

**District II**  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720

**District III**  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170

**District IV**  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

**State of New Mexico**  
**Energy Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 South St. Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
Revised July 18, 2013

**HOBBS CLAIMED REPORT**

**AUG 09 2013**

**RECEIVED**

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

<sup>1</sup> Operator Name and Address <b>Vanguard</b> <b>VANGUARD PERMIAN LLC</b> <b>P O BOX 1570 281 NORTH NM HIGHWAY 248</b> <b>EUNICE, NM 88231</b>		<sup>2</sup> OGRID Number <b>258350</b>
		<sup>3</sup> API Number <b>30-025-38825</b>
<sup>4</sup> Property Code <b>312410</b>	<sup>5</sup> Property Name <b>GRIZZELL B</b>	<sup>6</sup> Well No. <b>6</b>

**7. Surface Location**

UL - Lot	Section	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County
H	8	22S	37E		2310	North	575	EAST	LEA

**8. Proposed Bottom Hole Location**

UL - Lot	Section	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County
H	8	22S	37E		2310	NORTH	575	EAST	LEA

**9. Pool Information**

Pool Name	Pool Code
<b>BLINEBRY</b>	

**Additional Well Information**

<sup>11</sup> Work Type <b>P</b>	<sup>12</sup> Well Type <b>O</b>	<sup>13</sup> Cable/Rotary <b>R</b>	<sup>14</sup> Lease Type <b>STATE</b>	<sup>15</sup> Ground Level Elevation <b>3422 KB</b>
<sup>16</sup> Multiple <b>Y</b>	<sup>17</sup> Proposed Depth <b>5987</b>	<sup>18</sup> Formation <b>BLINEBRY</b>	<sup>19</sup> Contractor	<sup>20</sup> Spud Date
Depth to Ground water <b>80</b>	Distance from nearest fresh water well			Distance to nearest surface water

☐ We will be using a closed-loop system in lieu of lined pits During this procedure we plan to use the Closed-Loop System with a steel tank and haul contents to the required disposal

per OCD Rule 19.15.171

**Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
	12.25	8.625	24	1140		
	17	5.5	17	7429		

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer

<sup>23</sup> I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

I further certify that I have complied with 19.15.14.9 (A) NMAC ☐ and/or 19.15.14.9 (B) NMAC ☐, if applicable.

Signature:

Printed name: **GAYE HEARD**

Title: **AGENT**

E-mail Address: **gheard@oilreportsinc.com**

Date:

Phone:

**OIL CONSERVATION DIVISION**

Approved By:

Title:

Approved Date:

Expiration Date:

Conditions of Approval: Approval to drill & test all new zones separate, but cannot produce Downhole Commingle until DHC is approved in Hobbs District office according to R-11363.

**SEP 09 2013**

**Am**



HOBBS OCD

AUG 09 2013

RECEIVED

**WORKOVER PROCEDURE**  
**Add Perforations, Stimulate & Test the Blinebry**  
**Grizzell B #6**  
**Eunice Area**  
**Lea County, New Mexico**  
**8/6/2013**

AFE # \_\_\_\_\_

**Well Data:**

RKB - GL: 3432' / 3422'  
Surf. Casing: 8-5/8", 24# J-55, set at 1140'  
Prod. Casing: 5-1/2", 17# K-55, set at 7429'  
Tbg & Pkr: 2 7/8", 6.5# J-55 EUE, set at unknown  
Perforations: Drinkard/Tubb/Abo 6,151' – 6,846' (See WBD)  
PBSD: 7,379' FC WLM,  
BHP: Not certain – well on pump  
BHT: 108°F @ TD from logs

**Casing Specifications**

Depth ( ft)	Casing Wt & Grade	Burst	Col	Body Yield	JT Yield	Wall	ID	Drift Dia.	Top Cmt
0 – 1140'	8-5/8, 24#, J-55 ST&C	2,950	1,370	630	381	-	8.097	7.972	Surf.
0 – 7,429'	5-1/2", 17#, K-55	5,320	4,910	273	272	-	4.892	4.767	DV @ 3442'

**Safety:**

Vanguard's policy on safety as employees and contractors is for everyone to go home safely every day. To this end a safety meeting involving all persons on location will be held at the beginning of each day and prior to any significant activity during the course of this operation. **It is the responsibility of the Wellsite Supervisor to lead these safety**

Grizzell B #6  
Isolate, Perf, Stim & Test Blinebry

meetings, document attendance, note in the daily report, and retain the documentation for the permanent well record.

While there are multiple aspects running a safe operation, one key point that should be made at each safety meeting is the Stop Work Authority (SWA) policy. The SWA Policy grants all persons on a Vanguard site, facility, location, or property the **Right, Obligation, Authority, and Responsibility** to stop any work or action that are unsafe to personnel, equipment, or that if continued may damage the environment. This is a key component of our safety policy and must be conveyed to all personnel on location.

HOBBS UCD

**Scope of Operations:**

AUG 09 2013

Isolate the current Drinkard/Tubb/Abo interval and add 69 new perforations to the Blinebry Formation, fracture stimulate and test the Blinebry.

**Contact Information:**

Name	Title	Office	Cell
Bryan Kindred	Workover Foreman		575-602-1788
Mike Jones	Production Foreman	575-396-0812	575-390-4611
Newt Painter	Production Superintendent	432-362-2209	432-438-3872
Randall Hicks	Senior Operations Engineer	832-377-2207	713-252-1626
Frank Lemkowitz	Operations Manager	832-377-2237	713-560-3122

**Procedure:**

1. MIRU completion rig and test anchors.
2. Unseat pump and POOH w/ rods and pump.
3. ND WH and NU BOP. Kill well with 2% KCL water, if necessary. Release TAC and POOH w/ tubing.
4. PU, strap and TIH with 4-3/4" bit, 5-1/2" casing scrapper & 2-7/8" tubing. Clean out hole to ~6130' until clean returns, POOH.
5. MI wireline w/ packoff. RIH w/ CBP and GR/CCL & correlate to the Schlumberger Platform Express Log dated 13-Oct-2008.
6. Set CBP @ ~6100'.
7. MU 3-1/8" slick casing guns set at 3 spf, 120° phasing (0.40" hole, 21" penetration).
8. Perforate as follows:
  - a. 5475' – 5478' (3', 9 shots)
  - b. 5500' – 5504' (4', 12 shots)
  - c. 5652' – 5655' (3', 9 shots)
  - d. 5812' – 5816' (4', 12 shots)
  - e. 5902' – 5905' (3', 9 shots)
  - f. 5938' – 5941' (3', 9 shots)
  - g. 5984' – 5987' (3', 9 shots) – (69 total shots)

Grizzell B #6  
Isolate, Perf, Stim & Test Blinebry

9. RD wireline.
- a. PU a 5-1/2" Arrowset I packer and RIH to ~5987'.
  - b. MIRU pump truck (with 4000 gals acid) and test lines to 3500 psi.
  - c. Spot 500 gals of acid across perforations. Load tubing with 2 % KCl and set packer at 5450'. Test packer and casing to 3500 psi
  - d. Pump 3500 gals 15% NEFE acid with 125 ball sealers.
  - e. Pump 500 gal then drop 125 balls over next 2500 gals.
  - f. Pump last 500 gals and flush to 5987'.
  - g. Record ISIP, 5 min, 10 min and 30 min.
  - h. RU swabber and swab well in to test acid job. Recover load and report fluid/gas entry.
  - i. Load hole and release packer, POOH and lay out tubing.
10. RDMO completion rig.
11. Call out 4-500 bbl tanks & fill with 2% KCl water. Install frac valve in preparation for frac job.
12. RU frac Co. and test lines & pump as per frac schedule.
13. Monitor ISIP, 10 min, 15 min. Flowback until well dies.
14. MIRU completion rig.
15. RIH w/ 5-1/2" TAC, SN and 2-7/8" tubing. Set SN at 5875'.
16. RIH w/ rods and pump.
17. RD & MO.
18. Turn well on to production.
19. Test well to determine if we will need to get comingle permit.
20. See additional procedure to comingle zones, if needed.

HOBBS OCD

AUG 09 2013

RECEIVED

*Note: It is the responsibility of Wellsite Supervisor to enter all daily activity reports and costs into WellView on a timely basis.*

**Originator:**

---

**Randall Hicks**  
**Senior Operations Engineer**

**Approved:**

---

**Frank Lemkowitz**  
**Operations Manager**

*Grizzell B #6*  
*Isolate, Perf, Stim & Test Blinbry*



**Grizzell B #6**  
**Blinebry/Drinkard/Tubbs/Abo - 30-025-38825**  
**Lea County, New Mexico**  
 INTERIM COMPLETION - 7/2013


KB: 3432'  
 GL: 3422'

TOC @ surf  
 500 sxs

8 5/8" csg @ 1140

TOC @ surf  
 650 sxs

5 1/2" csg @ 7429'



**CASING PROGRAM**

<u>Depth</u>	<u>Size</u>	<u>Weight</u>	<u>Grade</u>	<u>I.D.</u>	<u>Collapse</u>	<u>Burst</u>
1140	8 5/8"	24#	J-55	8.097	1,370	2,950
7429'	5 1/2"	17#	K-55	4.892	4,910	5,320

**PRODUCTION TUBING**

<u>Depth</u>	<u>Size</u>	<u>Weight</u>	<u>Grade</u>	<u>Threads</u>
unknown	2 7/8"	6.5#	J-55	EUE

**HOBBS OCD**

**AUG 09 2013**

**RECEIVED**

DV Tool @ 3442'

Upper Blinebry Perforations 21 holes:  
 5,475' - 5,478' (3 spf, 9 holes)  
 5,500' - 5,504' (3 spf, 12 holes)

Middle Blinebry Perforations 21 holes:  
 5,652' - 5,655' (3 spf, 9 holes)  
 5,812' - 5,816' (3 spf, 12 holes)

Lower Blinebry Perforations 27 holes:  
 5,902' - 5,905' (3 spf, 9 holes)  
 5,938' - 5,941' (3 spf, 9 holes)  
 5,984' - 5,987' (3 spf, 9 holes)

**Composite Bridge Plug @ 6100'**

Upper Drinkard/Tubb Perforations 24 holes:  
 6,151' - 6,155' (3 spf, 12 holes)  
 6,261' - 6,265' (3 spf, 12 holes)

Drinkard Perforations 36 holes:  
 6,530' - 6,536' (6 spf, 36 holes)

Abo Perforations 56 holes:

6,596' - 6,598' (8 holes)	6,728' - 6,732' (8 holes)
6,604' - 6,606' (4 holes)	6,752' - 6,756' (8 holes)
6,663' - 6,667' (8 holes)	6,797' - 6,800' (6 holes)
6,700' - 6,704' (8 holes)	6,843' - 6,846' (6 holes)

PBSD = 7,379' FC

*Note: This schematic is not to scale. For display purposes only.*