Form 3160-5 (August 2007)

# UNITED STATES DEPARTMENT OF THE INTERIOR

OCD Hobbs	
HOBBS	OCD

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

В	UREAU OF LAND MANA	GEMENT		5. Lease Serial No.	s: July 31, 2010	
SUNDRY	NMLC059152	3				
SUNDRY Do not use th abandoned we	6. If Indian, Allottee or Tribe Name					
SUBMIT IN TRI	PLICATE - Other instruc	ctions on reverse side.	RECEIVED	7. If Unit or CA/Agr	eement, Name and/or No.	
1. Type of Well	8. Well Name and No. CAPROCK MALJAMAR UNIT 267					
Oil Well Gas Well Oth  2. Name of Operator	<del>//</del>	TERRY B CALLAHAN			JAMAN ONTI 207	
LINN OPERATING INC	9. API Well No. 30-025-33751					
3a. Address 600 TRAVIS STREET, SUITE HOUSTON, TX 77002	3b. Phone No. (include area Ph: 281-840-4000	code)	10. Field and Pool, or Exploratory MALJAMAR;GRAYBURG-SAN AND			
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	)		11. County or Parish	, and State	
Sec 24 T17S R32E Mer NMP 32.821890 N Lat, 103.721973		VL /		LEA COUNTY	, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE NATURE	OF NOTICE, R	EPORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION		TY	PE OF ACTION			
☑ Notice of Intent	☐ Acidize	□ Deepen	☐ Produc	tion (Start/Resume)	☐ Water Shut-Off	
	Alter Casing	☐ Fracture Treat	Reclam	ation	■ Well Integrity	
☐ Subsequent Report	□ Casing Repair	■ New Construction	n 🗖 Recom	plete	□ Other	
☐ Final Abandonment Notice	Change Plans	Plug and Abando	on 🗖 Tempor	arily Abandon		
	☐ Convert to Injection	□ Plug Back	■ Water I	Disposal		
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab- determined that the site is ready for fi	ally or recomplete horizontally, k will be performed or provide operations. If the operation re- pandonment Notices shall be file	give subsurface locations and the Bond No. on file with BLI sults in a multiple completion	measured and true vo M/BIA. Required su or recompletion in a including reclamatio	ertical depths of all perti bsequent reports shall be new interval, a Form 31	nent markers and zones. e filed within 30 days 60-4 shall be filed once and the operator has	
Proposed P&A Procedures					<del>-</del>	
1. MIRU plugging equip. NU B	OP.		U	אוחוווחאין ר	F APPROVAL	
2. RIH and set 5-1/2 CIBP @3 3900-3800'.		•				
3. Spot 25 sx cmt @ 1620-152	(Base of Salt) WOC &	Tag <b>ZZ 85</b> /	- 2/63	5.		
4. Spot 25 sx cmt @ <del>720-620?</del>	(Top of Salt). WOC & Ta	g. 1310'-12	00'			
5. Perf & Sqz w/110 sx cmt @ 490-surface.  RECLAMATION PROCEDURE ATTACHED						
14. I hereby certify that the foregoing is	Electronic Submission #2	219980 verified by the BLM OPERATING NC, sent to processing by JOHNNY D	the Hobbs	•		
	CALLAHAN	~ 1		E SPECIALIST III		
Signature (Electronic S	ubmission)	Date 09/	13/2013			
	THIS SPACE FO	R FEDERAL OR STA	TE OFFICE U	SE		
Approved By James	a. Domes	Title _	SEAS	.,	Date 9-19-13	
Conditions of approval if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to condu	itable title to those rights in the	not warrant or subject lease Office	PD.		·	
Fitle 18 U.S.C. Section 1001 and Fitle 43 U.S. States any false, fictitions of fraushful fits	J.S. Section 1212, make it a tajements of epresentations of	orims for any person knowing to any matter within its jurisdi	y and willfully to ma	ake to any department or	agency of the United	

# Additional data for EC transaction #219980 that would not fit on the form

### 32. Additional remarks, continued

6. Cut off well head and weld on Dry Hole Marker

Verify cost to Surface all annulus.
\* Use closed loop system to circulate into

We3 Hame:	CMU #267						
f	r	- 1				Well Name;	CMU #387
ļ	Location:		Current	***		AT: No:	30-025-33751
Location Section:	1056" FAL & 2003" FW1 7: 175 R: 33E Sec: 24		Wellbore Diagr	9131		Spied Date: WBD Update:	(2/1/1997 4/12/2013 R. Van Howe
Sinch:	3: 173 R: 332 Sec: 76		801	KI6		Man obnas:	12/2/2013 R. VAN HOME
Survey			ii	13		Hole Stre:	11 1/4
County:	Lei					FUTL CHE	B-5/8", 20A, ISNY-42 ST&C
Lat/Long: Field:	Malamer Grayburg San Andres			1 2		Cement blend: Depth:	325 to 440°
146.7	Devalors		Z	133		TOC:	Ore con to Surf
GL:	1,677		- <b>3</b> 11	115		1177	
DF.			\$13	11/8		Hole Size:	HAND AND CONTRACTOR OF THE PROPERTY OF THE PRO
KIT-GL Cole:				146.	8-5/8", 20#, 10 hs	in Cur	
ch w/log?	L		셐	10	iti fi ret.		
Localne Sepuis	ements:		\$	ž		Cornent Bland:	
	PA-LALI SETTING		<u>}</u>	35			
1			3	3.		Resurns:	
L				ŝ		TOC	
-	<del>                                     </del>		- 31			Language	
Dete 2/3/1977	Spud 12:1/4" hole & drid to A40; Set \$-5/8" mg @ 4	INV P. and J. J. 335 as /2-r 120 as to and	<i>ii</i>	3:		Catally ad Contraction	_
				3		Petalls of Perforation	
2/8/1907	Defined to 4,650, Set 5-1/2* 278 3-55 178 C cts @ 645	57, 76', 79', 81', 83', 4.109', 1/7, 13', 14', 15', 26', 17',	1	8		5/29/1997	Perfo 3953'-4234'
Ì		9', 60', 67', 68', 73', 74', 75', 76', 4,220', 21', 22', 23', 24',	<u> </u>	17			
5/29/1997	25', 28', 31', 34', w 1 5#F (50 Holes)		81	18			
6/3/1997	RIH w/ Howco R-4 par & 125 cs 2-3/8" the to 3989".	Acidity, POH w/ plu and the.	i i	35			
1	HIM w/ 5-1// Howco perma-telch pur, on-oil tool &	125 pt 2-3/6" IPC tbg to 3,879.41". ND BOP. Pumped	8	N			
	paties fluid. Set plu & 1397. Tested cap to 500#, Hei	id Os, ABMO. Initial injection rate of 400 BVIPD @	8	8			
6/W1997	21004.	and the second s	i i	13			
	\$2.201.007 field Show the art has \$11 \$10.0 Ment of the	and plu, RIH w/ naw ptr (same kind) & \$25 jts 2-3/8" PC	3	beladakanna bibani marahin malayakan seriak			
0/21/1998		P. NU WH. Laft we'l on injection 700 EWPD @ 1800#.	3	18			
1		<u> </u>		13			
-				3			
<b>-</b>			<del>1</del>	13		AND DEPT THEORY	lment.Desath
<del></del>			4	Ž.		6/4/1997	
		the state of the s	¥ <del>1</del>	H		1,953'-4,214	Acidine/6000 gal 15% Fer-check acid + 48 ball seaters
			4	Ĭ.			, -
			3	H			
		·	3.	11			
			*1	9			
		A CONTRACTOR OF THE CONTRACTOR	en e	1.			
			31	13			
			3	13			Tubing Date I
			3	2		intrin	Description
			<u></u>	3			
]				3		Pkr Depth.	<del></del>
<del></del>			31	12		hr belief	1,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
			料	13			
<u> </u>			V. W. 1600	1			Red Drief (top to bottom)
}			3	Ľ.		Roda	Perciption
			3	9			
			∤	ŝ			
			<u>.</u>	8			
<b></b>			SI .	2			
				Ž.		Compine Voft	
				ž		LANGE LA PLENCE	
ļ			<b>\$ </b>	8			
<b> </b>	The state of the s		<u>}</u>	200			
			**************************************	1			
<b></b>				3			
<del> </del>	the section of the se			18			
			<u>is</u>	18			
			<u> </u>	Į.			
<del> </del>			8	lê.			122
				lä		Hole Stret Frod Coar	7.7/\$ 5-1/2*, 174, F55 L18C
			<b>#</b>	8		Capacity (bbl/ft):	, mr , art, flag birty
				8		Cement Blend:	2200 ses
<b></b>			*** 18	8		Returns	
	and the second s			Įĝ.		TOC: Depth	surf 4457
				a <mark>lgibbigig</mark> waan mankan man ya man man man man man man man man man ma		"	
			<u> </u>	耳		1	
~~~~~~			<del> </del>	듹	1 06 21.4 2741		
			5	谐	3,953'-4,234'	Line with a second discount.	
			<u> </u>				
			<u>a</u>	J			
			7	D	3-1/7", 17#		
<del> </del>			TD: 4,450		H150 4,450°		
	and the state of t		10.45				
		— — — — — — — — — — — — — — — — — —					

.

E

Proposed Wellbore Diagram Wellbore: CMU 8267							
Lecation Section	Location; Level HML & 2005 FWL  Fr 373 Rt 245 Fer; 24	ollikole	Proposed Welltone Diagram		West Assessed After the parties Access Contract WEST Unpublished	('Mu' e ( f )' 26-035-1375; 1/2/1947 1/2/20(1) R. Van Henen	
Block: Survey: County: Let/Jones: Freed:	(A) Well-proje Gregourg Jan Assista	721/4" h.le 85/8" 20 25 325 54, circ, 438			New Sarat Sard Cap: Careered Stared: Departs:	12 tyl 6 tyre, 22m, 15st-42 Stibi: 315 81:	The second secon
GL: PF-GI CAP LL B/LOS)	Clave Hors:	325 St. Circ.	4	हैं इन्द्रोड, इंज, कड़ा इन्हें कु मंड	Hole For:	Orr cre to Set	1
Lendos Proer				म्हर्ज है 5दा मा 110 वर द्रम्य ही 450 अलीवर द्रिका 25 हरद हम्म ही द्रमुक 72ज	Consent Band; Bathers: \$130:		
Deta 1/2/1997 1/3/1992 1/3W1987 4/3/1997 WW1987	Military mirera des par a 175 ht 2-5, \$" the se bray".	7.4 cmdd w/ 3700 cc; Cr; 245 cc to cc; 7.7 pr; 77, 87, 82, 80, 80, 90, 107, 135, 107, 127, 28, 84, 81, 87, 87, 87, 87, 88, 87, 87, 87, 87, 87	Construction Associate Colleges - of	った	Petrolic of Perforable 1/29/2897	5 / 2 17 £	J-55
6/11/1998	1900+ 	RE-AD WALLER WAS AS REPORTED FOR THE			had of Fractions Fire	etrem Desaits	
				1901 15 is 401 Ø 1.530 1.530	\$\427.794 \$\47.794	gradess field 64 + Seize Frenches Mitgling (OCCO), active 6	
			Periodo Pario			Teldang betraff	3
			Section Contraction of		Fla Depth	Patricular	
			Section Control		Rade	And Cored (top to horser)  Description	
			Some Selfano		hempina livitu		3
			CALL WASH			•	
			30 mm		Hole, Signi Priod Cag: Capacity (bbs/rit): Certains Mondi;	77/4 5-1/7, 174, 5-55 1/5-C 1700 816	
				\$651 25 5- 10-0 @ 1,800-3 200* Cast @ 1,500*	Regards: 1002 Depth	ent erso	
				9.000-43.90°	3,953	- 4 23 4 150 1206 Circ.	) (×
			7'2:4,4 b7	5-177, 179 201 <b>2</b> 5-4,4517	د/ در	circ.	*/
According to the second					Anhy	1110	
					TISOLA	1110	
		3900	)			22 35	
		3900	5	روند. معمور معتبد	'R	27 28 	
		~	л. J	/ G	B	3766	
			Alay	/ <	fift.	4180	

.

# BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

# Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.



# United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

#### **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
  Operations must include adequate measures for stabilization and reclamation of disturbed lands.
  Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
  process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

## **Inspection & Enforcement**

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist 575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston Environmental Protection Specialist 575-234-5974

Solomon Hughes Natural Resource Specialist 575-234-5951

# **Permitting**

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

Legion Brumley Environmental Protection Specialist 575-234-5957

# Realty, Compliance

Randy Pair Environmental Protection Specialist 575-234-6240