

Submit 1 Copy To Appropriate District  
Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised July 18, 2013

HOBBS OGD

OCT 18 2013

RECEIVED

WELL API NO. 30-025-41376
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Young 16 NC State <i>Com</i>
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Young; Bone Spring 65330
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770'

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter N: 330 feet from the South line and 2040 feet from the West line  
Section 16 Township 18S Range 32E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3770'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/08/13.. TD 8 3/4" hole @ 9510'. Ran 9510' of 7" 26# P110 BT & C csg. Cemented with 850 sks BJ Lite Class H (50:50:10) with additives. Mixed @ 11.9 /g w/ 2.38 yd. Tail w/400 sks Class H w/additives. Mixed @ 15.6/g w/1.18 yd. Plug down @ 5:00 PM 10/08/13. Circ 114 sks cement to pit. WOC. At 6:30 AM 10/10/13, tested BOPE & csg to 2500# for 30 minutes, held OK. Drilled out with 6 1/8" bit.

Spud Date: 09/24/13

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Jackie Lathan* TITLE Regulatory DATE 10/15/13

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: *[Signature]* TITLE Petroleum Engineer DATE OCT 22 2013  
Conditions of Approval (if any):

OCT 22 2013