

HOBBS OCD

OCT 28 2013

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 20105. Lease Serial No.
NMLC031620A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator
CONOCO INCORPORATEDContact: RHONDA ROGERS
E-Mail: rogersr@conocophillips.com3a. Address
10 DESTA DRIVE WEST, SUITE 100 W.
MIDLAND, TX 797053b. Phone No. (include area code)
Ph: 432-688-9174

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

~~Multiple--See Attached~~

I-24-20S-37E

2490/S & 1310/E

8. Well Name and No. SEMU Permian
~~Multiple--See Attached~~ #1289. API Well No. 30-025-
~~Multiple--See Attached~~ 3431310. Field and Pool, or Exploratory
~~Multiple--See Attached~~ Warren Tubbs (GAS)

11. County or Parish, and State

LEA COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

ConocoPhillips request to add Grayburg perms @ 3882'-3991' and abandon the Tubbs perms @ 6466'-6620' by placing CIBP @ 6390' w/35' cmt on top of CIBP. Please refer to attached procedures.

During this procedure we plan to use the Closed-Loop System and haul content to the required disposal.

Essentially procedure is approved as is; however on operator's procedure step #6: Operator to tag top of cement and report results to BLM



14. I hereby certify that the foregoing is true and correct.

Electronic Submission #221211 verified by the BLM Well Information System

For CONOCO INCORPORATED, sent to the Hobbs

Committed to AFMSS for processing by JOHNNY DICKERSON on 10/17/2013 (14JLD0719SE)

Name (Printed/Typed) RHONDA ROGERS

Title STAFF REGULATORY TECHNICIAN

Signature (Electronic Submission)

Date 09/25/2013

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By EDWARD FERNANDEZ

Title PETROLEUM ENGINEER

Date 10/24/2013

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Additional data for EC transaction #221211 that would not fit on the form

7. If Unit or CA/Agreement, Name and No., continued

892000321N
892000321O

Wells/Facilities, continued

Agreement	Lease	Well/Fac Name, Number	API Number	Location
NMLC031620A	NMLC031620A	SEMU 128	30-025-34313-00-S1	Sec 24 T20S R37E NESE 2490FSL 1310FEL
NMLC031620A	NMLC031620A	SEMU 128	30-025-34313-00-S2	Sec 24 T20S R37E NESE 2490FSL 1310FEL
NMNM71041M	NMLC031620A	SEMU 128	30-025-34313-00-S4	Sec 24 T20S R37E NESE 2490FSL 1310FEL
NMNM71041L	NMLC031620A	SEMU 128	30-025-34313-00-S3	Sec 24 T20S R37E NESE 2490FSL 1310FEL

10. Field and Pool, continued

WARREN



SEM U 128
API#: 30-25-34313
Skaggs Drinkard Field
Lea County, New Mexico

The purpose of the proposed project is to add GRAYBURG perforations and abandon the TUBB perforations. This well was originally completed in the upper DRINKARD on 4/21/1998 with an acid frac treatment

ConocoPhillips is the operator of the subject well with a 50% working interest and a 43.75% net revenue interest.

Well Category One:

Well Category 1 due to a 100 ppm H₂S ROE < 50'.

This well is not capable of hydrocarbon flow.

Class 2, 3000 psi, Hydraulic BOP is recommended.

No choke manifold is to be used. ONE BOP EXCEPTION: One untested barrier – dynamic fluid column.

H ₂ S	ROE- ft.
100 ppm	4
500 ppm	2

BOPE Class One: Hydraulic BOP recommended per Projects Group.

PROCEDURE

1. Prior to service unit MI & RU,. Test anchors. Last well service 4.02.2012.
2. Spot 9 clean 500 bbl frac tanks. Load tanks w/ fresh water prior to frac date. Water to be biocide-treated by Service Company.
3. MI & RU service unit. Un-seat packer. ND well. NU hydril 1 X 7-1/16" 5K Blowout Preventer (Single BOP: blinds) and environmental tray. Scan 2-3/8", 6.5# J-55 production tbg out of hole. LD Tbg.
4. The following is a summary of the current well configuration:

Spud Date: 3.11.98	RI's Date: 4.12.98	Depth RKB		Elev.: 3536 KB; 3547 GL (KB - GL: 11 ft.)
		top	blm	
8-5/8", 7.972, 23#, M-50,		0	1251	Lead: 385 Sxs , Class C @ 12.4 ppg
Hole Size: 12.25,				Tail : 220 sxs, Class C @ 14.8 ppg
				TOC @ Surface
5-1/2", 4.825, 17# K55 , Hole: 7 7/8"		0	7005	1st Stage :
				Lead: 145 sxs, class C @ 11.85 ppg
5-1/2", 17# J55 , DV tool		3690	3692.5	Tail: 440 sxs , Class C @ 13.6 ppg
				2nd Stage :
				Lead: 320 sxs, class C @ 13.85 ppg
				Tail: 385 sxs , Class C @ 14 ppg

Mud weight : 10 ppg @ TD (7008')		
-----------------------------------	--	--

Perforations:

Formation	Perforations (MD)	Total <ft>	Frac Grad	SPF	Phase	Anticipated Reservoir Pressure	Anticipated Reservoir Temperature
Grayburg	3671-3684, 3694-3696, 3703-3705, 3732-3744, 3752-3758 3770-3773 3823-3839 3834-3840 3844-3850 3856-3859	188	NA	1	0	2000	114°
Tubb	6466-6476 6507-6517 6524-6532 6549-6600 6618-6620	154	.68	2	60	1800	114o

5. PU & RIH w 3-1/2", 9.3#, N-80 tbg work string tbg w/ 4-3/4" bit & 5-1/2", 17# csg scraper to 6450. Circulate bottoms up. Well Capacity w tubing 150 bbl. POOH with WS and bit.
6. PU CIBP & packer. RIH w/ tbg, packer & CIBP-1. Set CIBP-1 @ 6390 (Abandoning TUBB). Pressure test against CIBP @ 2500 #. Spot 35 ft of cement on top of CIBP (If dump bailer is to be used tag is required). POOH w/ tbg.
7. TIH with open ended tubing. Fill hole with 27 Bbls of 14.8 ppg mud up to 5306'. Pull up hole. Mix and pump 14 sks of 14 ppg (class C Cement) as a cement plug (154') to isolate the Glorieta formation. POOH. WOC. Tag is required to confirm depth of plug.
8. RU **SLB** Perforators. NU lubricator & test @ 500#. Perforate following intervals at 3 spf @ 60-degree phasing w/ 3-3/8", HSD Power Jet 3406, HMX, 22.8 gm. (EHD: 0.37 in.; Penetration: 37 in.)...

Tag Cement
Top
& Report
To BLM

	top	blm	ft.	SPF	Perfs
Grayburg	3882	3885	3	3	9
	3912	3917	5	3	15
	3926	3929	3	3	9
	3949	3951	2	3	3
	3955	3961	6	3	18
	3966	3970	4	3	12
	3976	3981	5	3	15
	3989	3991	2	3	6
			30		90

9. RIH w/ tbg, PKR & CIBP with ball catcher. Test tbg @ 8500# while RIH (3-1/2", 9.3#, N-80 Internal Yield Prs: 10,160#). Acidize Grayburg perforations w/ total 75 bbl (3150 gal) 15% NE Fe HCl:

Acidize Partial Interval (3882-3991):

- Set CIBP @ 4080 (between perf: 3991 & csg collar: 4085
- Set packer @ 3870. Circulate wellbore fluid out. Test 3-1/2" x 5-1/2" annulus & PKR @ 500#. Break Perfs.
- Pump 15% NE Fe HCl using 60, 5/8" RCN balls followed by 4.3 bbl 2% KCl.
- SD and allow well to equalize.
- Pump w/ 23 bbl 2% KCl to flush to bottom perf.
- Record ISIP, SITP (5 min), SITP (10 min) & SITP (15 min).]
- Reset packer to 3600'

Note: Due to the configuration of the wellbore there may be problems setting the packer @ 3870 to acidize partial interval (3882-3991) due to only 23ft of blanket pipe between bottom of existing perfs (3859) and top of new perfs (3882). At that point it is recommended to set packer between set of existing perfs (3770-3773 & 3823-3839) and extend the EOT to 3860.

10. RU HALLIBURTON. Set treating line pop-off to release @ 8500#.

Set pump trips @ 8000#.

Install spring-operated relief valve on csg-tbg annulus. Pre-set @ 500#.

Load 3-1/2" x 5-1/2" annulus. Note annulus fills volume. Place 200# on csg.

Test surface lines @ 9000#.

Frac 3671-3991 down 3-1/2", 9.3#, N-80 tbg as per attached schedule (see attachments). Anticipated treating rate: 30 BPM @ 6800#:

Report ISIP, SITP (5 min), SITP (10 min) & SITP (15 min). RD SLB. SDON.

11. SI for a minimum of 18 hrs to allow resin-coated sand to cure. Flow back well until dead. Starting flowback rate should not be higher than 1/2 bbl /min. **MIRU**. Release packer and tag for fill. If needed rig up reverse unit and circulate wellbore clean. POOH & LD 3-1/2", 9.3#, N-80 frac string & PKR.
12. RIH. w / 2 7/8" tubing (hydro testing while going in hole) according to proposed design in well view. NDBOP. NUWH and run with rods as per Rodstar design. Space pump, hang well, load tubing and check pump action. RDMO. Handover to Operations.

	Capacity		Internal Diam. : in.		Internal Yield (Burst): psi	
	bbl / ft	gal /ft	nom.	drift	100%	80%
3-1/2", 9.3#, N-80	0.0087	0.3652	2.992	2.867	10160	8128
5-1/2", 17#, J-55	0.02324	0.9764	4.892	4.767	5320	4256

Attachments:

1. Pump Schedule.



Microsoft Office
Excel Worksheet

SEMU 128

								Clean Volumes				Slurry volumes			
Stage	Rate	Fluid Type	Propan t conc	Stage Mass	Stage time	Cum Time		Gals	Bbls	Cum gals	Cum Bbls	Gals	Bbls	Cum Gals	Cum Bbls
Pad		30 Linear Gel			26	26		33000	786	33000	786	33000	786	33000	786
1 Sand Stage		30 XL Fluid	20/40 Brown	0.25	1000	3		4000	95	37000	881	4038	96	4038	882
2 Sand Stage		30 XL Fluid	20/40 Brown	0.5	2000	3		4000	95	41000	976	4075	97	4075	979
3 Sand Stage		30 XL Fluid	20/40 Brown	0.75	3000	3		4000	95	45000	1071	4113	98	4113	1077
4 Sand Stage		30 XL Fluid	20/40 Brown	1	4000	3		4000	95	49000	1167	4151	99	4151	1176
5 Sand Stage		30 XL Fluid	20/40 Brown	1.25	5000	3		4000	95	53000	1262	4189	100	4189	1275
6 Sand Stage		30 XL Fluid	20/40 Brown	1.5	6000	3		4000	95	57000	1357	4226	101	4226	1376
7 Sand Stage		30 XL Fluid	20/40 Brown	1.75	7000	3		4000	95	61000	1452	4264	102	4264	1478
8 Sand Stage		30 XL Fluid	20/40 Brown	2	8000	3		4000	95	65000	1548	4302	102	4302	1580
9 Sand Stage		30 XL Fluid	20/40 Brown	2.25	9000	3		4000	95	69000	1643	4340	103	4340	1683
10 Sand Stage		30 XL Fluid	20/40 Brown	2.5	10000	3		4000	95	73000	1738	4377	104	4377	1788
12 Sand Stage		30 XL Fluid	20/40 Brown	2.75	11000	4		4000	95	77000	1833	4415	105	4415	1893
13 Sand Stage		30 XL Fluid	20/40 Brown	3	12000	4		4000	95	81000	1929	4453	106	4453	1999
14 Sand Stage		30 XL Fluid	20/40 Brown	3.25	13000	4		4000	95	85000	2024	4491	107	4491	2106
15 Sand Stage		30 XL Fluid	20/40 RC	3.5	14000	4		4000	95	89000	2119	4528	108	4528	2213
16 Sand Stage		30 XL Fluid	20/40 RC	3.75	15000	4		4000	95	93000	2214	4566	109	4566	2322
17 Sand Stage		30 XL Fluid	20/40 RC	4	16000	4		4000	95	97000	2310	4604	110	4604	2432
18 Sand Stage		30 XL Fluid	20/40 RC	4	16000	4		4000	95	101000	2405	4604	110	4604	2541
Spot Acid		30 15% HCL				0		500	12	101500	2417	500	12	500	2553
Flush		10 2% KCL				3		1300	31	102800	2448	1300	31	1300	2584

Total treatment time < Hr >	1.5
Total propanant < Lbs >	152000
20/40 Brown	91000
20/40 RC	61000
Fluids Breakdown Clean < Gals >	101500
Linear Gel	33000
15% HCL	500
XL Fluid	68000
Frac tanks to line up	9

Power Requirements

MAX HHP <HP>	6111.3
Input Power <KW>	827.99

MD Top	MD Bottom	Net Footage	TVD Top	TVD Bottom	SPF	# of perf
3671	3684	13	3671	3684	1	13
3694	3696	2	3694	3696	1	2
3703	3705	2	3703	3705	1	2
3732	3744	12	3732	3744	1	12
3752	3758	6	3752	3758	1	6
3730	3773	43	3730	3773	1	43
3823	3839	16	3823	3839	1	16
3834	3840	6	3834	3840	1	6
3844	3850	6	3844	3850	1	6
3856	3859	3	3856	3859	1	3
3882	3885	3	3882	3885	3	9
3912	3917	5	3912	3917	3	15
3926	3929	3	3926	3929	3	9
3949	3951	2	3949	3951	3	6
3955	3961	6	3955	3961	3	18
Midperf:	3816	128				166

Status
Existing
Proposed