

Date Spudded: 01/01/69
4313.5' KB, 4302' GL

Post-WKO Wellbore Diagram
✓ **CrownQuest Operating, LLC**
✓ **State "27" #2 SWD**
✓ 660' FSL, 660' FEL, Sec. 27, T-14-S, R-32-E, (P)
✓ **Lea County, NM, API #30-025-22932**

17½" Hole →

13 ⅜", 48#, J-55 csg @ 382'.
Cmt w/400 sx, circ to surface.

11" Hole →

TOC ± 2300' by calc

8-5/8", 24# & 32#, J-55 casing @
4050'. Cmt'd w/300 sx. Did not
circ.

7 ⅞" Hole →

TOC ± 8500' by calc

5 ½" Lock-Set Packer with on/off
@ 9,699' (set w/12k)

Bough "A" & "B" Perfs :
9789'-9798', 9806'-9812', 9840'-9847',
9870'-9880', 9880'-9892'

Bough "C" Perfs :
9904'-9910', 9920'-9924'

Bough "C" Perfs : 9960'-9970'

CIBP @ 9950'

TD: 10,009'
PBTD: 9950'

5½", 15.5 & 17#, N-80 & K-55 csg @ 10,009'
Cmt'd w/200 sx. Cmt did not circ. TOC
8020' by CBL.

HOBBS OCD

NOV 14 2013

RECEIVED

WORK SUMMARY

Accepted for Record Only

Tubing Record (10/29/12):

306 joints tubing:
-25 jts 2-7/8" IPC
-50 jts 2-7/8" J55
-57 jts Salta 2-7/8"
-72 jts IPC 2-3/8"
-102 Salta 2-3/8"
-1-51/2" Lock-Set Pkr w/ on-off tool 4.78'
Bottom of Tubing 9694.22'

NOV 14 2013