

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

HOBBS OGD

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 13 2014

WELL API NO. 30-025-41459
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Tumbling Dice 2 State Com
8. Well Number 1H
9. OGRID Number 7377
10. Pool name or Wildcat Red Hills; Upper Bone Spring Shale
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3358' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
EOG Resources, Inc.

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter M; 220 feet from the South line and 760 feet from the West line
Section 2 Township 25S Range 34E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/5/14 Ran 123 jts 9-5/8", 40#, (29) HCK55 & (94) J55 LTC casing set at 5290'.

1/6/14 Cemented lead w/ 1100 sx Class C, 12.7 ppg, 2.21 yield;
tail w/ 200 sx Class C, 14.8 ppg, 1.346 yield.

→ Circulated 30 sx cement to surface. WOC 24+ hrs.

1/7/14 Tested casing to 2000 psi for 30 minutes. Test good.
Resumed drilling 8-3/4" hole.

Spud Date: 12/31/13

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 01/03/14

Type or print name Stan Wagner E-mail address: PHONE 432-686-3689

For State Use Only
APPROVED BY Mary Brown TITLE Compliance Officer DATE 1/14/2014

Conditions of Approval (if any):

JAN 14 2014