

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-03219
5. Indicate Type of Lease STATE FEE XX
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name East Pearl Queen Unit
8. Well Number 37
9. OGRID Number 25482
10. Pool name or Wildcat Pearl Queen
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
State of New Mexico formerly Xeric Oil & Gas Corp

3. Address of Operator
1625 N French Drive Hobbs, NM 88240

4. Well Location
Unit Letter O : 660 feet from the S line and 1980 feet from the E line
Section 27 Township 19S Range 35E NMPM Lea County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A XX
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/7/2014 Moved in rigged up. Installed BOP. RIH with work string and tagged up at 4363'.

1/8/2014 Circulated hole with MLF. Spotted 25 sx cement at 4263'. POOH to 3455' and spotted 25 sx cement. POOH to 1820' and spotted 25 sx cement. POOH and perforated @ 350'. Circulated cement down casing to perfs @ 350' and up annulus to surface. Took 115 sx.

1/9/2014 Cut off wellhead and installed marker.

HOBBS OCD

JAN 17 2014

RECEIVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE _____ TITLE _____ DATE _____

Type or print name _____ E-mail address: _____ PHONE: _____

For State Use Only

APPROVED BY: Mark Whittem TITLE Compliance Officer DATE 01/17/2014

Conditions of Approval (if any):

JAN 21 2014