Submit 1 Copy To Appropriate District	State of New Mexico	Form C-103
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
• 1625 N. French Dr., Hobbs, NM 88240 OCD District II – (575) 748-1283 HOBBS		WELL API NO. 30-025-39808
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, PEB74207 2014 District IV – (505) 476-3460	1220 South St. Francis Dr.	STATE STATE FEE
District IV – (505) 476-3460 FCD 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRWHOTICES	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS DIFFERENT RESERVOIR. USE "APPLICATION PROPOSALS.)	TO DRILL OR TO DEEPEN OR PLUG BACK TO A ON FOR PERMIT" (FORM C-101) FOR SUCH	BLACK MAMBA 15 STATE
	Well Other	8. Well Number
2. Name of Operator	D.	9. OGRID Number
Devon Energy Production Company, Ll 3. Address of Operator		6137 10. Pool name or Wildcat
333 W. Sheridan Avenue, Oklahoma Ci	ity, OK 73102	WILDCAT; WOLFCAMP GAS
4. Well Location		
	00'feet from theSouth line and 18	40' feet from the East line
Section 15	Township 23S Range 33E	NMPM Lea County, NM
	. Elevation (Show whether DR, RKB, RT, GR, etc.	
37	16' GL	
12. Check Appr	ate Nature of Notice,	Report or Other Data
P. Approved for Plugging of well bore The Liability under bond is retained per The Liability under bond is retained by the found at	nding receipt of SUB	SEQUENT REPORT OF:
P' Approved for Plugging of well bore The Liability under bond is retained per PL C-103 (Specifically for Subsequer PL C-103 (Specifically for Subsequer PL C-103 (Specifically for Subsequer) PL C-103 (Specifically for Subsequer)	nt Report of Well nt Report of Well REMEDIAL WOR	
P' Approved for Pluggs is retained positive. The Liability under bond is retained positive. The Liability under bond is retained positive. The Liability under forms is retained positive. The Liability under bond is	OCD web page COMMENCE DR	-
PL C-100 which may	CASING/CEMEN	
DC Plugging/ with place of plugging/ with plugging plugging with plugging p	·	
CLC under emprd.state.iiii.s		
	OTHER:	
	d operations. (Clearly state all pertinent details, an	
proposed completion or recomp	SEE RULE 19.15.7.14 NMAC. For Multiple Co	impletions: Attach wellbore diagram of
proposed completion of recomp	iction.	
	104'. Spot 140 sx Cl C cmt to surface.	
2. 2/21/14. Set dry hole marker. S	Spudder hole plugged & abandoned.	
Spud Date:	Rig Release Date:	
I hereby certify that the information above	ve is true and complete to the best of my knowledg	ge and belief.
SIGNATURE ROMME SI	TITLE_Operations_Technician	DATE 2-25-14
The second secon	C mod oddina. Deci Cl. 101	HONE: 405 552 4415
Type or print nameRonnie Slack For State Use Only	E-mail address: _Ronnie.Slack@dvn.com P	HUNE: _405-552-4615
N, n,	1	(c) - 1 w)
APPROVED BY: Wall Whi	take TITLE Compliance O	MAR 0 3 2014 (4)
Conditions of Approval (if any):		1100 2 2011
		MAK W & ZOTT

1700 FSL & 1840' FEL; SEC 15-T23S-R33E County: LEA State: NM 1: 3716' GL Spud Date: 7/26/10 Compl Date: Not completed 0-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev:	1700 FSL & 1840' FEL; SEC 15-T235-R33E County: LEA State: NM	n: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E	n: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E	On: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E County: LEA State: NM Spud Date: 7/26/10 Compl Date: Not completed Date: 2/24/14 Rev: SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	on: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E	On: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E County: LEA State: NM Spud Date: 7/26/10 Compl Date: Not completed 30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: Wellbore plugged out. (2/10/14) Set dry hole marker. (2/21/14) Set dry hole marker. (2/21/14) 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	on: 1700 FSL & 1840' FEL; SEC 15-T23S-R33E		VON ENERGY PF				
Spud Date: 7/26/10 Compl Date: Not completed D-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: UDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6'	Spud Date: 7/26/10 Compl Date: Not completed 30-025-39808 Prepared by: Ronnie Slack PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104"	on: 3716' GL 30-025-39808 Prepared by: Ronnie Slack Date: 7/26/10 Compl Date: Not completed PUDDER HOLE PLUGGED & ABANDONED 2/21/14 Rev: Wellbore plugged out. (2/10/14) 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	on: 3716 GL Spud Date: 7/26/10 Compl Date: Not completed 30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6" Cmt'd back to 3", fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	ion: 3716' GL 30-025-39808 Prepared by: Ronnie Slack SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	on: 3716' GL 30-025-39808 Prepared by: Ronnie Slack Date: 7/26/10 Compl Date: Not completed Date: 2/24/14 Rev: PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Sput Date: 7/26/10 Compl Date: Not completed Date: 2/24/14 Rev: Wellbore plugged out. (2/10/14) Set dry hole marker. (2/21/14) Set dry hole marker. (2/21/14) 1. Spot 140 sx cmt from 104' to surface. (2/10/14)	Spud Date: 7/26/10 Compl Date: Not completed 30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spud Date: 7/26/10 Compl Date: Not completed Rev: Wellbore plugged out. (2/10/14) Set dry hole marker. (2/21/14) 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	on: 3716 GL 30-025-39808 Prepared by: Ronnie Slack PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Sput Date: 7/26/10 Compl Date: Not completed Date: Not completed Date: 2/24/14 Rev: Wellbore plugged out. (2/10/14) Set dry hole marker. (2/21/14) 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	Name: BLACK MAMBA 15 STATE 1	T226 N225		A 1; WO		
D-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: UDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Wellbore plugged out. (2/10/14) Set dry hole marker. (2/21/14)	20" Open Hole from 6' to 104' Pudder Hole Plugged & ABANDONED 2/21/14 A8" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 1. Spot 140 sx cmt from 104' to surface. (2/10/14)	30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48' Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ronnie Slack PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ronnie Slack Date: 2/24/14 Rev: PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'		1235-R33E		27.710		1.4.1
Wellbore plugged out. (2/10/14) 2/21/14 48" Hole 30" conductor w/locking lid @ 6'	Wellbore plugged out. (2/10/14) 48" Hole 30" conductor wilocking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	SPUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6" Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	PUDDER HOLE PLUGGED & ABANDONED 2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'						нетеа
2/21/14 48" Hole 30" conductor w/locking lid @ 6'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor wilocking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	2/21/14 48" Hole 30" conductor w/locking lid @ 6' Cmt'd back to 3', fill dirt from 3' to surface 1. Spot 140 sx cmt from 104' to surface. (2/10/14) 20" Open Hole from 6' to 104'	30-025-39808 Prepared by: Ron	nie Slack	Date: 2/24/14		Rev:	
100 100 100 100 100 100 100 100 100 100	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	20" Open Hole from 6' to 104'	48" Hole 30" conductor w/locking lid @ 6'	e e		Set dry	hole marker. (2/21/14)	