	SUNDRY NOTICES AND REPORTS ON WELLS				Expires: July 31, 2010 5. Lease Serial No. NMNM27508	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter anMAR 2 4 2014 abandoned well. Use form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side. RECEIVED				7. If Unit or CA/Agreement, Name and/or No.		
I. Type of Well ☐ Gas Well ☐ Other				8. Well Name and No. WILDER FEDERAL AC 29 5H		
2. Name of Operator CONOCOPHILLIPS Contact: ASHLEY BERGEN E-Mail: ashley.bergen@conocophillips.com				9. API Well No. 30-025-41509		
3a. Address 3b. Phone No. (include area code) P.O. BOX 51810 Ph: 432-688-6983 MIDLAND, TX 79710 //				10. Field and Pool, or Exploratory JENNING; BONE SPRINGS, UP		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description				11. County or Parish, and State		
Sec 29 T26S R32E NENE 7	24FNL 877FEL			LEA COUNTY,	NM /	
12. CHECK API	PROPRIATE BOX(ES) TO INI	DICATE NATURE OF	NOTICE, RI	L EPORT, OR OTHEI	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
□ Notice of Intent	Acidize	Deepen	—	ion (Start/Resume)	UWater Shut-Off	
Subsequent Report	Alter Casing	Fracture Treat	Reclam		Well Integrity Other	
Final Abandonment Notice	 Casing Repair Change Plans 	New Construction Plug and Abandon	Recomp Tempor	arily Abandon	Drilling Operations	
_	Convert to Injection	Plug Back	U Water I	-		
w/ 13 3/8", 54.5#, J-55 csg s	H w/ 17 1/2" bit & drilled ahead et @ 996'. Pre-flush w/ 20 bbls l	FW. Pumped 520 sx (15	3 bbls) of cla	ass	<u>a</u>	
 w/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (13) 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w. (93 bbls) of class C tail cmt. Dro to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled v/ 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled 0, csg set @ 13,809. Prc & 425 sx (185 bbls) of L	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of	ass & obls) np f lead	pproval == (D ONLY. All Federal	
 w/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (13 cmt & 1370 sx (342 bbls) of a TOC 210'. ND NOP NU WH. 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w, (93 bbls) of class C tail cmt. Dri to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO.	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls F\	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of W, bump plu	ass & obls) np f lead g &	of Approval == CORD ONLY. All	
 w/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (13 cmt & 1370 sx (342 bbls) of a TOC 210'. ND NOP NU WH. 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w, (93 bbls) of class C tail cmt. Drr to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO.	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled a 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls FV 53 verified by the BLM We OPHILLIFS, sent to the Ho	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of W, bump plu	ass & obls) np f lead g & n System	ls of Approval == ECORD ONLY. All BLM Approval	
 W/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (12 cmt & 1370 sx (342 bbls) of TOC 210'. ND NOP NU WH. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) ASHLEY 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w, (93 bbls) of class C tail cmt. Drr to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO.	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled a 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls FV 53 verified by the BLM We OPHILLIFS, sent to the Ho	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of N, bump plu	ass & obls) np f lead g & n System	ls of Approval == ECORD ONLY. All BLM Approval	
 W/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (12 cmt & 1370 sx (342 bbls) of TOC 210'. ND NOP NU WH. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) ASHLEY 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w, (93 bbls) of class C tail cmt. Dri- to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO. is true and correct. Electronic Submission #23916 For CONOCC / BERGEN	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls FV 63 verified by the BLM We DPHILLIFS, sent to the Ho Title STAFF	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of W, bump plu II Information obbs REGULATC	ass & obls) np f lead g & n System DRY TECH	ls of Approval == ECORD ONLY. All BLM Approval	
 W/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (11 cmt & 1370 sx (342 bbls) of TOC 210'. ND NOP NU WH. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) ASHLEY Signature (Electronic 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w, (93 bbls) of class C tail cmt. Dri- to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO. is true and correct. Electronic Submission #23916 For CONOCC / BERGEN	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls FV 53 verified by the BLM We OPHILLIFS, sent to the Ho Title STAFF Date 03/18/2	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of W, bump plu II Information obbs REGULATC	ass & obls) np f lead g & n System DRY TECH	ls of Approval == ECORD ONLY. All BLM Approval	
 w/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (11 cmt & 1370 sx (342 bbls) of TOC 210'. ND NOP NU WH. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) ASHLEY Signature (Electronic Approved By onditions of approval, if any, are attach 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w. (93 bbls) of class C tail cmt. Dr. to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO. is true and correct. Electronic Submission #23916 For CONOCC / BERGEN = Submission) THIS SPACE FOR Fl 	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled a 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L blug , disp w/ 292 bbls FV 53 verified by the BLM We DPHILLIFS, sent to the Ho Title STAFF Date 03/18/2 EDERAL OR STATE Title	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of W, bump plu II Information obbs REGULATC	ass & obls) np f lead g & n System DRY TECH	ls of Approval == ECORD ONLY. All BLM Approval	
 w/ 13 3/8", 54.5#, J-55 csg s C lead cmt & 440 sx (107 bb circ 117 bbls to surf. NU BOI 4515'. RIH w/ 9 5/8", 36#, J- of class C lead cmt & 384 sx plug w/ 1760# & circ 85 bbls 13,820' (TD/MD) reached on bbls FW. Pumped 328 sx (1' cmt & 1370 sx (342 bbls) of TOC 210'. ND NOP NU WH. 14. 1 hereby certify that the foregoing Name (<i>Printed/Typed</i>) ASHLEY Signature (Electronic Approved By anditions of approval, if any, are attack trify that the applicant holds legal or e hich would entitle the applicant to com- 	et @ 996'. Pre-flush w/ 20 bbls l bls) of class C tail cmt. Drop plug P. Test csg 1500#- test good. Rl 55 csg set @ 4508'. Pre-flush w. (93 bbls) of class C tail cmt. Dr. to surf. PT 2500#- test good. Rl 3/3/14. RIH w/ 5 1/2", 23#, L-80 38 bbls) of LiteCRETE lead cmt conventional tail cmt. Dropped p . RDMO. is true and correct. Electronic Submission #23916 For CONOCC / BERGEN = Submission) THIS SPACE FOR Fl 	FW. Pumped 520 sx (15 g & disp w/ 118 bbls FW, IH w/ 12 1/4" bit & drilled / 20 bbls FW. Pumped 9 op plug, disp w/ 346 bbls IH w/ 8 3/4" bit & drilled a 0, csg set @ 13,809'. Pre & 425 sx (185 bbls) of L olug , disp w/ 292 bbls FV 63 verified by the BLM We OPHILLIFS, sent to the Ho Title STAFF Date 03/18/2 FEDERAL OR STATE 	3 bbls) of cla bump plug a l ahead to 02 sx (405 b s of FW, bun ahead to e-flush w/ 30 iteCRETE of N, bump plu II Information obbs REGULATC 014 OFFICE U	ass bbls) np f lead g & DRY TECH SE	OCD Conditions of Approval == Accepted for <u>RECORD ONLY.</u> All forms requires BLM Approval	

••;

- ·