

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30- <u>025-23138</u>
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator OXY USA Inc.		6. State Oil & Gas Lease No. <u>E2516</u>
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name <u>Aztec State</u>
4. Well Location Unit Letter <u>E</u> : <u>2310</u> feet from the <u>north</u> line and <u>910</u> feet from the <u>west</u> line Section <u>9</u> Township <u>17S</u> Range <u>33E</u> NMPM County <u>Log</u>		8. Well Number <u>9</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>4199'</u>		9. OGRID Number 16696
		10. Pool name or Wildcat <u>Maljamar GBSA</u>

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-4504' PBDT-4496' Perfs-4324-4454'

8-5/8" 28# csg @ 377' w/ 225sx, 11" hole, TOC-Surf-Circ
5-1/2" 14# csg @ 4498' w/ 250sx, 7-7/8" hole, TOC-3200'-TS

1. RIH & set CIBP @ 4274', M&P 35sx cmt to 4025'
2. Perf @ 2620', sqz 35sx cmt to 2520' WOC-Tag
3. Perf @ 1450' 1575', sqz 55sx cmt to 1400' WOC-Tag
4. Perf @ 427' sqz 140sx cmt to surface
10# MLF between plugs
Above ground steel tanks will be utilized

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 4/21/14

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: Makayla Brown TITLE Dist. Supervisor DATE 4/24/2014

Conditions of Approval (if any):

APR 28 2014

OXY USA Inc. - Proposed
Aztec State #9
API No. 30-025-23138

140sx @ 427'-Surface

11" hole @ 377'
8-5/8" csg @ 377'
w/ 225sx-TOC-Surf-Circ

Perf @ 427'

55sx @ 1575-1400' WOC-Tag

1450'
Perf @ 1575'

35sx @ 2620-2520' WOC-Tag

Perf @ 2620'

CIBP @ 4274' w/ 35sx to 4025'

7-7/8" hole @ 4504'
5-1/2" csg @ 4498'
w/ 250sx-TOC-3200'-TS

Perfs @ 4324-4454'

PB-4496'

TD-4504'

OXY USA Inc. - Current
Aztec State #9
API No. 30-025-23138

11" hole @ 377'
8-5/8" csg @ 377'
w/ 225sx-TOC-Surf-Circ

PB-4496'

TD-4504'

Perfs @ 4324-4454'

7-7/8" hole @ 4504'
5-1/2" csg @ 4498'
w/ 250sx-TOC-3200'-TS