

**Finley Resources, Inc**

**Shell State A 1**

**Lea County, NM**

**API# 30-025-08932**

**Equipment and Design:**

Finley's agent will use a "Closed Loop" system in the plugging of this well. The following equipment will be on location: (1) 250 bbl Steel pit

**Operations and Maintenance:**

During each day of operation, the rig crew will inspect and monitor the fluids contained within the steel tank and visually monitor any release that may occur. Should a release, spill or leak occur, the NMOCD District 1 office in Hobbs, NM (575 393-6161) will be notified as required in NMOCD rule 19.15.29.8.

**Closure:**

After plugging operations, fluids and solids will be hauled and disposed at New Mexico OCD approved disposal facility

**JUL 30 2014**

# Shell State A-1

660' FNL, 660' FWL of sec

Sec 16, T 22s R 36 E

Eunice Field, Lea Co, completion Date: 1937

GR 3574

API #

NM ID B-1167

12 ½ @ 243'  
w / 100 sx

## Est Tops:

Anhy 1455'

T Salt 1713'

B Salt 2762'

## TBG:

2 3/8" BPMJ [ 31.65 ] PS [ 4.00 ]

2" std SN [ 1.10 ] 4 2 3/8" 8rd EUE J-55 tbg.

[ 124.88 ] 7 jts 2 3/8" 8rd EUE J-55 tbg.

[ 187.56 ] 2 3/8" X 7"

TAC [ 2.87 ] 112 jts 2 3/8" J-55 8rd EUE tbg.

## Rds:

151 3/4 rods

9 5/8" @ 1478'  
w/450sx.

EOT @ 3853.42,

SN @ 3817.77,

TAC @ 3504.23

7" @ 3675' W/  
250sx  
Calc TOC: 1582'

Lower 7 Rivers & Queen :  
3553'-3872'

5 ½ liner @  
3695' -3847'

Current  
7/22/2014

# Shell State A-1

660' FNL, 660' FWL of sec

Sec 16, T 22s R 36 E

Eunice Field, Lea Co, completion Date: 1937

GR 3574

API #

NM ID B-1167

## Est Tops:

Anhy 1455'

T Salt 1713'

B Salt 2762'

3) Perf and Sqz @343' w/65 sxs circ to surf.

2) Perf and Sqz @1578' w/35 sxs.

1) CIBP @3453' w/25 sx cmt .

Lower 7 Rivers & Queen :  
3553'-3872'

5 ½ liner @  
3695' -3847'

12 ½ @ 243'  
w / 100 sx

9 5/8" @ 1478'  
w/450sx.

7" @ 3675' W/  
250sx.  
Calc TOC: 1582'

Current  
7/22/2014

