•	BL	UNITED STATE PARTMENT OF THE I JREAU OF LAND MANA	NTERIOR IGEMENT		OMB NO Expires: 5. Lease Serial No.	APPROVED D. 1004-0135 July 31, 2010
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					NMNM59392 6. If Indian, Allottee or Tribe Name	
<u> </u>						
	SUBMIT IN TRI	PLICATE - Other instru	ctions on reverse side.		7. If Unit or CA/Agree	ement, Name and/or No.
					8. Well Name and No. LUSK AHB FEDERAL 10H 9. API Well No. 30-025-40990-00-S1	
4. Location of Well	(Footage, Sec., T.	, R., M., or Survey Description	ı)		11. County or Parish, a	and State
Sec 35 T19S R32E NWNW 150FNL 660FWL			RECEIVED		LEA COUNTY, NM	
· 12.	. CHECK APPR	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF 1	NOTICE, RE	PORT, OR OTHER	R DATA
TYPE OF SUI	BMISSION	TYPE OF ACTION				
☐ Notice of Inte	ent	Acidize	Deepen	Productio	on (Start/Resume)	UWater Shut-Off
Subsequent R		Alter Casing	Fracture Treat	Reclamation		Well Integrity
Final Abando		Casing Repair	New Construction Plug and Abandon	Recompl		Other
	Simen Police	Convert to Injection			-	
If the proposal is t Attach the Bond I	under which the worl	k will be performed or provide	the Bond No. on file with BLM/BL	Required sub	equent reports shall be t	filed within 30 days
Attach the Bond u following comple testing has been c determined that th	under which the worl etion of the involved completed. Final Aba he site is ready for fir	k will be performed or provide operations. If the operation re andonment Notices shall be fil	The Bond No. on file with BLM/BI sults in a multiple completion or reco ed only after all requirements, includ	<ol> <li>Required subsompletion in a network</li> </ol>	ew interval, a Form 3160	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/JA-12/30 Tagged cerner Circulated hole Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a	under which the worl completed. Final Aba he site is ready for fin 10/14 20 3 nt at 7,217 ft. Dr e clean. Drilled c g with 500 gals X water with Baker 15 mins, good. If ft. 4 ne Spring 10,113 acid and frac'd wi	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tag ylene and 1200 gals 7-1, CRW-132 chemical. Pre Pressured casing to 1500 3 ft-14,208 ft (432 holes).	the Bond No. on file with BLM/BIA sults in a multiple completion or rec	A. Required sub- ompletion in a ne ling reclamation, clean. ed hole with 3 . Lost 20 psi ement. Est	w interval, a Form 316( have been completed, a down	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/JA-12/30 Tagged cerner Circulated hole Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a	under which the worl tion of the involved completed. Final Aba he site is ready for fir 10/14 29 3 nt at 7,217 ft. Dr e clean. Drilled c g with 500 gals X water with Baker 15 mins, good. If ft. 4 ine Spring 10,113 acid and frac'd wi J 2-7/8 inch 6.4 lb	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tac ylene and 1200 gals 7-1, CRW-132 chemical. Pre Pressured casing to 150 3 ft-14,208 ft (432 holes), ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft.	the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, includ to DV tool at 7,229 ft and drille gged at 14,209 ft. Circulated of 22 percent HCL acid. Displace essure test casing to 7000 psi 0 psi. Logged well to top of co . Acidized with 60,000 gallons is of 20/40 Premium CRC san	A. Required subsompletion in a neighbor in a	w interval, a Form 316( have been completed, a down	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/J-12/30 Tagged cerner Circulated hold Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a at 9,743 ft and	under which the worl etion of the involved completed. Final Aba he site is ready for fir 30/14 2.9 3 ant at 7,217 ft. Dr e clean. Drilled of g with 500 gals X water with Baker 15 mins, good. If ft. 4 ane Spring 10,113 acid and frac'd wi 12-7/8 inch 6.4 lb	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tac ylene and 1200 gals 7-1, CRW-132 chemical. Pre Pressured casing to 150 3 ft-14,208 ft (432 holes), ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft. Electronic Submission # For YATES PETF d to AFMSS for processin	the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, includ to DV tool at 7,229 ft and drille gged at 14,209 ft. Circulated of 22 percent HCL acid. Displace essure test casing to 7000 psi 0 psi. Logged well to top of co . Acidized with 60,000 gallons to f 20/40 Premium CRC san 238485 verified by the BLM We ROLEUM CORPORATION, sent g by BEVERLY WEATHERFOR	A. Required subsompletion in a neighbor in a	w interval, a Form 316( have been completed, a down ker System 4 (14BMW0358SE)	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/J-12/30 Tagged cerner Circulated hold Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a at 9,743 ft and	under which the worl tion of the involved completed. Final Aba he site is ready for fir additional states of the additional states of the additional states of the states of the states of the the spring 10,113 additional states of the the spring 10,113 additional states of the states of the s	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tac ylene and 1200 gals 7-1, CRW-132 chemical. Pre Pressured casing to 150 3 ft-14,208 ft (432 holes), ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft. For YATES PETF d to AFMSS for processin ATTS	the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, includ to DV tool at 7,229 ft and drille gged at 14,209 ft. Circulated of 22 percent HCL acid. Displace essure test casing to 7000 psi 0 psi. Logged well to top of co . Acidized with 60,000 gallons to f 20/40 Premium CRC san 238485 verified by the BLM We ROLEUM CORPORATION, sent g by BEVERLY WEATHERFOR	A. Required subsompletion in a neighbor of the subsompletion in a neighbor of the subsompletion, and the subsompletion, and the subsompletion of the subsomp	w interval, a Form 316( have been completed, a down ker System 4 (14BMW0358SE)	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/J-12/30 Tagged cerner Circulated hold Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a at 9,743 ft and	under which the worl tion of the involved completed. Final Aba he site is ready for fir 30/14 29 3 ont at 7,217 ft. Dr e clean. Drilled of g with 500 gals X water with Baker 15 mins, good. If ft. 4 ane Spring 10,113 acid and frac'd wi d 2-7/8 inch 6.4 lb that the foregoing is Committee wed) LAURA W/	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tag ylene and 1200 gals 7-1. CRW-132 chemical. Pre Pressured casing to 1500 3 ft-14,208 ft (432 holes) ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft. For YATES PETF d to AFMSS for processin ATTS	the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, includ to DV tool at 7,229 ft and drille gged at 14,209 ft. Circulated of /2 percent HCL acid. Displace essure test casing to 7000 psi 0 psi. Logged well to top of co . Acidized with 60,000 gallons to a f 20/40 Premium CRC san 238485 verified by the BLM We ROLEUM CORPORATION, sent g by BEVERLY WEATHERFOR Title REG R	A. Required subsompletion in a neighbor of the second seco	w interval, a Form 3160 have been completed, a down cer 4 (14BMW0358SE) ECHNICIAN	0-4 shall be filed once
Attach the Bond u following comple testing has been c determined that th 12/26/J-12/30 Tagged cerner Circulated hold Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a at 9,743 ft and	under which the worl tion of the involved completed. Final Aba he site is ready for fir 30/14 29 3 ont at 7,217 ft. Dr e clean. Drilled of g with 500 gals X water with Baker 15 mins, good. If ft. 4 ane Spring 10,113 acid and frac'd wi d 2-7/8 inch 6.4 lb that the foregoing is Committee wed) LAURA W/	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tag ylene and 1200 gals 7-1. CRW-132 chemical. Pre Pressured casing to 1500 3 ft-14,208 ft (432 holes) ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft. For YATES PETF d to AFMSS for processin ATTS	the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, including to DV tool at 7,229 ft and drille (2 percent HCL acid. Displace assure test casing to 7000 psi 0 psi. Logged well to top of ca . Acidized with 60,000 gallons is of 20/40 Premium CRC san 238485 verified by the BLM We ROLEUM CORPORATION, sent g by BEVERLY WEATHERFOR Title REG R Date 03/11/2	A. Required subsompletion in a neighbor of the second seco	w interval, a Form 3160 have been completed, a down cer 4 (14BMW0358SE) ECHNICIAN	0-4 shall be filed once and the operator has
Attach the Bond u following completesting has been c determined that the 12/26/J-12/30 Tagged cerner Circulated hold Pickled casing percent KCL w to 6980 psi in TOC at 4,170 1/1/14-2/18/14 Perforated Bor percent HCL a at 9,743 ft and 14. Thereby certify the Name (Printed/Ty) Signature	under which the worl tion of the involved completed. Final Aba he site is ready for fir it at 7,217 ft. Dr e clean. Drilled cg gwith 500 gals X; water with Baker 15 mins, good. If ft. 4 ne Spring 10,113 acid and frac'd wi d 2-7/8 inch 6.4 lt that the foregoing is Committee wped) LAURA W/ (Electronic St COEPT I, if any, are attached nt holds legal or equi	k will be performed or provide operations. If the operation re andonment Notices shall be fil nal inspection.) rilled 12 ft cement down to cement down to TD. Tag ylene and 1200 gals 7-1. CRW-132 chemical. Pre Pressured casing to 1500 3 ft-14,208 ft (432 holes)) ith a total of 3,898,640 lb o L-80 tubing at 9,750 ft. true and correct. Electronic Submission # For YATES PETF d to AFMSS for processin ATTS ubmission) THIS SPACE FC	e the Bond No. on file with BLM/BI/ sults in a multiple completion or rece ed only after all requirements, includ to DV tool at 7,229 ft and drille gged at 14,209 ft. Circulated of 22 percent HCL acid. Displace essure test casing to 7000 psi 0 psi. Logged well to top of co . Acidized with 60,000 gallons is of 20/40 Premium CRC san 238485 verified by the BLM We ROLEUM CORPORATION, sent g by BEVERLY WEATHERFOR Title REG R Date 03/11/2 DR FEDERAL OR STATE JAMES A TitleSUPERVI s not warrant or	A. Required subsompletion in a neighbor of the second seco	w interval, a Form 3160 have been completed, a down cer 4 (14BMW0358SE) ECHNICIAN	0-4 shall be filed once

• .