BS OC	Dubmit 3 Copies To Appropriate District Office District 1	State of New Mex Energy, Minerals and Natura			Form C-103 May 27, 2004
	USES N. French Dr., Hobbs, NM 88240		7105047005	WELL API NO. 30-025-29526	
03	1301 W. Grand Ave., Artesia, NM 88210	1220 South St. Francis Dr.			
•	District III			5. Indicate Type of Lease STATE F	EE 🗍
	1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease N	
RECEI	Santa Fe, NW 8/505 Sol. Francis Dr., Santa Fe, NM 87505		E-1582		
/m -		CES AND REPORTS ON WELLS	·	7. Lease Name or Unit A	greement Name
	(DO NOT USE THIS FORM FOR PROPOS			ARCO 28 STATE	g, comen , mine
	DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other P&A'D			8. Well Number	
				2	
	Name of Operator SUNDOWN ENERGY LP			9. OGRID Number 232611	
	3. Address of Operator			10. Pool name or Wildcat	
	13455 NOEL RD, STE. 2000, DALLAS, TX 75240			REEVES (QUEEN)	
	4. Well Location				
	Unit Letter B: 330 feet from the NORTH line and 1650 feet from the EAST line				
	Section 28 Township 18S Range 35E NMPM County LEA				
	11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3913.8' GR				
	Pit or Below-grade Tank Application or Closure				
	Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water				
	Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material				
	12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
	NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
	PERFORM REMEDIAL WORK ☑ PLUG AND ABANDON ☐ REMEDIAL WOR			· · · · · - · - · · ·	OF: NG CASING □
	TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR				
	PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB				
	OTHER: RE-ENTER P&A WELL 🖾 OTHER:				
	OTHER: RE-ENTER P&A WELL OTHER:				
	of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
	1- Dig out old cellar- weld on 8 5/8" and 4 1/2" stubs; nipple up well head & BOP				
	2- Pick up 3 ¾" bit and tubing; Clean out cement plugs (0-147' and 1620'-1760') and cement and CIBP at 4400'.				
	Continue to PBTD at approximately 4500'. POOH laying down work string.				
	3- Run 4 1/2" internally coated packer & 2 3/8" Internally coated tubing to				
	4430' (PERFS : 4480'- 448	3')- test for injectivity. Test anni	ulus as required	by State of New Mexico	
	4- Install injection line and place well in service.				
	I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below grade tank has been will be constructed or those according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .				
	SIGNATURE Delunda Diadou TITLE ADMIN. ASST. DATE 03/25/2014 Type or print name BELINDA BRADLEY E-mail address: bbradley@sundownenergy.com Telephone No. 432-943-8770				03/25/2014 043-8770
	For State Use Only				
	APPROVED BY: Conditions of Approval (if any):	TITLE		DATE	
	conditions of Approval (if any).				