

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-41647
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-1743
7. Lease Name or Unit Agreement Name Convoy BUC State
8. Well Number 1H
9. OGRID Number 025575
10. Pool name or Wildcat Triste Draw; Bone Spring, East

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter P : 15 feet from the South line and 400 feet from the East line
Unit Letter A : 330 feet from the North line and 400 feet from the East line
Section 28 Township 24S Range 33E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,481' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: Production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/6/14 - Drilled to 10,596' KOP and continued drilling directional.
12/6/14 - Drilled to 11,303' reduced hole to 8-1/2" and resumed drilling.
12/11/14 - Reached TD 8-1/2" hole to 15,824'.
12/13/14 - Set 5-1/2" 17# P-110 BT&C casing at 15,824'. Toe sleeve set at 15,808'. Float collar set at 15,821'. Cemented with 700 sacks LiteCrete + 0.2% D167 + 2% D174 + 0.02% D208 + 0.75% D800 + 0.2% D46 + 0.1% D65 (yld 2.45, wt 9.70). Tailed in with 1,735 sacks PVL + 3#/sx D042 + 0.7% D112 + 2% D154 + 2% D174 + 0.01% D208 + 0.2% D46 + 0.8% D800 + 0.2% D65 (yld 1.33, wt 13.50).

Spud Date:

11/14/14

Rig Release Date:

12/14/14

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Laura Watts

TITLE Regulatory Reporting Technician

DATE January 9, 2015

Type or print name

Laura Watts

E-mail address:

laura@yatespetroleum.com

PHONE:

575-748-4272

For State Use Only

APPROVED BY:

[Signature]

TITLE

Petroleum Engineer

DATE

01/16/15

Conditions of Approval (if any):

JAN 21 2015

MB

[Signature]