District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

## State of New Mexico Energy Minerals and Natural Resources

Form C-101 June 16, 2008

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit to appropriate District Office

AMENDED REPORT

1220 S. St. Fi	rancis Dr., S	anta Fe, N	NM 87505			Santa Fe, N	IM 875	505				
Al	PPLICA	TION	FOR PERN	IIT TO	DRI	LL, RE-EN	TER,	DEEP	EN, PLUGB		R ADD A ZONE	
Operator Name and Address OASIS WATER SOLUTIONS LLC PO BOX 36, MONUMENT, NM 88265										OGRID Number 310761		
									30 -	<sup>3</sup> API Number 30 -		
<sup>3</sup> Property Code <sup>3</sup> Property							Name "Well No.					
COOF												
° Proposed Pool 1 SWD;SAN ANDRES (96121)							<sup>10</sup> Proposed Pool 2					
	<u> </u>	, , , , , , , , , , , , , , , , , , , ,		7	Surface Lo	re Location						
UL or lot no. Section 17		Townshi	Township Range		Lot Idn Feet fro		T		Feet from the	East/West lin	e County	
		20S 37E							2200 We		Lea	
-		8 P	roposed Bo	ottom	Hole Location	ocation If Different From Surface						
UL or lot no.	UL or lot no. Section Townshi							South line	Feet from the	East/West line County		
							1.77.11.2			<u> </u>		
II no a	T. G.1		12 *** ** **		Addit	tional Well I	ntorma			- 15		
11 Work Type Code <b>N</b>			<sup>12</sup> Well Type Code <b>S</b>		<sup>13</sup> Cable/Rotary <b>Rotary</b>			,	Lease Type Code		15 Ground Level Elevation 3538	
16 Multiple			17 Proposed Dept				8 Formation		19 Contractor		<sup>20</sup> Spud Date	
No			4900		Lower San And							
Hole Size Casing Size Casing weight/foot								nt Progi	ram Sacks of Ce	ment	Estimated TOC	
17.5			13.375		48 #		1085		900		0	
12.25		9.625			32 #		2540		1700		0	
8.75		7		1	17 #		4170		1000		0	
		ļ										
Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.  Drill 17.5" hole to 1085' and set 13.375" surface casing, cement to surface. Drill out with 12.25 bit to 2540' (+/-) and set 9.625 intermediate casing, cement to surface. Drill 8.75" hole to 4170' (+/-), set 7" casing, cement to surface. Drill 6.124 hole to 4900. Set packer with plastic lined tubing within 100' of open hole interval.  SWD application submitted to Santa Fe. After SWD application is approved notify NMOCD Hobbs office at least 24 hours prior to conducting MIT test. MIT test will be performed prior to any injection.  BOP - once rig type is determined will notify NMOCD of BOP to be used by form C-103												
23 I hereby certify that the information given above is true and complete to the best of my knowledge and belief.  Signature:							OIL CONSERVATION DIVISION  Approved by:					
	le le	W	Dea									
Printed name: Eddie Seay				y \	Title:							
Title: Agent					Approval Date:			Expiration Date:				
E-mail Addre			seay04@lea	co.net								
Date: 1/12/15 Phone: 575-390-2454							Conditions of Approval Attached					