30-025-42397

EOG RESOURCES, INC. HAWK 26 FED #4H

Hydrogen Sulfide Plan Summary

- A. All personnel shall receive proper H2S training in accordance with Onshore Order III.C.3.a.
- B. Briefing Area: two perpendicular areas will be designated by signs and readily accessible.
- C. Required Emergency Equipment:
 - Well control equipment
 - a. Flare line 150' from wellhead to be ignited by flare gun.
 - b. Choke manifold with a remotely operated choke.
 - c. Mud/gas separator
 - Protective equipment for essential personnel.

Breathing apparatus:

- a. Rescue Packs (SCBA) 1 unit shall be placed at each breathing area, 2 shall be stored in the safety trailer.
- b. Work/Escape packs —4 packs shall be stored on the rig floor th sufficient air hose not to restrict work activity.
- c. Emergency Escape Packs —4 packs shall be stored in the doghouse for emergency evacuation.

Auxiliary Rescue Equipment:

- a. Stretcher
- b. Two OSHA full body harness
- c. 100 ft 5/8 inch OSHA approved rope
- d. 1-20# class ABC fire extinguisher
- H2S detection and monitoring equipment:

The stationary detector with three sensors will be placed in the upper dog house if equipped, set to visually alarm @ 10 ppm and audible @ 14 ppm. Calibrate a minimum of every 30 days or as needed. The sensors will be placed in the following places: Rig floor / Bell nipple / End of flow line or where well bore fluid is being discharged.

(Gas sample tubes will be stored in the safety trailer)

- Visual warning systems.
 - a. One color code condition sign will be placed at the entrance to the site reflecting the possible conditions at the site.
 - b. A colored condition flag will be on display, reflecting the current condition at the site at the time.
 - c. Two wind socks will be placed in strategic locations, visible from all angles.

EOG RESOURCES, INC. HAWK 26 FED #4H

■ Mud program:

The mud program has been designed to minimize the volume of H2S circulated to surface. The operator will have the necessary mud products to minimize hazards while drilling in H2S bearing zones.

■ Metallurgy:

All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.

• Communication:

Communication will be via cell phones and land lines where available.

EOG RESOURCES, INC. HAWK 26 FED #4H


PUBLIC SAFETY:	LISU	911 or
Lea County Sheriff's Department		(575) 396-3611
Rod Coffman		(575) 590 5011
Fire Department:		
Carlsbad		(575) 885-3125
Artesia		(575) 746-5050
Hospitals:		
Carlsbad		(575) 887-4121
Artesia		(575) 748-3333
Hobbs		(575) 392-1979
Dept. of Public Safety/Carlsbad		(575) 748-9718
Highway Department		(575) 885-3281
New Mexico Oil Conservation		(575) 476-3440
U.S. Dept. of Labor		(575) 887-1174
EOG Resources, Inc.	Office	(122) (96 2600
EOG / Midland	Omce	(432) 686-3600
Company Drilling Consultants:		
Danny Kiser Will Henderson	Cell	(432) 894-3417
Larry King	0011	(102) 05 1 0 1 1
Drilling Engineer		
Kirby Castille	Office	(432) 686-3657
•	Cell	(432) 559-4987
Drilling Manager		
Steve Munsell	Office	(432) 686-3609
	Cell	(432) 894-1256
Drilling Superintendent		
Ron Welch	Office	(432) 686-3695
	Cell	(432) 386-0592
Cactus Drilling		
Cactus Drilling		(580) 799-2752
Cactus 123 Drilling Rig	Rig	(432) 894-3417
Tool Pusher: Jack Herndon	Cell	(405) 519-6552
	Cell	(405) 250-6368
Larry Slife		(-0506-0506
Safety		
Reggie Phillips (HSE Manager)	Office	(432) 686-3747
	Cell	(432) 250-7507

Emergency Assistance Telephone List



SECTION 26, TOWNSHIP 24 SOUTH, RANGE 33 EAST, N.M.P.M. LEA COUNTY, NEW MEXICO

DETAIL VIEW SCALE: 1" = 100'



THIS PROPOSED PAD SITE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY EOG RESOURCES, INC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OF ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.