Submit 1 Copy To Appropriate District State of New Mexico Form C-103 Energy, Minerals and Natural Resources Revised July 18, 2013 District I - (575) 393-6161 WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II - (575) 748-1283 30-025-42362 OIL CONSERVATION DIVISION 811 S. First St., Artesia, NM 88210 5. Indicate Type of Lease District III - (505) 334-6178 1220 South St. Francis Dr. STATE 🛛 FEE \square 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV - (505) 476-3460 6. State Oil & Gas Lease No. 1220 S. St. Francis Dr., Santa Fe, NM VB-1834 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR Tele Delux 32 State PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well Other 4H 2. Name of Operator 9. OGRID Number NA/2 2 2015 **Endurance Resources LLC** 270329 3. Address of Operator 10. Pool name or Wildcat 203 W. Wall St., Suite 1000, Midland, Texas, 79701 97088-WC-025 G-08 52535340; Bone Spr 4. Well Location Unit Letter 150 feet from the North line and 660 feet from the East line Section 32 Township 25s Range 35e **NMPM** Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3218.9 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON □ REMEDIAL WORK ALTERING CASING | **TEMPORARILY ABANDON CHANGE PLANS** \boxtimes COMMENCE DRILLING OPNS. P AND A **PULL OR ALTER CASING** MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE П **CLOSED-LOOP SYSTEM** OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Well to spud on or about March 4, 2015 Request to: amend surface casing depth from 980 ft to 1055 ft (25 ft into Rustler)-cement to surface amend intermediate casing setting depth from 5251 ft to 9165 ft.(Top of Bone Spring) amend Intermediate casing string to 4100 ft of 40# HC L-80 + 5050' 40# HC P-110 - 2 stage cement to surface. amend to Drill 12 1/4" hole from 1055 ft. to 9165 ft. w/ oil base mud. 43.5# AMENDED Rig Release Date: Spud Date: I hereby certify that the information above is true and complete to the best of my knowledge and belief. **SIGNATURE** TITLE Engineer Date: Feb. 27,2015 Type or print name Manny Sirgo E-mail address: manny@enduranceresourcesllc.com PHONE: 432-242-4680 For State Use Only

Petroleum Engineer

TITLE

APPROVED BY:

Conditions of Approval (if any):