HOBBS OCT	)
-----------	---

OCD Hobbs

(August 2007)	DEPARTMENT OF THE	UNITED STATES EPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		OMB NO. 1004-0135 Expires: July 31, 2010			
	INDRY NOTICES AND REPO t use this form for proposals to	ORTS ON WELLS	MAY 2 6 201	5. Lease Serial No. NMNM03216			
abando	oned well. Use form 3160-3 (AF	D) for such proposa		6. If Indian, Allotte	e or Tribe Name		
SUBMI	T IN TRIPLICATE - Other instru	ctions on reverse sic	le. RECEIVED	7. If Unit or CA/Ag	reement, Name and/or No.		
1. Type of Well  ☑ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No. JACK B-17 2		
Name of Operator     CONOCOPHILLIPS COMPANY     CONOCOPHILLIPS COMPANY     CONOCOPHILLIPS COMPANY     Contact: GREG BRYANT     E-Mail: greg.bryant@basicenergyservices.com					9. API Well No. 30-025-11129-00-S1		
3a. Address MIDLAND, TX 79710	3b. Phone No. (include Ph: 432-563-3355 Fx: 432-563-3364	area code)	10. Field and Pool, or Exploratory LANGLIE				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State			
Sec 17 T24S R37E NWNW 660FNL 660FWL			·	LEA COUNTY, NM			
12. CHEC	CK APPROPRIATE BOX(ES) T	O INDICATE NATUI	RE OF NOTICE, R	<u>l</u> EPORT, OR OTH	ER DATA		
TYPE OF SUBMISSI	ON		TYPE OF ACTION				
	☐ Acidize	☐ Deepen		MITTING <sw< td=""><td></td></sw<>			
Notice of Intent	☐ Alter Casing	☐ Fracture Trea	CONVE				
☐ Subsequent Report	☐ Casing Repair	☐ New Constru	KEIUK	N TO	TA		
☐ Final Abandonment l		□ Plug and Aba		- Da	CHG LOC		
<b>_</b> =	☐ Convert to Injection		INT TO	PACTM P&A	NRP&A R		
If the proposal is to deeper Attach the Bond under whi following completion of the testing has been completed determined that the site is 1.  1) MIRU, NDWH, NUI 2) Set CIBP @ 2793' 3) Perf @ 1405' - Sqz 4) Perf @ 327' - Circ	BOP. POOH w/ Prod Equip - Circ hole w/ MLF. Cap w/ 25sx 50sx cmt to 1305'. WOC-Tag	give subsurface locations a e the Bond No. on file with lessults in a multiple completi led only after all requirement	and measured and true we BLM/BIA. Required su on or recompletion in a nts, including reclamation	ertical depths of all per ibsequent reports shall l new interval, a Form 3	tinent markers and zones.  be filed within 30 days  160-4 shall be filed once  1, and the operator has		
•			SEE	ATTACHED I	IOD.		
					- · · •		
			CONI	DITIONS OF	APPROVAL		
14. I hereby certify that the fo	Electronic Submission #	)PHILLIPS COMPĂNY, :	sent to the Hobbs	•			
Name (Printed/Typed) G	REG BRYANT		AGENT				
Signature (E	lectronic Submission)	Date	02/18/2015				

THIS SPACE FOR FEDERAL OR STATE OFFICE USE Title Approved By Conditions of approval if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. RFO Office

Title 18U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

# WELLBORE SKETCH ConocoPhillips Company -- Permian Basin Business Unit

Date: February 10, 2015 RKB @ 3298 DF @ 3294 GL @ 3288 Subarea: Lease & Well No. : Jack B17 - 02 Legal Description 660 FNL & 660 FVAL, Sec 170, T 24S, R 37E 12 1/4" Hole County: Lea State: New Mexico Field: Jaimai Date Spudded : 7/12/1947 Rig Released: 8/15/1947 API Number : 30-025-11129 Status: Producing OGRID 5073 Lease # NM 0321613 Lbs. Max intorval Date Type Gals Sand Pross ISIP Rate Down 10 3/4" 36# SpiralWeld @ 277" Cmi'd w/ 250 sxs, circ 8/17/1947 Set uncomented 4" liner @ 3646-3330". TOC @Surface 8/17/1947 Perf 3481-3646 3481-3646 1/31/1955 RO 8000 16,000 3481-3646 11/12/1979 15% HCL 6930 3481-3646 9/25/1980 15% HCL 500 2/4/1982 Liner collapsed @ 3619 9/6/1994 Set CMRT @ 3315 w/ 60' cmt on top, TOC 3255' Sqz w/ 90 sxs cmt below CMRT 15% HCL 9(6)1994 9/6/1994 300 Peri 2893, 2899, 2907, 2912, 2918, 2927, 2932, 2940, 2944, 2948, 2952, 2956, 2959, 2970, 2978, 2982, 9/7/1994 2985, 2990, 2996, 2998, 3004, 3008, 3014, 3024, Top Salt @ 1355. 3030, 3036, 3044, 3053, 3060, 3068, 3072, 3119, 3125; 3131, 3139, 3156 w/ 1 SPF 2893-3156 9/7/1994 15% HCL 4200 2893-3156 . 63,966 248,180 9/7/1994 CO2 Foam TOC 5 /12" @ 2226" (TS) Base Sall @ 2667 2893-3156 CMRT @ 3315' w/ 60' cmt on top; TOC @ 3255' Sqz below CMRT w/ 90 sxs cmt TOL @ 3330" 5 1/2" 14# J-55 @ 3358" Cmtd v// 600 sx; TOC @ 2226 (TS) Formation Tops: Rustler 3481-3646 Saledo Tansill Open Hole Yates 2850 3358-3653 Seven Rivers 3125 Queen 3480 Penrose Collapsed Liner @ 3619' 4" 11# Liner @ 3646 PBTD 3255

3653

#### WELLBORE SKETCH ConocoPhillips Company -- Permian Basin Business Unit

Date: February 10, 2015

RKB @ 3298 DF @ 3294' GL @ 3288' Subarea : Hobbs Lease & Well No. : Jack B17 - 02 Legal Description: 660 FNL & 660 FWL; Sec 17D, T 24S, R 37E 12 1/4" Hole County: State : New Mexico Lea Field: Jalmat Date Spudded : 7/12/1947 Rig Released: 8/15/1947 API Number: 30-025-11129 Siatus: Producing OGRID 5073 Loaso# NM 0321613 Lbs. Max Max Interval Date Туре Sand Press ISIP Rate Down 10 3/4" 36# SpiralWeld @ 277: Cmt'd w/ 250 sxs, circ 8/17/1947 Set uncomented 4" liner @ 3646-3330" TOC @Surface 8/17/1947 Pert 3481-3646' 3481-3646 P&S 150sx cmt @ 327'-3' 1/31/1955 RO 0008 18,000 3481-3646 11/12/1979 15% HCL 6930 3481-3646 9/25/1980 15% HCL 500 Liner collapsed @ 3619'
Set CMRT @ 3315 w/ 60' cmt on top, TOC 3255'
Sqz w/ 90 sxs cmt below CMRT 2/4/1982 9/6/1994 9/6/1994 9/6/1994 15% HCL 300 9/7/1994 Perf 2893, 2899, 2907, 2912, 2918, 2927, 2932, 2940, 2944, 2948, 2952, 2956, 2959, 2970, 2978, 2982, 2985, 2990, 2996, 2998, 3004, 3008, 3014, 3024, 3030, 3036, 3044, 3053, 3060, 3068, 3072, 3119. Top Salt @ 1355 # # M ... / 18 17 P&S 50sx cmt @ 1405'-1305' - Tag 3125, 3131, 3139, 3156 w/ 1 SPF 2893-3156 9/7/1994 15% HCL 4200 2893-3156 9/7/1994 CO2 Feam 63,966 248,160 TOC 5/12" @ 2226" (TS) Base Salt @ 2667 Spot 25sx cmt @ 2793'-2617' - Tag Sei CIBP @ 2793" :2893-3156 CMRT @ 3315' w/ 60' cmt on top; TOC @ 3255' Sqz below CMRT w/ 90 sxs cmt TOL @ 3330" 7 7/8" Hale 5 1/2" 14# J-55 @ 3358" 1355- 26.80 Cmt'd w/ 600 sx; TOC @ 2226' (TS) Formation Tops: Rustler Saledo .3481-3646 Tansill Open Hole Yates 2850 3358-3653 Seven Rivers 3125 Queen 34E0 Penrose Collepsed Liner @ 3519'

4" 11# Liner @ 3646"

PBTD 3255 3653

TO

## BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

J. Amos 3/6/11



## United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Carlsbad Field Office .620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

#### Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
  Operations must include adequate measures for stabilization and reclamation of disturbed lands.
  Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
  process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Solomon Hughes Natural Resource Specialist 575-234-5951

Jeffery Robertson Natural Resource Specialist 575-234-2230

Duncan Whitlock Environmental Protection Specialist 575-234-5926

Linda Denniston Environmental Protection Specialist 575-234-5974

Douglas Hoag Civil Engineering Tech 575-234-5979 Cody Layton Supervisory Multi Resources 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612