JUN 1 0 2015

## BC Operating, Inc. Hydrogen Sulfide Drilling Operations Plan

RECEIVED

#### Topaz 30 Federal Com #3H

SHL: 240' FNL & 2180' FEL of Unit Letter 'B', Section 31, T-20S, R-34E

BHL: 240' FNL & 1980' FEL of Unit Letter 'B', Section 30, T-20S, R-34E

Lea County, New Mexico

The H<sub>2</sub>S Drilling Operations Plan is submitted with Form 3160-3, Application for Permit to Drill, in accordance with BLM Onshore Oil and Gas Order Number 6 Section III.A.1., covering the above described well.

### I. Hydrogen Sulfide Training


All personnel, whether regularly assigned, contracted or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- A. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S).
- B. The prior use and maintenance of personal protective equipment and life support systems.
- C. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures and prevailing winds.
- D. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- A. The effects of H<sub>2</sub>S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- B. Corrective action and shut in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- C. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500') and weekly H<sub>2</sub>S and well control drills for all personnel in each crew. The initial training session shall include a review or the site specific H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.



## II. <u>H<sub>2</sub>S Safety Equipment and Systems</u>

Note: All  $H_2S$  safety equipment and systems will be installed, tested and operational when drilling reaches a depth of 500' above or three days prior to penetrating the first zone containing or reasonably expected to contain  $H_2S$  (prior to drilling out of the 13 3/8" surface casing shoe for this well).

A. Well Control Equipment (All BOP and BOP equipment is shown in Drilling Plan – Exhibits 1-4).

Flare line

Choke manifold and remotely operated chokes

Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.

Auxiliary equipment to include annular preventer, mud-gas separator and rotating head.

B. Protective equipment for essential personnel:

Mark II Surviveair 30 minute units located in the dog house and at briefing areas

C. H<sub>2</sub>S detection and monitoring equipment:

2 portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when H<sub>2</sub>S levels of 20 ppm are reached.

D. Visual Warning Systems:

Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate.

E. Mud Program: The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to the surface.

### F. Metallurgy:

All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool kill lines, choke manifold lines and valves shall be suitable for H<sub>2</sub>S services.

#### G. Communication:

Company vehicles equipped with cellular telephone.

BC Operating, Inc. has conducted a review to determine if an H<sub>2</sub>S Contingency Plan is needed for this well and has determined that there is minimal potential for the accumulation for any hazardous concentration of H<sub>2</sub>S; therefore, no H<sub>2</sub>S Contingency Plan has been submitted for this well.

ing service of the se

## **WARNING**

# YOU ARE ENTERING AN H<sub>2</sub>S AREA AUTHORIZED PERSONNEL ONLY

- 1. BEARDS OR CONTACT LENSES NOT ALLOWED
- 2. HARD HATS REQUIRED
- 3. SMOKING IN DESIGNATED AREAS ONLY
- 4. BE WIND CONSCIOUS AT ALL TIMES
- 5. CHECK WITH BC OPERATING, INC. FORMAN AT MAIN OFFICED

**BC OPERATING, INC.** 

432-684-9696

bet made at 1 to 1 to 1 to 1 to 1 to 1

## **Emergency Call List**

BC Operating, Inc. Office 432-684-9696

Deane Durham 432-684-9696 (Office)

432-431-9701 (Cell)

Nic Klopp 432-684-9696 (Office)

432-422-2510 (Cell)

Bruce Madden 432-684-9696 (Office)

432-894-0721 (Cell)

## **Emergency Response Numbers**

New Mexico State Police 575-392-5580

Lea County Sheriff Dept 575-396-3611

Lea Regional Medical Center 575-492-5000

Ambulance 911

**BC Operating, Inc.** Topaz 30 Fed Com Battery Diagram



