Submit 1 Copy To Appropriate Distr Office District I – (575) 393-6161	State of New Mexico Energy, Minerals and Natural Resources		Form C-103 Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 882 <u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 874 <u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	OIL CONSERVATION 1220 South St. Fra Santa Fe, NM 8	ncis Dr.	WELL API NO. 30-025-42538 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name Brown Bear 36 State
1. Type of Well: Oil Well	Gas Well Other	OBBS OCD	8. Well Number 702H
Name of Operator EOG Resources,	Inc.	2fna	9. OGRID Number 7377
3. Address of Operator P.O. Box 2267 M	IJU	L 1 3 5013	10. Pool name or Wildcat WC-025 G-09 S253336D; Upper WC
4. Well Location N 244 South RECEIVED 1379 West			
Unit Letter Section	teet from the	line and ange 33E	feet from the line NMPM County Lea
	11. Elevation (Show whether DF 3319' GR		County
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE C PERFORM REMEDIAL WOR TEMPORARILY ABANDON PULL OR ALTER CASING DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM	F INTENTION TO: K PLUG AND ABANDON CHANGE PLANS CHANGE PLANS CHANGE COMPL CHANGE COMPL CHANGE COMPL CHANGE COMPL CHANGE COMPL CHANGE C	SUBS REMEDIAL WORK COMMENCE DRII CASING/CEMENT	LING OPNS. P AND A
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
5/19/15 Spud 14-3/4" hole. 5/20/15 Ran 25 jts 10-3/4", 40.5#, J55 STC casing set at 1129'. Cement lead w/ 600 sx Class C, 13.5 ppg, 1.75 CFS yield; tail w/ 200 sx Class C, 14.8 ppg, 1.34 CFS yield. 5/21/15 Circulated 292 sx cement to surface. WOC 24+ hrs. Tested casing to 1500 psi for 30 minutes. Test good. 5/22/15 Resumed drilling 9-7/8" hole.			
Spud Date: 5/19/15	Rig Release D	Pate:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Star	— IIILE	gulatory Analyst	DATE
Type or print name For State Use Only	E-mail addre	ss: troleum Enginee	PHONE: 432-686-3689
APPROVED BY: Conditions of Approval (it an)	TITLE_		DATE 07/23/13
11		JIII - 2	8 2015 MB