Submit 1 Copy To Appropriate District Office	State of New Me		Form C-103
District I – (575) 393-6161 Energy 1625 N. French Dr., Hobbs, NM 88240	y, Minerals and Natu	ral Resources	Revised July 18, 2013 WELL API NO.
District II - (575) 748-1283	CONSERVATION	DIVISION	30-025-06794
1625 N. French Dr., Hobbs, NM 88240 District III – (575) 748-1283 811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505		cis Dr.	5. Indicate Type of Lease STATE ☐ FEE ☐
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460 Santa Fe, NM 87505		505 L	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM PS 87505			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name S.J. SARKEYS "26"
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other: WATER INJECTION			8. Well Number 4
2. Name of Operator			9. OGRID Number
CHEVRON U.S.A. INC. 3. Address of Operator			4323 10. Pool name or Wildcat
15 SMITH RD MIDLAND, TX 79705		BLINEBERRY OIL AND GAS (PRO GAS)	
4. Well Location			
Unit Letter F: 1980 feet from the NORTH line and 1980 feet from the WEST line			
Section 26 Township 21S Range 37E NMPM LEA County 11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
3816' GL	ion (show whether 21,		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK			
TEMPORARILY ABANDON			
DOWNHOLE COMMINGLE			
CLOSED-LOOP SYSTEM	1 57	OTUED.	
OTHER: RE-ENTER ? REPLUS OTHER:			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
WELL CURRENTLY HAS PRESSURE AND SLIGHT WATERFLOW ON 13" SURFACE CASING.			
1. NOTIFY NMOCD PRIOR TO MIRU.			
 MIRU, DRILL OUT CEMENT IN 5-1/2" CSG TO 1020'. SPOT 25SX OF CLASS "C" CEMENT FROM 1020' TO 800'. WOC & TAG. 			
4. PERF AND SQUEEZE 55SX OF CLASS "C" CEMENT FROM 650' TO 450'. IF CANNOT SQUEEZE, SPOT CEMENT			
AND SI WELL WHILE ATTEMPTING TO SQUEEZE CEMENT. WOC & TAG. 5. PERF AND SQUEEZE 110SX OF CLASS "C" CEMENT FROM 400' TO SURFACE. IF CANNOT SQUEEZE, SPOT			
5. PERF AND SQUEEZE 110SX OF CLASS "C" CEMENT FROM 400' TO SURFACE. IF CANNOT SQUEEZE, SPOT CEMENT AND SI WELL WHILE ATTEMPTING TO SQUEEZE CEMENT.			
6. CUT-OFF WH AND INSTALL DRY HOLE MARKER.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE: M. La Road TITLE: PROJECT MANAGER DATE: 07/28/2015			
Type or print name: M. LEE ROARK E-mail address: LROARK@CHEVRON.COM PHONE: 432-687-7279			
APPROVED BY: Value Stown DITLE 1 Suffer Super BOLDATE 8 17/2015 Conditions of Approval (if any):			