

**Owl SWD Operating, LLC
Brininstool Ranch SWD Well No.3
Section 19, Twp 23-S, Rng 33-E
Lea County, New Mexico**

Well Program - New Drill

Objective: Drill new well for commercial salt water disposal into the Devonian, Silurian and Ordovician formations. (Note: Ordovician might only be accessed for logging rathole, mudlogging and e-logging to determine final depths.)

I. Geologic Information - Devonian / Silurian Formations

This area of the Devonian consists of dolomites with some cherty dolomites characterized by intercrystalline and vugular porosity. Additional porosity can be found when the well bore encounters detrital carbonates interspersed throughout.

Estimated Formation Tops:

B/Fresh Water	400
T/Rustler	1283
T/Salado	1363
Delaware Sand	5142
Bone Spring	8778
Wolfcamp	12258
Strawn	14096
Atoka	14273
Morrow	15043
Middle Morrow	15393
Lower Morrow	15561
Woodford	15750
Devonian	16000
Silurian	17800
TD (Ordovician)	*18000

*Please see narrative portion of drilling/pipe specs for TD options.

2. Drilling Procedure

- a. MIRU drilling rig and associated equipment. Set up H₂S wind direction indicators; brief all personnel on Emergency Evacuation Routes.
- b. All contractors conduct safety meeting prior to current task. All equipment inspected daily. Repair / replace as required.
- c. Well spud operations commence.
- d. Mud logger monitoring returns; cuttings & waste hauled to specified facility. (Sundance, Lea County)
- e. After surface casing set/drilled; if H₂S levels >20ppm detected, implement H₂S Plan accordingly. (e.g., cease operations, shut in well, employ H₂S safety trailer & personnel safety devices, install flare line, etc. - refer to plan.)
- f. Spills contained & cleaned up immediately. Repair or otherwise correct the situation within 48 hours before resuming operations. Notify OCD within 24 hours. Remediation started ASAP if required. Operator shall comply with 19.15.29 NMAC and 19.15.30 NMAC, as appropriate.

AUG 31 2015

Well Program - New Drill (cont.)

g. Sundry forms filed as needed - casing, cement, etc. - operations continue to completion.

3. Casing program - Casing designed as follows:

STRING	HOLE SZ	DEPTH	CSG SZ	COND	WT/GRD	CLLPS/BR	TNSN
Surface	24.0"	0-1,300'	20.0"	New	106.5 lb. J/K-55	1.125/1.1	1.8
Intermediate	17.5"	0-5,150'	13.375"	New	68 lb. HPC-110	1.125/1.1	1.8
2nd Inter	12.25"	0-12,000'	9.875"	New	62.8 lb. P-110	1.125/1.1	1.8
Prod/ Liner*	8.5"	11,800'-16,400'	7.0"	New	32.0 lb. L-80 BT&C	1.125/1.1	1.8
Openhole*	5.875" hole	16,400'-17,550'	OH	n/a	n/a	n/a	n/a

Notes:

- ✓ On both Intermediate casing strings, the cement will be designed to circulate to surface. Both strings will have cement bond logs run (radial, CET or equivalent) to surface.
- ✓ While running all casing strings, the pipe will be kept a minimum of 1/3 full at all times to avoid approaching the collapse pressure of casing.
- ✓ * Based on mudlogging and e-logs, 7.0" casing shoe may be set between 16,000' and 16,400'. Similarly, TD may be from 17,550' to 18,000' as determined by logging and suitable porosity has been exposed. IN ANY EVENT, maximum openhole interval would be from 16,000' to 18,000'.

4. Cementing Program:

Surface – LEAD 1255 sx (13.5#; 1.76 ft³/sk); TAIL 216 (14.8#; 1.34 ft³/sk) w/ 50 % excess; circulated to surface

1st Intermediate – LEAD 3763 sx (12.7#; 1.94 ft³/sk); TAIL 470 sx (14.8#; 1.33 ft³/sk) 50% excess; circulated to surface

2nd Intermediate – LEAD 2042 sx (11.9#; 2.45 ft³/sk); TAIL 261 sx (14.2#; 1.27 ft³/sk) 30% excess; circulated to surface.

Prod Liner – 691 sx (14.2#; 1.27 ft³/sk) 30% excess; TOC = 11,800' calc.

5. Pressure Control - BOP diagram is attached to this application. All BOP and related equipment shall comply with well control requirements as described NMOCD Rules and Regulations and API RP 53, Section 17. Minimum working pressure of the BOP and related equipment required for the drillout shall be 5000 psi. The NMOCD Artesia district office shall be notified a minimum of 4 hours in advance for a representative to witness BOP pressure tests. The test shall be performed by an independent service company utilizing a test plug (no cup or J-packer). The results of the test shall be recorded on a calibrated test chart submitted to the OCD district office. Test shall be conducted at:

- a. Installation;
- b. after equipment or configuration changes;
- c. at 30 days from any previous test, and;
- d. anytime operations warrant, such as well conditions

Well Program - New Drill (cont.)

6. Mud Program & Monitoring - Mud will be balanced for all operations as follows:

DEPTH	MUD TYPE	WEIGHT	FV	PV	YP	FL	Ph
0-1300'	FW Spud Mud	8.5-9.2	70-40	20	12	NC	10.0
1300'-5150'	Brine Water	9.8-10.2	28-32	NC	NC	NC	10.0
5150'-12,000'	FW/Gel	8.7-9.0	28-32	NC	NC	NC	9.5-10.5
12,000'-16,400'	XCD Brine Mud	11.0-	45-48	20	10	<5	9.5-10.5
16,400'-17,550'	FW Mud	8.4-8.6	28-30	NC	NC	NC	9.5-10.5

Mud and all cuttings monitored w/ cuttings recovered for disposal. Returns shall be visually and electronically monitored. In the event of H₂S, mud shall be adjusted appropriately by weight and H₂S scavengers.

7. Auxiliary Well Control and Monitoring – Hydraulic remote BOP operation, mudlogging to monitor returns.

8. H₂S Safety - This well and related facilities are not expected to have H₂S releases. However, there may be H₂S in the area. There are no private residences or public facilities in the area but a contingency plan has been developed. Owl SWD Operating, LLC will have a company representative available to personnel throughout all operations. If H₂S levels greater than 10ppm are detected or suspected, the H₂S Contingency Plan will be implemented at the appropriate level.

H₂S Safety - There is a low risk of H₂S in this area. The operator will comply with the provisions of Onshore Oil and Gas Order #6.

- a) Monitoring - all personnel will wear monitoring devices.
- b) Warning Sign - a highly visible H₂S warning sign will be placed for obvious viewing at the vehicular entrance point onto location.
- c) Wind Detection - two (2) wind direction socks will be placed on location.
- d) Communications - will be via cellular phones and/or radios located within reach of the driller, the rig floor and safety trailer when applicable.
- e) Alarms - will be located at the rig floor, circulating pump / reverse unit area and the flareline and will be set for visual (red flashing light) at 15 ppm and visual and audible (115 decibel siren) at 20 ppm.
- f) Mud program - If H₂S levels require, proper mud weight, safe drilling practices and H₂S scavengers will minimize potential hazards.
- g) Metallurgy - all tublars, pressure control equipment, flowlines, valves, manifolds and related equipment will be rated for H₂S service if required.

The Owl SWD Operating, LLC H₂S Contingency Plan will be implemented if levels greater than 10ppm H₂S are detected.

Well Program - New Drill (cont.)

9. Logging, Coring and Testing – Owl SWD Operating expects to run;

- a. CBL (Radial, CET or equivalent) on both intermediate casing strings.
- b. Standard porosity log suite from TD to approximately 15,000'.
- c. No corings or drill tests will be conducted. (The well may potentially be step rate tested in the future if additional injection pressures are required.)

10. Potential Hazards - No abnormal pressures or temperatures are expected.

No loss of circulation is expected to occur with the exception of drilling into the target disposal zone. All personnel will be familiar with the safe operation of the equipment being used to drill this well.


The maximum anticipated bottom-hole pressure is 9000 psi and the maximum anticipated bottom-hole temperature is 190° F.

11. Waste Management - All drill cuttings and other wastes associated with and drilling operations will be transported to the Lea County Sundance facility (or alternate), permitted by the Environmental Bureau of the New Mexico Oil Conservation Division.

12. Anticipated Start Date - Upon approval of all permits for SWD, operations would begin within 30 days. Completion of the well operations will take six to seven weeks. Installation of the tank battery, berms, plumbing and other and associated equipment would be occurring during the same interval. In any event, it is not expected for the construction phase of the project to last more than 60 days, depending on availability of contractors and equipment. At the time of this submittal, and subject to the availability of the drilling contractor, the anticipated start date is:

September 15, 2015.

13. Configure for Salt Water Disposal – Subsequent to SWD permit approval from OCD and prior to commencing any work, an NOI sundry(ies) will be submitted to configure the well for SWD and will detail the completion workover including all work otherwise described above, any change to the procedure noted herein and to perform mechanical integrity pressure test per BLM and OCD test procedures. (Notify BLM and NMOCD 24 hours prior.) The casing/tubing annulus will be monitored for communication with injection fluid or loss of casing integrity. Anticipated daily maximum volume is 25,000 bpd and average of 15,000 bpd at a maximum surface injection pressure of 3200 psi (0.2 psi/ft to uppermost injection interval, i.e., casing shoe). If satisfactory disposals rates cannot be achieved at default pressure of .2 psi/ft, Owl Oil and Gas, LLC will conduct a step-rate test and apply for an injection pressure increase 50 psi below parting pressure.



LONQUIST & CO. LLC



AUSTIN | WICHITA
HOUSTON | CALGARY

Texas License F-8952

3345 Bee Cave Road, Suite 201
Austin, Texas 78746
Tel: 512.732.9812
Fax: 512.732.9816

OWL SWD Operating, Inc

Country: USA

Survey/STR:

API No.:

State ID No.:

Drawn: MMC

Rev No:

Brininstool SWD No. 3

State/Province: New Mexico

Site:

Field:

Project No:

Reviewed: RSC

Notes: Devonian completion with a 9.875" Intermediate 2 casing.

County/Parish: Lea

Status: To Be Drilled


Ground Elevation:

Date: 7/21/2015

Approved: SLP

APD Calculation Summary C295:K384										
2nd Dia	20	surface csg in a 24 inch hole.			Design Factors			SURFACE		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight		
"A"	106.50	K 55	ST&C	6.93	1.13	0.88	1,300	138,450		
"B"							0	0		
w/8.4#/g mud, 30min Sfc Csg Test psig: 1,120				Tail Cmt	does not	circ to sfc.	Totals:	1,300	138,450	
Comparison of Proposed to Minimum Required Cement Volumes										
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE	Min Dist Hole-Cplg	
24	0.9599	1471	2496	1327	88	10:13	1620	2M	1.50	
Burst Frac Gradient(s) for Segment(s) A, B = b All > 0.70. OK.										
#N/A										
3rd Dia	13 3/8	casing inside the 20			#N/A	Design Factors			INTERMEDIATE	
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight		
"A"	68.00	HPP 110	ST&C	#N/A	#N/A	#N/A	5,150	350,200		
"B"							0	0		
w/8.4#/g mud, 30min Sfc Csg Test psig:				Totals:	5,150	350,200				
The cement volume(s) are intended to achieve a top of				0	ft from surface or a			1300	overlap.	
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE	Min Dist Hole-Cplg	
17 1/2	0.6946	4233	7930	#N/A	#N/A	10:29	4092	5M	#N/A	
#N/A										
4th Dia	9 7/8	casing inside the 13 3/8			Design Factors			PRODUCTION		
Segment	#/ft	Grade	Coupling	Joint	Collapse	Burst	Length	Weight		
"A"	62.80	p 110	BUTT	2.10	1.53	1.32	12,000	753,600		
"B"							0	0		
w/8.4#/g mud, 30min Sfc Csg Test psig: 2,640				Totals:	12,000	753,600				
The cement volume(s) are intended to achieve a top of				0	ft from surface or a			5150	overlap.	
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE	Min Dist Hole-Cplg	
12 1/4	0.2866	2303	5330	#N/A	#N/A	10:80	5593	10M	0.81	
Class 'H' tail cmt yld > 1.20				MASP is within 10% of 5000psig, need exrta equip?						
5th Dia	7	Liner w/top @ 11800			Design Factors			LINER		
Segment	#/ft	Grade	Coupling	Body	Collapse	Burst	Length	Weight		
"A"	32.00	P 110	BUTT	1.95	1.17	1.27	4,600	147,200		
"B"							0	0		
w/8.4#/g mud, 30min Sfc Csg Test psig: 992				Totals:	4,600	147,200				
The cement volume(s) are intended to achieve a top of				11800	ft from surface or a			200	overlap.	
Hole Size	Annular Volume	1 Stage Cmt Sx	1 Stage CuFt Cmt	Min Cu Ft	1 Stage % Excess	Drilling Mud Wt	Calc MASP	Req'd BOPE	Min Dist Hole-Cplg	
8 1/2	0.1268	691	878	595	48	10:80			0.422	
Capitan Reef est top XXXX.				MASP is within 10% of 5000psig, need exrta equip?						

RIG 224 LAYOUT




MINIMUM LOCATION SIZE FROM WELL CENTER	
TO CATWALK	150'-0"
TO GENERATORS	190'-0"
TO RESERVE PIT	80'-0"
TO DOG HOUSE SIDE	125'-0"

Brininstool SWD No.3 Setup

North →

0'-0" 20'-0" 40'-0"

MOUSE HOLE
CONFIGURATION



SCALE 4X
RAT HOLE DEPTH--68' AT 2" SLOPE




SIDEWINDER
D R I L L I N G

JAN 31, 2015




Brininstool SWD No.3 – Site Layout w/ H2S & Safety Items Sidewinder Rig 224




1. MIRU Drilling and drilling support contractors / equipment.
2. Set up H2S wind direction indicators; brief all personnel on Emergency Evacuation Routes.
3. All contractors conduct safety meeting prior to current task.
4. If H2S levels >20ppm detected, implement H2S Plan accordingly. (e.g., cease operations, shut in well, employ H2S safety trailer & personnel safety devices, install flare line, etc. - refer to plan.)
5. All equipment inspected daily. Repair / replace as required.
6. Mud logger monitoring returns; cuttings & waste hauled to specified facility. CRI - LEA COUNTY
7. Spills contained & cleaned up immediately. Repair or otherwise correct the situation within 48 hours before resuming operations. Notify OCD within 24 hours. Remediation started ASAP if required. Operator shall comply with 19.15.29 NMAC and 19.15.30 NMAC, as appropriate.
8. Sundry forms filed as needed - casing, cement, etc. - operations continue to completion

BOPE 5K & Closed-Loop Schematic (w/ 13.375" Rams)



CHOKE MANIFOLD DIAGRAM - SEDEWINDER RIG 224



Rtg.	Qty.	224		BOP Inventory Sheet	
		Annular Preventer			
		Model	Size	hydrill	
		Working Pressure	13 5/8	3000	
		Serial Number		307291	
		Top Connection		3000	
		Bottom Connection		5000	
		Ram Preventers			
		Double / Single	double		
		Model	lasson s		
		Size	13 5/8	5000	
		Working Pressure		134754	
		Serial Number		5000	
		Top Connection		5000	
		Bottom Connection		5000	
		Qty. Side Outlets	4		
		Size of Side Outlets	4"		
		PSI Rating of Side Outlets	5000		
		Ram Preventers			
		Double / Single	n/a		
		Model	n/a		
		Size	n/a		
		Working Pressure	n/a		
		Serial Number	n/a		
		Top Connection	n/a		
		Bottom Connection	n/a		
		Qty. Side Outlets	n/a		
		Size of Side Outlets	n/a		
		PSI Rating of Side Outlets	n/a		
		Rams			
		Size & Designation	variable rams / top		
		Size & Designation	blindes / bottom		
		Size & Designation			
		Size & Designation			
		Size & Designation			
		Wing Valves			
		Size	4"		
		Working Pressure	5000		
		Serial Number	v622		
		Designation	kill side		
		Flange Size	pr160		
		Flange Rating	5000		
		Wing Valves			
		Size	4"		
		Working Pressure	5000		
		Serial Number	n/a		
		Designation	check side		
		Flange Size	pr160		
		Flange Rating	5000		
		Drilling Spool			
		Size	13 5/8		
		Working Pressure	5000		
		Serial Number	1130126764		
		Top Connection	5000		
		Bottom Connection	5000		
		Qty. Side Outlets	2		
		Size of Side Outlets	4		
		PSI Rating of Side Outlets	5000		
		Choke Manifold #1 Valve			
		Make	n/a		
		Model	n/a		
		Serial Number	n/a		
		Choke Manifold #2 Valve			
		Make	horn equipment		
		Model	130053		
		Serial Number	39890		
		Choke Manifold #3 Valve			
		Make	horn equipment		
		Model	130053		