	UNITED STATES			OCD-HO	APPROVED	
(Abgust 2007) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an HOBBS OCD abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side SEP 39 2003 1. Type of Well Oil Well Gas Well Ø Other: INJECTION				OMB NO. 1004-0135 Expires: July 31, 2010 5. Lease Serial No. NMNM56265 6. If Indian, Allottee or Tribe Name		
			BSOCD 6.			
			And in the local division in the local divis			
			RECEIVED 8. Well Name and FEDERAL L 1		No.	
2. Name of Operator Contact: VICKI JOHNSTON NEARBURG PRODUCING COMPANYE-Mail: vjohnston1@gmail.com			9.	9. API Well No. 30-025-20811		
		Phone No. (include area code 830-537-4599	io. (include area code) 10. Field and Po 37-4599 SWD; YAT		ol, or Exploratory ES-SEVEN RIVERS	
4. Location of Well (Footage, Sec., T		11. County or Parish, and State				
Sec 25 T20S R34E Mer NMP	SENW 1650FNL 1980FWL	-		LEA COUNTY,	NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO INE	ICATE NATURE OF	NOTICE, REPO	RT, OR OTHE	ER DATA	
TYPE OF SUBMISSION		TYPE O	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut	
	Alter Casing	Fracture Treat	Reclamation	1. J. C. S.	U Well Integr	
Subsequent Report	Casing Repair	New Construction	Recomplete		Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily	Abandon		
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved	Illy or recomplete horizontally, give su k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only	ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec	ured and true vertica A. Required subseque ompletion in a new i	ed work and appro I depths of all perti- tent reports shall be nterval, a Form 310	nent markers and zo e filed within 30 day 60-4 shall be filed o	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fin Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of C 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pact out plug. Release from On/Of down tbg and out casing w/15	eration (clearly state all pertinent detailly or recomplete horizontally, give st k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pac x 7" AS 1x pkr w/1.875" F profi at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compre f tool and PU several feet off po 0 bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #312733	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ing tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject	ng date of any propos ured and true vertica A. Required subseque ompletion in a new i ding reclamation, hav sing Company wi l jts 2-7/8" L-80 ft H with 7" dump bailer, RIH w/redressed JE 8rd (TK-70 bll. RIH w/pump s. Circulate Latch back on to tivity test.	eed work and appro I depths of all perti- tent reports shall be nterval, a Form 31 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fin Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pact out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detailly or recomplete horizontally, give site will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pace X 7" AS 1x pkr w/1.875" F profile at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# comprefit tool and PU several feet off profile OP & NU wellhead. Pump out true and correct. Electronic Submission #312733: For NEARBURG PROD Committed to AFMSS for pro	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ing tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject overified by the BLM We UCING COMPANY, sent cessing by LINDA JIMEN	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 fe H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 bll. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs IEZ on 08/20/2015	eed work and appro I depths of all perti- ient reports shall be nterval, a Form 310 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fin Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pact out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detailly or recomplete horizontally, give site will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pace X 7" AS 1x pkr w/1.875" F profile at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# comprefit tool and PU several feet off profile OP & NU wellhead. Pump out true and correct. Electronic Submission #312733: For NEARBURG PROD Committed to AFMSS for pro	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ing tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject overified by the BLM We UCING COMPANY, sent cessing by LINDA JIMEN	ng date of any propos ured and true vertica A. Required subsequ ompletion in a new i ding reclamation, hav ting Company wi ing Company wi ting Company wi ting Company wi ting Company wi hit s2-7/8" L-80 G H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test.	eed work and appro I depths of all perti- ient reports shall be nterval, a Form 310 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fin Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pact out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detailly or recomplete horizontally, give set k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pac x 7" AS 1x pkr w/1.875" F profi at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compre f tool and PU several feet off po 0 bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #31273: For NEARBURG PROD Committed to AFMSS for pro	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ing tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject overified by the BLM We UCING COMPANY, sent cessing by LINDA JIMEN	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 C H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs IEZ on 08/20/2015 JCTION MANAGE	eed work and appro I depths of all perti- ient reports shall be nterval, a Form 310 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fit Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of C 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pac out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detailly or recomplete horizontally, give set k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pac x 7" AS 1x pkr w/1.875" F profi at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compre f tool and PU several feet off po 0 bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #31273: For NEARBURG PROD Committed to AFMSS for pro	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ng tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject by LINDA JIMEN Title PRODU	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 & H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs IEZ on 08/20/2015 JCTION MANAGE 015	eed work and appro I depths of all perti- ient reports shall be nterval, a Form 310 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fit Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of C 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pac out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detail lily or recomplete horizontally, give si k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pac x 7" AS 1x pkr w/1.875" F profi at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compre f tool and PU several feet off pio 0 bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #31273: For NEARBURG PROD Committed to AFMSS for pro N	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ng tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject by LINDA JIMEN Title PRODU	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 & H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs IEZ on 08/20/2015 JCTION MANAGE 015	eed work and appro I depths of all perti- ient reports shall be nterval, a Form 310 ve been completed, Il set a 5.5#	nent markers and zo e filed within 30 day 60-4 shall be filed o	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fit Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of C 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pac out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detail lily or recomplete horizontally, give si k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pac x 7" AS 1x pkr w/1.875" F profi at 4000'. POOH w/Baker setti IBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compre f tool and PU several feet off pio 0 bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #31273: For NEARBURG PROD Committed to AFMSS for pro N	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ng tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject by LINDA JIMEN Title PRODU	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 & H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs IEZ on 08/20/2015 JCTION MANAGE 015	ed work and appro depths of all perti- ient reports shall be nterval, a Form 310 be been completed, all set a 5.5# cem term 0 ER CCEPTED	nent markers and zo e filed within 30 day 60-4 shall be filed o and the operator ha	
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ak determined that the site is ready for fi Per Maxey Brown-NMOCD (in CIBP at 4,000'. Procedure: MIRU Pulling Unit. ND wellhe EUE 8rd (IPC) tbg. LD 2-7/8" CIBP/CCL to 4000'. Set CIBP putting 35' cement on top of C 2-7/8" x 7" AS 1x pkr w/1.875" internally coated) tbg. Set pact out plug. Release from On/Of down tbg and out casing w/15 packer with On/Off tool. ND B	eration (clearly state all pertinent detailly or recomplete horizontally, give sis k will be performed or provide the Bo operations. If the operation results in andonment Notices shall be filed only nal inspection.) compliance with Order SWD-1 ad and NU BOP. Release pace x 7" AS 1x pkr w/1.875" F profil at 4000'. POOH w/Baker settilBP. TOC @ 3965'. POOH & F profile & T2 On/Off tool, 111 ker at 3634' in 15,000# compref tool and PU several feet off pio O bbls 2% KCL water w/double OP & NU wellhead. Pump out true and correct. Electronic Submission #31273! For NEARBURG PROD Committed to AFMSS for pro N ubmission) THIS SPACE FOR FE	Is, including estimated startin ibsurface locations and meas nd No. on file with BLM/BL a multiple completion or rec after all requirements, include (471), Nearburg Product ker and POOH with 111 le w/T2 On/Off tool. RI ng tool. RIH w/cement LD dump bailer. PU & jts 2-7/8" L-80 6.5# EU ssion w/BOP still on we acker. Close BOP rams inhibited packer fluid. plug and perform inject Sverified by the BLM We UCING COMPANY, sent cessing by LINDA JIMEN Title PRODU Date 08/14/2 DERAL OR STATE	ag date of any propos ured and true vertica A. Required subsequ- ompletion in a new i ding reclamation, hav- sing Company wi I jts 2-7/8" L-80 6 H with 7" dump bailer, RIH w/redressed IE 8rd (TK-70 ell. RIH w/pump s. Circulate Latch back on to tivity test. II Information Sys- to the Hobbs JCTION MANAGE OFFICE USE	ed work and appro depths of all perti- ient reports shall be nterval, a Form 310 be been completed, all set a 5.5# cem term 0 ER CCEPTED	nent markers and zo e filed within 30 day 60-4 shall be filed o and the operator ha FOR REC Date Date	

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

OCT 07 2015

m

Additional data for EC transaction #312735 that would not fit on the form


32. Additional remarks, continued

٠,

Perform Mechanical Integrity Test (MIT) on casing, holding 500# for 30 minutes and record on chart. RDMO workover rig and rental tools. Turn well to injection.

Completion Report was submitted on May 21, 2015. Please see attached revised Proposed Wellbore Diagram.

PROPOSED WELLBORE DIAGRAM



OPEN HOLE:

6/18/2015