UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Hobbs

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

Lease Serial No. NMNM19858

| _ | | | | |
|---|-----------|----------|----------|-----|
| 6 | If Indian | Allottee | or Tribe | Nam |

| SUNDRY | NMNM198 | NMNM19858 | | | | | | | |
|--|---|--|--|-------------------|--|---------------------|------------------|--|--|
| Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. | | | | | | ottee or Tribe Na | ime | | |
| SUBMIT IN TRI | PLICATE - Other instruc | ctions on revers | e side. Of | T 19 200 | 7. If Unit or CA | /Agreement, Na | me and/or No. | | |
| 1. Type of Well ☑ Oil Well ☐ Gas Well ☐ Other | | | | | | 8 Well Name and No. | | | |
| Name of Operator EOG RESOURCES INCORP | 110 | 9. API Well No. 30-025-347 | | / | | | | | |
| 3a. Address MIDLAND, TX 79702 | 3b. Phone No. (in Ph: 432-686-3 | (include area code) 10. Field and Pool, or Explorat RED HILLS | | | | ry | | | |
| 4. Location of Well (Footage, Sec., T | . R. M. or Survey Description |) | | | 11. County or P | arish, and State | | | |
| Sec 35 T24S R33E SWSW 13 32.169972 N Lat, 103.549498 | 50FSL 660FWL | 1 | | E-PEDIA. | LEA COUN | | | | |
| 12. CHECK APPI | ROPRIATE BOX(ES) TO | INDICATE NA | ATU! R | ONVERS ETURN T | TING SW | D DATA | | | |
| TYPE OF SUBMISSION | | 4 | CS | ETURN T | 0 | RBDMS | JECTIONS | | |
| ☐ Notice of Intent | ☐ Acidize | □ Deepen | "" | TOPA | ENVIRO | TA | | | |
| | ☐ Alter Casing | ☐ Fracture | Treat | | OLA NID | CHG L | | | |
| Subsequent Report Subsequent Re | ☐ Casing Repair | □ New Co | | ☐ Recom | | P&A | OC | | |
| ☐ Final Abandonment Notice | ☐ Change Plans | □ Plug and | | | rarily Abandon | - WAI | RIM | | |
| | ☐ Convert to Injection | Plug Ba | ck | ■ Water | Disposal | | | | |
| 9/14/15 MIRU to P&A. 9/15/15 RIH work and release 9/17/15 RIH and set 5-1/2" C Pull up hole to 6510'. Spot 25 Pull up hole to 3000'. 9/18/15 RIH w/ freepoint. Det Cut casing at 3000'. Laydown 9/21/15 RIH to 5450'. Spot 45 Pull up hole to 3000'. | BP at 9250'. Spot 10 sx c sx Class H cement plug f ermined 5-1/2" casing free 5-1/2" casing. | ement plug at 92 rom 6500' to 630 e at 3000'. | 250'. 10'. | | DET | | of the well bore | | |
| 14. I hereby certify that the foregoing is | true and correct | | | - | | | | | |
| the state of the s | Electronic Submission #3 | 317991 verified by | the BLM W | ell Informatio | n System | | | | |
| Co | mmitted to AFMSS for pro | cessing by LINDA | JIMENEZ o | n 10/05/2015 | (15LJ1641SE) | | | | |
| Name(Printed/Typed) STAN WA | Tit | Title REGULATORY ANALYST | | | | | | | |
| Signature (Electronic S | Submission) | Da | te 09/29/ | 2015.TCD | FOR DEC | 2000 | | | |
| | THIS SPACE FO | R FEDERAL (| the same of the sa | | - Company of the Party of the P | JURDI | | | |
| | | | | | | | | | |
| Approved By Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conduct the applicant the applicant the applicant to conduct the applicant the applican | itable title to those rights in the | not warrant or subject lease | ffice | Illn | 1 4 2015 | Di | ate | | |
| Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent | U.S.C. Section 1212, make it a statements or representations as | crime for any person to any matter within | knowingly ar | willfully to p | THE STREET STREET | ent or agency of | the United | | |
| ** BLM REV | ISED ** BLM REVISED | ** BLM REVI | SED * BL | M REVISE | D ** BLM REV | ISED ** | 1 7 | | |

MAB/000 10/20/2015

OC 1 20 2015

Additional data for EC transaction #317991 that would not fit on the form

32. Additional remarks, continued

9/22/15 RIH and tag cement at 4752'. Pull up hole to 3112'. Spot 75 sx Class C cement plug from 3112' to 2793'. WOC 4 hrs. RIH and tag cement at 2793'. Pull up hole to 1720'. Spot 45 sx Class C cement plug at 1720'. WOC 4 hrs. RIH and tag cement at 1587'. Pull up hole to 728'. Spot 45 sx Class C cement plug from 728' to 425'. WOC.

9/23/15 RIH and tag cement at 425'. Pull up hole to 100'. Pumped 35 sx surface plug from 100' to surface.

9/24/15 Cut off wellhead, weld on ground level dry hole marker. Well P&A.