Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## **NMOCD** Hobbs

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

|       | Expires: July | 3 |
|-------|---------------|---|
| Lease | Serial No.    | Ī |

| SUNDRY N        | OTICES   | AND I | REPORTS   | ON | WELLS |
|-----------------|----------|-------|-----------|----|-------|
| Do not use this |          |       |           |    |       |
| Have been about | Ilas far | 2460  | 2 /ADDI S |    |       |

| Do not use the abandoned we  | nis form for proposals to dr<br>ell. Use form 3160-3 (APD)   | fill or to re-enter an for such proposals.   | ı  | 6. If Indian, Allottee   | or Tribe Name   |  |
|--|--|--|--|--|---|--|
|  |  |  |  |  |   |  |
| SUBMIT IN TR   | IPLICATE - Other instruction   | ons on reverse side.   | verse side.  |  | 7. If Unit or CA/Agreement, Name and/or No.                               |  |
| Type of Well   |  |  |  | 8. Well Name and No.   |   |  |
| ☑ Oil Well ☐ Gas Well ☐ Or   |  |  |  | DIAMOND 5 FED  | COM /H /  |  |
| Name of Operator<br>EOG RESOURCES INCORP   | Contact: ST<br>CORATEDE-Mail: stan_wagner@   | TAN WAGNER<br>@eogresources.com  | 00000  | 9. API Well No.<br>30-025-41991-0  | 00-X1 /   |  |
| n. Address MIDLAND, TX 79702   |  | b. Phone No. (include area code<br>Ph: 432-686-3689  |  |  | Pool, or Exploratory<br>S   |  |
| Location of Well (Footage, Sec., 7   | T. R. M. or Survey Description   | NOV  | 3 0 2015   | 11. County or Parish,  | and State   |  |
|  |  |  |  |  |   |  |
| Sec 5 T25S R34E SWSE 011<br>32.152457 N Lat, 103.488864  |  | RE   | CEIVED   | LEA COUNTY,  | NM  |  |
| 12. CHECK APP  | ROPRIATE BOX(ES) TO II   | NDICATE NATURE OF  | NOTICE, RE   | PORT, OR OTHE  | R DATA  |  |
| TYPE OF SUBMISSION   |  | ТҮРЕ О   | F ACTION   |  |   |  |
| - National Class   | Acidize  | Deepen   | ☐ Production   | on (Start/Resume)  | ☐ Water Shut-Off  |  |
| ☐ Notice of Intent   | ☐ Alter Casing   | ☐ Fracture Treat   | ☐ Reclamat   |  | ☐ Well Integrity  |  |
| Subsequent Report     ■     Subsequent Report          | ☐ Casing Repair  | ☐ New Construction   | Recomple   |  | Other   |  |
| ☐ Final Abandonment Notice   | Change Plans   | ☐ Plug and Abandon   |  |  | Drilling Operation  |  |
| B That Mondonnent Mondo  | Convert to Injection   | Plug Back  | ☐ Temporarily Abandon ☐ Water Disposal   |  |   |  |
| If the proposal is to deepen direction Attach the Bond under which the word following completion of the involved testing has been completed. Final Aldetermined that the site is ready for f 3/28/15 Spud 17-1/2" hole. 3/29/15 Ran 29 jts 13-3/8", 6: Cement lead w/ 550 sx Class   | rk will be performed or provide the doperations. If the operation results bandonment Notices shall be filed of inal inspection.)  8#, J55 STC casing set at 12 C. 13.5 ppg. 1.75 CFS yield:  | e subsurface locations and meas<br>Bond No. on file with BLM/BL<br>s in a multiple completion or rec<br>only after all requirements, inclu-  | ared and true vert<br>A. Required subsompletion in a ne  | ical depths of all pertin<br>equent reports shall be<br>w interval, a Form 316                                       | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 3/28/15 Spud 17-1/2" hole. 3/29/15 Ran 29 its 13-3/8". 6i  | ally or recomplete horizontally, given the state of the performed or provide the state of operations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. Surface. WOC 27 hrs. 10 psi for 30 minutes. Test go   | e subsurface locations and meas<br>Bond No. on file with BLM/BL<br>s in a multiple completion or rec<br>only after all requirements, inclu-  | ared and true vert<br>A. Required subsompletion in a ne  | ical depths of all pertin<br>equent reports shall be<br>w interval, a Form 316                                       | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 3/28/15 Spud 17-1/2" hole. 3/29/15 Ran 29 jts 13-3/8", 60 Cement lead w/ 550 sx Class tail w/ 300 sx Class C, 14.8 pt Circulated 225 sx cement to s 3/30/15 Tested casing to 150   | ally or recomplete horizontally, given the state of the performed or provide the state of operations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. Surface. WOC 27 hrs. 10 psi for 30 minutes. Test go   | e subsurface locations and meas<br>Bond No. on file with BLM/BL<br>s in a multiple completion or rec<br>only after all requirements, inclu-  | ared and true vert<br>A. Required subsompletion in a ne  | ical depths of all pertin<br>equent reports shall be<br>w interval, a Form 316                                       | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following t | ally or recomplete horizontally, given will be performed or provide the logerations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. Jurface. WOC 27 hrs. O psi for 30 minutes. Test go.  | e subsurface locations and meas Bond No. on file with BLM/BL. S in a multiple completion or record after all requirements, including the substitution of the substitut | ured and true vert A. Required subs ompletion in a ne ding reclamation,  Il Information S to the Hobbs | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed,                          | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involver testing has been completed. Final Aldetermined that the site is ready for following that the site is ready for following that the site is ready for following the site is ready for following that t | ally or recomplete horizontally, give rk will be performed or provide the operations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. surface. WOC 27 hrs. 00 psi for 30 minutes. Test go.  | e subsurface locations and meas Bond No. on file with BLM/BL. s in a multiple completion or reconly after all requirements, included by the BLM West Sincorporated by the BLM West Sincorporated, sent g by JENNIFER SANCHEZ of  | ured and true vert A. Required subs ompletion in a ne ding reclamation,  Il Information S to the Hobbs | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system                 | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following that the site is ready for following that the site is ready for following the site is ready for following that t | ally or recomplete horizontally, give rk will be performed or provide the operations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. surface. WOC 27 hrs. 00 psi for 30 minutes. Test go.  | e subsurface locations and meas Bond No. on file with BLM/BL. s in a multiple completion or reconly after all requirements, included by the BLM West Sincorporated by the BLM West Sincorporated, sent g by JENNIFER SANCHEZ of  | Il Information Sto the Hobbs on 10/29/2015   | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system                 | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following that the site is ready for following that the site is ready for following the site is ready for following that t | ally or recomplete horizontally, give rk will be performed or provide the operations. If the operation results bandonment Notices shall be filed of inal inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. surface. WOC 27 hrs. 10 psi for 30 minutes. Test go.  1. True and correct.  Electronic Submission #296  For EOG RESOURC of the surface  | e subsurface locations and meas Bond No. on file with BLM/BL. s in a multiple completion or reconly after all requirements, included by the BLM West Sincorporated by the BLM West Sincorporated, sent g by JENNIFER SANCHEZ of  | Il Information S to the Hobbs on 10/29/2015 (ATORY ANAL)   | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system                 | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following t | ally or recomplete horizontally, given will be performed or provide the logerations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield; pg, 1.354 CFS yield. Provided by the complete structure of | e subsurface locations and meas Bond No. on file with BLM/BL. s in a multiple completion or record after all requirements, including the subsurface of the s | Il Information Sto the Hobbs on 10/29/2015   | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system [16]4\$0015\$E] | RECORD  |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following that the site is ready for following the site is ready for following that the site is ready for following the site is ready for following that the following that the following that the foregoing is site is the site is ready for following that the foregoing is site is the site is ready for following that the foregoing is site is the site is ready for following that the site is ready for following that the following that | ally or recomplete horizontally, given will be performed or provide the logerations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield; pg, 1.354 CFS yield. Provided by the complete structure of | e subsurface locations and meas Bond No. on file with BLM/BL s in a multiple completion or rec inly after all requirements, inclu- 25'.  737 verified by the BLM We ES INCORPORATED, sent g by JENNIFER SANCHEZ of Title REGUL  Date 03/31/2   | Il Information Sto the Hobbs on 10/29/2015   | system  System  EPTED FOR  | ent markers and zones.<br>filed within 30 days<br>0-4 shall be filed once |  |
| If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f 3/28/15 Spud 17-1/2" hole. 3/29/15 Ran 29 jts 13-3/8", 6: Cement lead w/ 550 sx Class tail w/ 300 sx Class C, 14.8 pt Circulated 225 sx cement to s 3/30/15 Tested casing to 150 Resumed drilling 12-1/4" hole   | ally or recomplete horizontally, given will be performed or provide the logerations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield; pg, 1.354 CFS yield. Provided by the complete structure of | e subsurface locations and meas Bond No. on file with BLM/BL sin a multiple completion or recomby after all requirements, including the subsurface of the su | Il Information Sto the Hobbs on 10/29/2015   | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system [16]4\$0015\$E] | RECORD  |  |
| If the proposal is to deepen direction Attach the Bond under which the word following completion of the involved testing has been completed. Final Aldetermined that the site is ready for following that the following that the foregoing is common that the site is ready for following that the foregoing is common that the foregoing is site is the property of the site is ready for following that the foregoing is common that the following that the foregoing is common that the following that the foregoing is common that the following the following that the followin | ally or recomplete horizontally, give rk will be performed or provide the operations. If the operation results bandonment Notices shall be filed of final inspection.)  8#, J55 STC casing set at 12 C, 13.5 ppg, 1.75 CFS yield; pg, 1.354 CFS yield. surface. WOC 27 hrs. 00 psi for 30 minutes. Test go For EOG RESOURC For EOG RESOURC fitted to AFMSS for processing (GNER)  THIS SPACE FOR   | e subsurface locations and meas Bond No. on file with BLM/BL s in a multiple completion or rec inly after all requirements, inclu- 25'.  737 verified by the BLM We ES INCORPORATED, sent g by JENNIFER SANCHEZ of Title REGUL  Date 03/31/2  FEDERAL OR STATE  Title  Title  Warrant or   | Il Information Sto the Hobbs on 10/29/2015   | ical depths of all pertinequent reports shall be winterval, a Form 316 have been completed, a system [16]4\$0015\$E] | RECORD  |  |