UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

5. Lease Serial No. NMLC032715


OCD Hobbs

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIE	PLICATE - Other instruc	ctions on reverse sid	16,	89101158	
Type of Well Oil Well	er: INJECTION	٧	DEC 212	015 8. Well Name at	nd No. IAL UNIT 133
 Name of Operator LEGACY RESERVES OPERA 	Contact: TING LRE-Mail: jsaenz@le	JOHN SAENZ gacylp.com	PECEIVE	9. API Well No 30-025-11	n. 161-00-C1 /
3a. Address 303 W WALL SUITE 1600 MIDLAND, TX 79702		3b. Phone No. (include Ph: 432-689-5200			ool, or Exploratory MATTIX
4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description)		11. County or I	Parish, and State
Sec 19 T24S R37E NESW 198	80FSL 1916FWL		E-PERM COM	LEA COU	NTY, NM
12. CHECK APPR	OPRIATE BOX(ES) TO	INDICATE NATU	CONVER RETURN CSNG	SION SIN	VO DATA
TYPE OF SUBMISSION		_7	RETURN CSNG INT TO PA	FAR	RBDMS INJECTIONS
Notice of Intent	☐ Acidize	☐ Deepen	"OPA	PAVIRO	TA DINS TIONS
	☐ Alter Casing	☐ Fracture Tre	at Rec.	SA NO	CHG LOC P&AR
☐ Subsequent Report	Casing Repair	☐ New Constru	action Reco	mplete	PRALOC
☐ Final Abandonment Notice	☐ Change Plans	Plug and Ab	andon	oorarily Abandon	P&AR
	Convert to Injection	☐ Plug Back	☐ Wate	r Disposal	
Proposed P&A Procedure: 1. RIH open ended and tag CII 2. Circulate minimum 9.5 ppg II 3. TOOH to 1210'. Circulate Point 1110'. Worker, Set @ 250' are w/packer, RIH w/opened ender 5. TOOH to 100'. Circulate P& 6. POOH, top off casing, remore RECLAMATION PROCEDURATIACHED	P&A mud to 1200' and sp &A mud to surface and sp and squeeze casing leak (d tubing and tag TOC at/ A mud and spot 100' cen ve WH, set P&A marker,	oot 150' of cement on pot 100' cement balan @ 301'-333" w/minimu above 250'. Circulate ment balance plug fro	um 40 sx. WOC, P P&A mud to surface m 100' to surface. cation.	OOH Perfet 30	as't squeeze cemat
14. I hereby certify that the foregoing is					
	Electronic Submission #	SERVES OPERATING	LP, sent to the Hol	obs	
Name (Printed/Typed) JOHN SAE	ENZ	Title	OPERATIONS E	NGINEER	
Signature (Electronic S	ubmission)	Date	08/28/2015		
	THIS SPACE FO	OR FEDERAL OR	STATE OFFICE	USE	
Approved By M. Wells		Title	Erg.		Date 12/8/15
Conditions of approval, if any, are attached certify that the applicant holds legal or equ which would entitle the applicant to condu-	itable title to those rights in the		CFO		
Title 18 U.S.C. Section 1001 and Title 43 V States any false, fictitious or fraudulent s	J.S.C. Section 1212, make it a tatements or representations as	crime for any person know to any matter within its ju	wingly and willfully to urisdiction.	make to any departn	ment or agency of the United

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **



1260

><>>>>

	Location:	
Footage:	1980 FSL & 1917 FWL	
Section:	19 - 24S - 37E	
Block:		
Survey:		
County:	Lea, New Mexico	
Lat:		
Long:		
	Elevations:	
GL:	3286	
KB:	3296	
KB Calc:	10	
ck w/log?	Yes	

Date	History
18-Oct-49	Initial completion: 3053' - 3110' (Yates), Acdz'd w/ 1,000 gals.
100	IP = 52 bopd, 0 bwpd, & 55.7 Mcfgpd (flowing)
9-Jul-53	Frac w/ 6,000 gals Ise oil & 4,500#'s sand
24-Jul-54	DO cmt 3241' - 3320' & CO open hole. Frac OH w/ 10,000 gals ise oil
	& 10,000# sand. Dual complete w/ pkr at 3,133*
1-Aug-55	Sqz perfs at 3,053' - 3,110' w/ 100 sx. Frac OH w/ 20,000 gals lse oil &
	20,000# sand. Perf 3182' - 3220' & 3245' - 3278'. Isolate & frac perfs w/
	20,000 gals Ise oil & 20,000# sand. Dual Complete w/ pkr at 3295'.
5-Jun-74	CO fill to 3680' & perf 3060' - 3155'. Convert to Injector.
16-Apr-86	Found HIC at 250 - 340'. Sqz csg w/ 500 sx Class C. Acidize perfs at
	3060' - 3278' w/ 5000 gals 15% NEFE & 1000# RS. Perf at 215' and
	pumped 100 sx cmt - circ to cellar. Failed MIT - found leak at 270' - 330'.
	Re-squeeze w/ 50 sx (Hesitation sqz).
22-Mar-94	CO fill 3647' - 3680' 8 perf 2982' - 3049' w/ 2 SPF.
	RIH w/ 2 3/8" IPC tbg & pkr. Set pkr @ 2929'. Initiated injection @
	672 bwpd, TP=vacuum.
1-Oct-94	Change well name to Cooper Jal Unit #133. (previous #'s 240 and 310)
14-Feb-02	Tag fill at 3,429' with slickline.
7-Nov-05	Tag fill at 3,434' with slickline.
21-Apr-09	Ran Injection Profile. Place well on inj. Rate/Press: 585 bwpd/684#
17-May-12	CO fill to 3670' - could not make any more hole. Failed MIT.
	Well tested with RBP at 2,948', but would not test with pkr.
14-Feb-14	Found leak in casing between 301'-333'
	NOON TO BE SEED OF THE SEED OF

	Tubing Detail (top to bottom)		
Joints	Tubing Detail (top to bottom) Description	Footage	Depth
	Street Library Laboratory		
		_	

Rod Detail (top to bottom)		
Description	Footage	Depth
S May 198 19 11		
	Rod Detail (top to bottom) Description	

Pumping Unit: Updated: 5/5/14 MLS

	Reservoir:	Cooper Jal
	Well ID Info:	CJU #133
Wellbore Diagram	API No:	30-025-11161
	Spud Date:	9/20/1949
	The state of	

Hole Size: 11"
Surf. Csg: 8-5/8", 32# J-55
Set @ 304"
Cement w/ 125 sx Lone Star Reg + 50 sx Incor Quick-set
Clrc: Yes
TOC: Surface

Shot 2 holes at 215' and circ cmt to surface (4/16/1986)

TOC: <u>225' (Temp Survey)</u> Sqz 250' - 340' leak w/ 500 sx (4/16/1986). Re-sqz w/ 50 sx.

Found leak 2-14-14 between 301'-333'
Aerta + 3 45'

Hole Size: Prod. Csg: Set @ Cement: Circ: TOC:

7-3/8" 5-1/2", 15.5# J-55 3320'

3320 700 sx w/ 3% gel + 250 sx regular + 50 sx Incor Yes Surface

Anhydrite @ 2976

Perfat 1260

Minimum 25 sx cont.

CIBP @ 2900'

Yates @ 2976

2982' - 3049'

Squeezed perfs 3053' - 3059'

3060' - 3155'

3182' - 3220' 7-R @ 3210'

3245' - 3278'

OH ID 4-3/4" OH Interval 3320'-3680'

Queen @ 3544'

TOF @ 3670'

PBTD 3670' TD 3680' Cooper Jal Unit

20.00	Location:	
Footage:	1980 FSL & 1917 FWL	
Section:	19 - 24S - 37E	
Block:		
Survey:		
County:	Lea, New Mexico	
Lat:		
Long:		
	Elevations:	
GL:	3286	
KB:	3296	
KB Calc:	10	
ck w/log?	Yes	

Date	History
18-Oct-49	Initial completion: 3053' - 3110' (Yates). Acdz'd w/ 1,000 gals.
	IP = 52 bopd, 0 bwpd, & 55.7 Mcfgpd (flowing)
9-Jul-53	Frac w/ 6,000 gals ise oil & 4,500#'s sand
24-Jul-54	DO cmt 3241' - 3320' & CO open hole. Frac OH w/ 10,000 gals ise oil
	& 10,000# sand. Dual complete w/ pkr at 3,133*
1-Aug-55	Sqz perfs at 3,053' - 3,110' w/ 100 sx. Frac OH w/ 20,000 gals lse oil &
	20,000# sand. Perf 3182' - 3220' & 3245' - 3278'. Isolate & frac perfs w/
	20,000 gals Ise oil & 20,000# sand. Dual Complete w/ pkr at 3295'.
5-Jun-74	CO fill to 3680' & perf 3060' - 3155'. Convert to Injector.
16-Apr-86	Found HIC at 250 - 340'. Sqz csg w/ 500 sx Class C. Acidize perfs at
	3060' - 3278' w/ 5000 gals 15% NEFE & 1000# RS. Perf at 215' and
	pumped 100 sx cmt - circ to cellar. Failed MIT - found leak at 270' - 330'
	Re-squeeze w/ 50 sx (Hesitation sqz).
22-Mar-94	CO fill 3647' - 3680' & perf 2982' - 3049' wi 2 SPF.
	RIH w/ 2 3/8" IPC tbg & pkr. Set pkr @ 2929'. Initiated injection @
	672 bwpd, TP=vacuum,
1-Oct-94	Change well name to Cooper Jai Unit #133. (previous #s 240 and 310)
14-Feb-02	Tag fill at 3,429' with slickline.
7-Nov-05	Tag fill at 3,434' with slickline.
21-Apr-09	Ran Injection Profile, Place well on inj. Rate/Press; 585 bwpd/684#
17-May-12	CO fill to 3670' - could not make any more hole. Failed MIT.
	Well tested with RBP at 2,948', but would not test with pkr.
14-Feb-14	Found leak in casing between 301'-333'
	Carlotter and the second
	Maria de la companya della companya
	TOTAL PARTY CONTRACTOR OF THE

	Tubing Detail (top to bottom) Description		
Joints	Description	Footage	Depth
VZE			

	Rod Detail (top to bottom)		
Rods	Description	Footage	Depth
		_	
	1000		

Pumping Unit: Updated: 5/5/14 MLS

CJU #133

EXISTING

Wellbore Diagram

Reservoir:	Cooper Jai	
Well ID Info:	CJU #133	
API No:	30-025-11161	
Spud Date:	9/20/1949	

Hole Size: Surf. Csg: Set @ Cement w/ Circ:

TOC:

11"
8-5/6", 32# J-55
304'
125 sx Lone Star Reg + 50 sx Incor Quick-set Yes Surface

Shot 2 holes at 215' and circ cmt to surface (4/16/1986)

TOC: <u>225' (Temp Survey)</u> Sqz 250' - 340' leak w/ 500 sx (4/16/1986). Re-sqz w/ 50 sx.

Found leak 2-14-14 between 301'-333'

Hole Size: Prod. Csg: Set @ Circ: TOC:

7-3/8" 5-1/2", 15.5# J-55 3320' 700 sx w/ 3% gel + 250 sx regular + 50 sx Incor Yes Surface

CIBP @ 2900"

>000000

Yates (2) 2975

2982' - 3049'

Squeezed perfs 3053' - 3059'

3060' - 3155'

3182' - 3220' 7-R @ 3210

3245' - 3278'

OH ID 4-3/4"

OH Interval 3320'-3680'

Queen @ 3544"

TOF @ 3670'

PBTD 3670' TD 3680'

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.

- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Linda Denniston Environmental Protection Specialist 575-234-5974

Henryetta Price Environmental Protection Specialist 575-234-5951

Dara Glass Environmental Protection Specialist 575-234-5924

Shelly Tucker Environmental Protection Specialist 575-234-5979