

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
**District III**  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
**District IV**  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

# State of New Mexico

Form C-101  
Revised July 18, 2013

## Energy Minerals and Natural Resources

### Oil Conservation Division

1220 South St. Francis Dr.

Santa Fe, NM 87505

HOBBS OCD

DEC 30 2015

RECEIVED

☐ AMENDED REPORT

### APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

<sup>1</sup> Operator Name and Address ENDURANCE RESOURCES LLC 203 West Wall Suite 1000 Midland, TX 79701		<sup>2</sup> OGRID Number 270329
		<sup>3</sup> API Number 30025-42991
<sup>4</sup> Property Code 314105	<sup>5</sup> Property Name Telecaster Bass 36 State	<sup>6</sup> Well No. 2H

#### <sup>7</sup> Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County
C	36	24 S	34 E		330	N	1980	W	LEA

#### <sup>8</sup> Proposed Bottom Hole Location

UL - Lot	Section	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County
N	36	24 S	34 E		330	S	1980	W	LEA

#### <sup>9</sup> Pool Information

Pool Name	Pool Code
Red Hills: Bone Spring East NORTH	96434

#### Additional Well Information

<sup>11</sup> Work Type New Well	<sup>12</sup> Well Type Oil	<sup>13</sup> Cable/Rotary R	<sup>14</sup> Lease Type State	<sup>15</sup> Ground Level Elevation
<sup>16</sup> Multiple N	<sup>17</sup> Proposed Depth 17,387' MD	<sup>18</sup> Formation 3 <sup>rd</sup> Bone Spring	<sup>19</sup> Contractor NorAm 23	<sup>20</sup> Spud Date 06/01/16
Depth to Ground water: 0-400'		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

#### <sup>21</sup> Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1000	760	Surface
Int1	12.25	9.625	43.5	9200	1240	Surface
Prod	8.75	5.5	20	17387	1360	4000

#### Casing/Cement Program: Additional Comments

Plan to drill a 17-1/2" hole to 1000' with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cement to surface. Drill 12-1/4" hole to 9,200' with Brine, and run 9-5/8", 43.5#, HCL-80 csg and cement to surface. Drill a 10"/ 100' curve and a ~4,355' lateral to TD of ~17,387'. Run 5-1/2", 20#, P-110 csg and cement to 4000'.

#### <sup>22</sup> Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	5000	5000	Cameron

<sup>23</sup> I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

I further certify that I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒, if applicable.

Signature: *Tinlee Tilton*

Printed name: Ms. Tinlee Tilton

Title: Engineer

E-mail Address: tinlee@enduranceresourcesllc.com

Date: 12/21/2015

Phone: 432-242-4693

#### OIL CONSERVATION DIVISION

Approved By: *[Signature]*

Title: Petroleum Engineer

Approved Date: 12/31/15

Expiration Date: 12/31/17

Conditions of Approval Attached

JAN 04 2016

# CONDITIONS OF APPROVAL

API #	Operator	Well name & Number
30-025-42991	ENDURANCE RESOURCES LLC	TELECASTER BASS STATE # 002H

Applicable conditions of approval marked with **XXXXXX**

## Administrative Orders Required

--	--

## Other wells

--	--

## Drilling

<b>XXXXXX</b>	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string

## Casing

<b>XXXXXX</b>	SURFACE & INTERMEDIATE(1) CASING - Cement must circulate to surface --
<b>XXXXXX</b>	PRODUCTION CASING - Cement must tie back into intermediate casing --
	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
<b>XXXXXX</b>	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water

## Lost Circulation

<b>XXXXXX</b>	Must notify OCD Hobbs Office if lost circulation is encountered at 575-370-3186

## Stage Tool

<b>XXXXXX</b>	Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186
<b>XXXXXX</b>	If using Stage Tool on Surface casing, Stage Tool must be greater than 350' and a minimum 200 feet above surface shoe.
<b>XXXXXX</b>	When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.

## Pits

<b>XXXXXX</b>	If using a pit for drilling and completions, must have an approved pit form prior to spudding the well

## Completion & Production

<b>XXXXXX</b>	Will require a directional survey with the C-104