


OCD Hobbs

15-904

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM116047
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator COG Operating LLC. 229137		7. If Unit or CA Agreement, Name and No.
3a. Address 2208 West Main Street Artesia, NM 88210		8. Lease Name and Well No. Smalls Federal #1H (35744)
3b. Phone No. (include area code) 575-748-6940		9. API Well No. 30-025-43001
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 190' FSL & 560' FEL Unit Letter P (SESE) Sec. 28.T22S.R34E At proposed prod. Zone 330' FNL & 660' FEL Unit Letter A (NENE) Sec 28.T22S.R34E		10. Field and Pool, or Exploratory (97922) WC-025 G-06 S223421L; Bone Spring
14. Distance in miles and direction from nearest town or post office* About 17 miles from Eunice		11. Sec., T.R.M. or Blk and Survey or Area Sec. 28 - T22S - R34E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 190'		12. County or Parish Lea County
16. No. of acres in lease 960		13. State NM
17. Spacing Unit dedicated to this well 160		
18. Distance from location* to nearest well, drilling, completed, applied for, on this lease, ft. SHL: 30' (Prop. Smalls #5H) BHL: 3644'		20. BLM/BIA Bond No. on file NMB000740 & NMB000215
19. Proposed Depth TVD: 11,100' MD: 15,655' PH: 11,500'		21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3403.8' GL
22. Approximate date work will start* 12/1/2015		23. Estimated duration 30 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature Mayte Reyes	Name (Printed/Typed) Mayte Reyes	Date 7-22-15
------------------------------	-------------------------------------	-----------------

Title Regulatory Analyst	
Approved by (Signature) Edward G. Fernandez Acting for Steve Caffey	Name (Printed/Typed) Office BLM-CARLSBAD FIELD OFFICE
Date DEC 31 2015	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

Capitan Controlled Water Basin
SEE ATTACHED FOR
CONDITIONS OF APPROVALAPPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED

*(Instructions on page 2)

Witness Surface &
Intermediate Casing

JAN 05 2016

COG Operating LLC, Smalls Federal 1H

1. Geologic Formations

TVD of target	11100'	Pilot hole depth	11500'
MD at TD:	15655'	Deepest expected fresh water:	605'

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	1830'	Water	
Top of Salt	2115'	Salt	
Tansill	3637'	Barren	
Yates	3708'	Oil/Gas	
Capitan Reef	4012'	Water	Possible lost circ
Delaware Group	5209'	Oil/Gas	Possible lost circ
Bone Spring	8505'	Oil/Gas	
3 rd Bone Spring Sand	10929'	Target Zone	
Wolfcamp	11206'	Oil/Gas	
Strawn	11721'	Oil/Gas	Will not penetrate

2. Casing Program

See COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0'	2010' 1980'	13.375"	54.5	J55	STC	1.21	1.05	4.76
12.25"	0'	5300' 5500'	9.625"	40	L80	BTC	1.19	1.05	4.16
8.75"	0'	15655'	5-1/2"	17	P110	LTC	1.42	2.03	1.67D
BLM Minimum Safety Factor							1.125	1.00	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
- BLM standard formulas were used on all SF calculations.
- Used 9.1 PPG for pore pressure calculations to top of Wolfcamp and 9.2 PPG for Wolfcamp.
- Will set DV tool within 100' of the top of the Capitan Reef. Estimated setting depth is 3915'.

COG Operating LLC, Smalls Federal 1H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	Y
If yes, does production casing cement tie back a minimum of 50' above the Reef?	Y
Is well within the designated 4 string boundary.	N
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

2. Cementing Program

Casing	# Skis	Wt. lb/ gal	Yld ft3/ sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	860	13.5	1.75	9.2	13	Lead: Class C + 4% Gel + 2% CaCl ₂
	275	14.8	1.34	6.4	6	Tail: Class C + 2% CaCl ₂
Inter. Stg 1	285	12.9	1.92	10.0	12	Lead: Class C Lite (65:35:6) + 4% Salt + 5# Kolseal
	200	14.8	1.34	6.4	6	Tail: Class C
Inter. Stg 2	945	12.9	1.92	10.0	12	Lead: Class C Lite (65:35:6) + 4% Salt + 5# Kolseal
	200	14.8	1.34	6.4	6	Tail: Class C
Prod.	1030	10.3	3.52	21.3	75	Lead: Halliburton Tuned Lite w/ 2# kolseal, 1.5# salt, 1/4# D-Air 5000, 1/8# PEF, etc
	1220	14.4	1.25	5.7	22	Tail: 50:50:2 H blend (FR, Retarder, FL adds as necessary)

Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

COG Operating LLC, Smalls Federal 1H

Casing String	TOC	% Excess
Surface	0'	36%
Intermediate – Stage 1	3915'	51%
Intermediate – Stage 2	0'	124%
Production	0'	39%

Pilot hole depth: 11500'

KOP: 10623'

4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	2M	Annular	x	50% of working pressure
			Blind Ram		2M
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	13-5/8"	5M	Annular	x	50% testing pressure
			Blind Ram		5M
			Pipe Ram		
			Double Ram	x	
			Other *		

* Actual equipment is 13-5/8" 5M Hydril Annular, will use for 2M WP System.

** - Actual equipment is 13-5/8" 5M Hydril Annular & 13-5/8" 10M Cameron triple ram, will use for 5M WP System.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

COG Operating LLC, Smalls Federal 1H

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
	Are anchors required by manufacturer? No.
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. See attached schematic.

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. shoe	FW Gel	8.6 – 9.0	28-34	N/C
Surf csg	Int shoe	*Saturated Brine	10.0 - 10.2	28-34	N/C
Int shoe	TMD	Cut Brine	8.6 - 9.5	28-34	N/C

*If lost circulation is encountered, will switch to fresh water.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason PVT
---	-----------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned		Interval
X	Mud log	Production
X	Triple Combo	Pilot Hole TD – Intermediate Casing
X	GR-Neutron	Intermediate Casing - Surface

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	5502 psi – Wolfcamp (11500' – Pilot Hole TD)
Abnormal Temperature	No

Mitigation measure for abnormal conditions.

- Lost circulation material/sweeps/mud scavengers.
- Maintain stock of LCM and weighting materials onsite.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S Plan attached

8. Other facets of operation

Is this a walking operation? Yes. *See COA*
 Will be pre-setting casing? No.
 Will well be hydraulically fractured? Yes.

Attachments

- Directional Plan
- BOP & Choke Schematics
- C102 and supporting maps
- Rig plat
- H2S schematic
- H2S contingency plan
- Interim reclamation plat