Submit 1 Copy To Appropriate District Office	State of New Mexico		Form C-103 Revised July 18, 2013
<u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240			WELL API NO.
District II - (575) 748-1283	ict II - (575) 748-1283		30-025-21868
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	Santa Fe, NM 87505		STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	,		006-260
87505 SUNDRY NOT	ICES AND REPORTS ON WI	ELLS	7. Lease Name or Unit Agreement Name
			T.P. State A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Y	
1. Type of Well: Oil Well	Gas Well  Other		8. Well Number
Name of Operator     OXY USA	Ino /	MAR 1 8 2016	9. OGRID Number 16696 ✓
3. Address of Operator	inc. V		10. Pool name or Wildcat
P.O. Box 50250 Midland, TX 79710 RECEIVED Bagley Permo Penn, W.			
4. Well Location			
Unit Letter J: 1980 feet from the South line and 1980 feet from the east line			
Section \ 👁	Township ((S		NMPM County Lea
	11. Elevation (Show whether	r DR, RKB, RT, GR, etc.,	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK INTO PA			
DILL OP ALTER CASING TO MULTIPLE COMPLETE CASING/CEMENT IOR			
DOWNHOLE COMMINGLE   P&A R			
CLOSED-LOOP SYSTEM			
OTHER:		OTHER:	
13. Describe proposed or completed operations. (Clearly str. e all pertinent details, and give pertinent dates, including estimated dates			
of starting any proposed work). SEE RULE 19.15. MAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
TD-10300' PBTD-10017' Perfs-8536-9898' RBP-10017'			
13-3/8" 48# csg @ 347' w/ 375sx, 17-1/2" hole, TOC-Surf-Circ			
8-5/8" 24-32# csg @ 3755' w/ 300sx, 11" hole, TOC-2435'-Calc			
8-5/8" 24-32# csg @ 3755' w/ 300sx, 11" hole, TOC-2435'-Calc 5-1/2" 17# csg @ 10300', DVT @ 4696' w/ 1250sx, 7-7/8" hole, TOC-3800'-TS  1. RIH & set CIBP @ 9080', M&P 15sx cmt to 8980' 2. RIH & set CIBP @ 8486', M&P 25sx cmt to 8320' 3. Perf 5-1/2" @ 6575', sqz 35sx to 6475' WOC-Tag 4. Perf 5-1/2" @ 3805', sqz 35sx cmt to 3705' WOC-Tag 4. Perf 5-1/2" & 8-5/8" @ 1800', sqz 60sx cmt to 1700' WOC-Tag 5. Perf 5-1/2" & 8-5/8" @ 397' sqz 300sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized  Rig Release Date:  Rig Release Date:			
1. RIH & set CIBP @ 9080', M&P 15sx cmt to 8980'			
2. RIH & set CIBP @ 8486', M&P 25sx cmt to 8320'			
Perf @4610 50-2  3. Perf 5-1/2" @ 6575', sqz 35sx to 6475' WOC-Tag  3. M&P 25sx cmt @ 4610-4445' WOC-Tag  4. Perf 5-1/2" @ 3805', sqz 35sx cmt to 3705' WOC-Tag  4. Perf 5-1/2" @ 3805', sqz 35sx cmt to 3705' WOC-Tag			
4. Perf 5-1/2" @ 3805', sqz 35sx cmt to 3705' WOC-Tag 4. Perf 5-1/2" & 8-5/8" @ 1800', sqz 60sx cmt to 1700' WOC-Tag 5. Perf 5-1/2" & 8-5/8" @ 397' sqz 300sx cmt to surface 10# MLF between plugs Above ground steel tanks will be utilized  Spud Date:  Rig Release Date:			
4. Perf 5-1/2" & 8-5/8" @ 1800', sqz 60sx cmt to 1700' WOC-Tag			
5. Perf 5-1/2" & 8-5/8" @ 397' sqz 300sx cmt to surface  10# MLF between plugs			
	Above ground steel tanks will b	e utilized	TIEY ING O.
		40	Jeg
Spud Date:	Rig Releas	se Date:	
-			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
Thereby terms, that the information were to the complete to the cost of my the medical control of the cost of my the cost of m			
			-1. (
SIGNATURE fu fa	TITLE_	Sr. Regulatory Adviso	DATE 3 16 (16
Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717			
For State Use Only			
APPROVED BY: Walle Witaken TITLE Petroleum Engn Specialist DATE 3/22/2016 Conditions of Approval (if any):			
VARIOUS DE ADDICIVAL III AUV I			

MAR 2 2 2016

OXY USA Inc. - Proposed TP State A #1 API No. 30-025-21868

17-1/2" hole @ 350' 13-3/8" csg @ 347' Perf @ 397' w/ 375sx-TOC-Surf Circ 60sx @ 1800-1700' WOC-Tag Perf @ 1800' 11" hole @ 3755' 8-5/8" csg @ 3755' w/ 300sx-TOC-2435'-Calc 35sx @ 3805-3705' WOC-Tag Perf @ 3805' 25sx @ 4610-4445' WOC-Tag 35sx @ 6575-6475' WOC-Tag Perf @ 6575' 7-7/8" hole @ 10300' 5-1/2" csg @ 10300' w/ 1250sx-TOC-7800'-TS CIBP @ 8486' w/ 25sx to 8320' DVT @ 4696'-TOC-3800' Perfs @ 8536-8580' Perfs @ 8772-8886' CIBP @ 9080' w/ 15sx to 8980' Perfs @ 9130-9898' RBP @ 10017' Perfs @ 10055-10128' CIBP @ 10150' Perfs @ 10162-10168' Perfs @ 10244-10254' CIBP @ 10210' TD-10300

OXY USA Inc. - Current TP State A #1 API No. 30-025-21868

