# HOBBS OCD

# BC Operating, Inc.MAR 2 8 2016Hydrogen Sulfide Drilling Operations PlanDECEIVED

#### Gay Nineties Federal Com #4H

### SHL: 2010' FSL & 2256' FEL of Unit Letter 'J', Section 36, T-19S, R-32E BHL: 240' FSL & 360' FWL of Unit Letter 'M', Section 1, T-20S, R-32E

#### Lea County, New Mexico

The H<sub>2</sub>S Drilling Operations Plan is submitted with Form 3160-3, Application for Permit to Drill, in accordance with BLM Onshore Oil and Gas Order Number 6 Section III.A.1., covering the above described well.

#### I. <u>Hydrogen Sulfide Training</u>

e. . . . . .

All personnel, whether regularly assigned, contracted or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- A. The hazards and characteristics of hydrogen sulfide  $(H_2S)$ .
- B. The prior use and maintenance of personal protective equipment and life support systems.
- C. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures and prevailing winds.
- D. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- A. The effects of H<sub>2</sub>S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- B. Corrective action and shut in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- C. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable  $H_2S$  zone (within 3 days or 500') and weekly  $H_2S$  and well control drills for all personnel in each crew. The initial training session shall include a review or the site specific  $H_2S$  Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

#### II. <u>H<sub>2</sub>S Safety Equipment and Systems</u>

Note: All  $H_2S$  safety equipment and systems will be installed, tested and operational when drilling reaches a depth of 500' above or three days prior to penetrating the first zone containing or reasonably expected to contain  $H_2S$  (prior to drilling out of the 13 3/8" surface casing shoe for this well).

A. Well Control Equipment (All BOP and BOP equipment is shown in Drilling Plan – Exhibits 1-4).

Flare line Choke manifold and remotely operated chokes Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit. Auxiliary equipment to include annular preventer, mud-gas separator and rotating head.

- B. Protective equipment for essential personnel: Mark II Surviveair 30 minute units located in the dog house and at briefing areas
- C. H<sub>2</sub>S detection and monitoring equipment:

2 portable  $H_2S$  monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when  $H_2S$  levels of 20 ppm are reached.

#### D. Visual Warning Systems:

Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate.

- E. Mud Program: The mud program has been designed to minimize the volume of  $H_2S$  circulated to the surface.
- F. Metallurgy:

All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool kill lines, choke manifold lines and valves shall be suitable for H<sub>2</sub>S services.

G. Communication:

Company vehicles equipped with cellular telephone.

BC Operating, Inc. has conducted a review to determine if an  $H_2S$  Contingency Plan is needed for this well and has determined that there is minimal potential for the accumulation for any hazardous concentration of  $H_2S$ ; therefore, no  $H_2S$  Contingency Plan has been submitted for this well.

WARNING		
	YOU ARE ENTERING AN H <sub>2</sub> S AREA	
	AUTHORIZED PERSONNEL ONLY	
1.	BEARDS OR CONTACT LENSES NOT ALLOWED	
	HARD HATS REQUIRED	
	SMOKING IN DESIGNATED AREAS ONLY	
	BE WIND CONSCIOUS AT ALL TIMES	
5.	CHECK WITH BC OPERATING, INC. FORMAN AT MAIN OFFICED	
-		
	BC OPERATING, INC.	
	432-684-9696	

# Emergency Call List

 BC Operating, Inc. Office
 432-684-9696

 Deane Durham
 432-684-9696 (Office)

 Nic Klopp
 432-684-9696 (Office)

 Bruce Madden
 432-684-9696 (Office)

 432-684-9696 (Office)
 432-684-9696 (Office)

 432-684-9696 (Office)
 432-684-9696 (Office)

# **Emergency Response Numbers**

.

New Mexico State Police	575-392-5580
Lea County Sheriff Dept	575-396-3611
Lea Regional Medical Center	575-492-5000
Ambulance	911

#### BC Operating, Inc. Gay Nineties #4H Surface Use Plan Exhibit 4 2010' FSL & 2256' FEL of Unit Letter J Section 36, T-19S, R-32E

