	UNITED STATE	NTERIOR		FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010	
BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an			N	5. Lease Serial No. NMNM94108	
abandoned w	vell. Use form 3160-3 (AP	D) for such proposals.	6. If	Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.			7. If N	7. If Unit or CA/Agreement, Name and/or No. NMNM104037X	
				8. Well Name and No. RED HILLS NORTH UNIT 904	
2. Name of Operator EOG RESOURCES INCOR	PORATEDE-Mail: stan_wagr	STAN WAGNER ner@eogresources.com		PI Well No. D-025-36237-00-S1	
3a. Address		3b. Phone No. (include area cod Ph: 432-686-3689		ield and Pool, or Exploratory ED HILLS	
MIDLAND, TX 79702 4. Location of Well <i>(Footage, Sec.</i>	T. P. M. or Super Description		S OCD	County or Parish, and State	
Sec 17 T25S R34E NENW 32.134992 N Lat, 103.4949	1000FNL 1700FWL	APR 0		EA COUNTY, NM	
12. CHECK AP	PROPRIATE BOX(ES) TO	O INDICATE NATURE OF	NOTICE, REPOR	T, OR OTHER DATA	
TYPE OF SUBMISSION		ТҮРЕ С	OF ACTION		
□ Notice of Intent	Acidize	Deepen	Production (S	tart/Resume) 🔲 Water Shut-Of	
	□ Alter Casing	Fracture Treat	□ Reclamation	Pr Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	D Other	
Final Abandonment Notice	Change Plans	Plug and Abandon		porarily Abandon	
	Convert to Injection		□ Water Dispos	al I work and approximate duration thereof	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & cirr 1/18/16 Circulate 250 bbls	Abandonment Notices shall be fil r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7.	led only after all requirements, inclu in. /8" injection tubing.	uding reclamation, have	erval, a Form 3160-4 shall be filed once been completed, and the operator has DECLAMATIO	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & cir. 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. F	Abandonment Notices shall be fil r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 12	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top o 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability	l as to plugging of the well bord under bond is retained until	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066	Abandonment Notices shall be fil r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. bi with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability	been completed, and the operator has	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & cirri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tuu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. i' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepte Liability Surface	been completed, and the operator has DECLAMATIONE S-S-IL I as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE)	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & circ 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN V	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2'' CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO ommitted to AFMSS for proc VAGNER	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepte Liability Surface (ell Information Syst t to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS	been completed, and the operator has DECLAMATIONE S-S-IL I as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE)	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit and 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For POG RESO ommitted to AFMSS for proc VAGNER	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability Surface //ell Information Syst in to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016	been completed, and the operator has DECLAMATIONE S-S-IL I as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE)	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & circ 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN V	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For POG RESO ommitted to AFMSS for proc VAGNER	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability Surface : on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE	been completed, and the operator has EXELAMATION Las to plugging of the well bore under bond is retained until restoration is completed. em 0055SE) T	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN V Signature (Electron Accepted For Record	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2'' CIBP set at 12 at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO ommitted to AFMSS for proc VAGNER ic Submission) THIS SPACE FO	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability Surface //ell Information Syst in to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016	been completed, and the operator has ECLAMATIONE S-S-IL d as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE)	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit and 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron Accepted Fot Record	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESOL ommitted to AFMSS for proc VAGNER ic Submission) THIS SPACE FO ched. Approval of this notice doe equitable title to those rights in th	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	uding reclamation, have of 4-1/2" liner at Accepter Liability Surface : on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE	been completed, and the operator has ECLAMATIO ESCLA	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. I 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron Approved By Conditions of approval, if any, are attac certify that the applicant holds legal or	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bt plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO ommitted to AFMSS for proce- VAGNER ic Submission) THIS SPACE F(a. Approval of this notice doe equitable title to those rights in th nduct operations thereon. 43 U.S.C. Section 1212, make it at	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	of 4-1/2" liner at Accepter Liability Surface /ell Information Syst it to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE	em 0055SE) T	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron Approved By Conditions of approval, if any, are attaccertify that the applicant to co Title 18 U.S.C Section 1001 and Title States any false, fictitious or fraudule	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2'' CIBP set at 12 at 12000'. Circulate 140 bt plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO ommitted to AFMSS for proce- VAGNER ic Submission) THIS SPACE Fe A. Approval of this notice doe equitable title to those rights in th nduct operations thereon. 43 U.S.C. Section 1212, make it an statements or representations a	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	of 4-1/2" liner at Accepter Liability Surface . /ell Information Syst it to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE MET MO Ind willfully to make to a m.	been completed, and the operator has DECLAMATIONE S-5-14 I as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE) T B-23 Date	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron Approved By Conditions of approval, if any, are attaccertify that the applicant to co Title 18 U.S.C Section 1001 and Title States any false, fictitious or fraudule	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2" CIBP set at 1: at 12000'. Circulate 140 bb plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO committed to AFMSS for proce VAGNER ic Submission) THIS SPACE FO ched. Approval of this notice doe equitable title to those rights in the nduct operations thereon. 43 U.S.C. Section 1212, make it and nt statements or representations a	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	of 4-1/2" liner at Accepter Liability Surface . /ell Information Syst it to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE MET MO Ind willfully to make to a m.	been completed, and the operator has DECLAMATIONE S-S-IL I as to plugging of the well bore under bond is retained until restoration is completed. em 0055SE) T B-S-Z3 Date	
determined that the site is ready for 1/11/16 MIRU to P&A. 1/13/16 Unset packer & ciri 1/18/16 Circulate 250 bbls 1/19/16 Finish POOH w/ tu 11440'. RIH w/ 4-1/2" gaug Notified BLM. Instructed to 1/20/16 RIH w/ 3-3/4" bit an 1/21/16 Clean out to 12066 1/22/16 POOH w/ tubing. If 1/25/16 RIH and tag CIBP Spot 90 sx Class H cement 14. I hereby certify that the foregoing Name (Printed/Typed) STAN W Signature (Electron Approved By Conditions of approval, if any, are attaccertify that the applicant to co Title 18 U.S.C Section 1001 and Title States any false, fictitious or fraudule	Abandonment Notices shall be fir r final inspection.) culate 210 bbls brine. Shut- brine. Begin POOH w/ 2-7/ bing and packer. Laydown. e ring and TD at 11472'. continue working deeper to nd sub. Shut-in. ' with no obstructions. RIH w/ 4-1/2'' CIBP set at 12 at 12000'. Circulate 140 bt plug from 12000' to 11165' g is true and correct. Electronic Submission # For EOG RESO ommitted to AFMSS for proce- VAGNER ic Submission) THIS SPACE Fe A. Approval of this notice doe equitable title to those rights in th nduct operations thereon. 43 U.S.C. Section 1212, make it an statements or representations a	led only after all requirements, inclu- in. /8" injection tubing. TIH w/ 7" gauge ring to top of 12000'. 2000'.	of 4-1/2" liner at Accepter Liability Surface . /ell Information Syst it to the Hobbs on 03/03/2016 (16LJ JLATORY ANALYS /2016 E OFFICE USE MET MO Ind willfully to make to a m.	em 0055SE) T my department or agency of the United	

Additional data for EC transaction #332080 that would not fit on the form

32. Additional remarks, continued

1/26/16 RIH and tag TOC at 11291'. Notified BLM. Instructed to Spot 25 sx Class H cement plug from 11291' to 11154'. WOC 6 hrs.

1/27/16 RIH and tag TOC at 11247'. Circulate 20 bbls mud. Spot 40 sx Class H cement plug from 10963' to 10744'. Spot 40 sx Class H cement plug from 9359' to 9140'.

1/28/16 Spot 40 sx Class H cement plug from 7525' to 7306'. RIH and cut 7" casing at 5150'.

1/29/16 Begin POOH w/ 7" casing. 2/03/16 Finish POOH w/ 7" casing. Circulate mud. Spot 70 sx cement plug from 5207' to 4962'.

2/04/16 RIH and tag TOC at 5000'. Circulate mud. Spot 85 sx cement plug from 3209' to 2946'. Spot 250 sx cement plug from 1211' to 436'.

2/05/16 RIH and tag TOC at 491'. Spot 85 sx cement plug from 262' to surface. RDMO. Clean location. Install P&A marker.