

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. <b>30-025-41969</b>
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>State 11</b>
8. Well Number <b>2</b>
9. OGRID Number <b>24010</b>
10. Pool name or Wildcat <b>West Midway-Upper Pen</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3937' GL</b>

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
**V-F PETROLEUM INC.**

3. Address of Operator  
**P.O. Box 1889, Midland, Texas 79702**

4. Well Location

Unit Letter **O** : **660** feet from the **South** line and **2,150** feet from the **East** line

Section **11** Township **17-S** Range **35-E** NMPM **Lea** County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
**3937' GL**

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT

REMEDIAL WORK  
COMMENCE DRILLING OR  
CASING/CEMENT JOB

OTHER: ☐

INT TO PA ☒  
P&A NR ☐  
P&A R ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

If the Queen (4,114' - 4,120') test to be unproductive, the following P/A operations are proposed:

2000'  
Plug @ 3,485' w/ <sup>40</sup> 25 sx CMT.  
~~Plug @ 2,800' w/ 25 sx CMT.~~  
~~Plug @ 1,500' w/ 25 sx CMT.~~  
Perf and Plug @ 525' w/ CMT to Surface.  
Cut Off CSG and Weld Plate on Top.  
Install Dry Hole Marker.

T.SALT 2000'  
B.SALT 3150'

Mud laden Fluid Between plugs

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Eric Sprinkle TITLE Petroleum Engineer DATE 4/04/2016

Type or print name Eric Sprinkle E-mail address: eric@vfpetroleum.com PHONE: 432-683-3344

For State Use Only

APPROVED BY: Mark Whitaker TITLE Petroleum Engr. Specialist DATE 04/04/2016

Conditions of Approval (if any):

APR 06 2016



Well: State 11 #2

Operator: V-F Petroleum Inc.

Location: 660 FSL &amp; 2,150 FEL

Field:

of Sec 11 T-17-S R-35-E

Elevation: GL= 3937

in Lea County, New Mexico

KB-GL= 17

API# 30-025-41969

KB= 3954

Tot Depth	Hole Size	Tops & Perfs	Casing & Cement
475	17 1/2"		13 3/8" 48# H-40 CSG w/ 495 sx CMT
		T Salt @ 1,500'	TOC @ 1,000' by CBL
		B Salt @ 2,800'	
3435	12 1/4"		9 5/8" 32# J-55 CSG w/ 1,000 sx CMT
		7 Rivers @ 3,500'	
		Queen @ 4,110'	
		Grayburg @ 4,490'	
		Perfs: 4,676' - 4,684'	
		San Andres @ 4,850'	
			CIPB @ 5,025'
		Perfs: 5,121' - 5,275'	
			5 1/2" 17# L-80 CSG w/ 1,140sx CMT
			Plug @ 5,511 w/ 65 sxs CMT
		Glorieta @ 6,330'	
		Blinberry @ 6,720'	
		Tubb @ 7,840'	Plug @ 7,502' w/ 40 sxs CMT
		Drinkard @ 8,020'	
		Abo @ 8,550'	Plug @ 9,494' w/ 40 sxs CMT
		Wolfcamp @ 9,710'	
11500	8 3/4"		Plug @ 11,460' w/ 40 sxs CMT

REMARKS: Current

Well: State 11 #2

Operator: V-F Petroleum Inc.

Location: 660 FSL &amp; 2,150 FEL

Field:

of Sec 11 T-17-S R-35-E

Elevation: GL= 3937

in Lea County, New Mexico

KB-GL= 17

API# 30-025-41969

KB= 3954

Tot Depth	Hole Size	Tops & Perfs	Casing & Cement
475	17 1/2"		13 3/8" 48# H-40 CSG w/ 495 sx CMT Perf & Plug @ 525' w/ CMT to Surf
		T Salt @ 1,500'	TOC @ 1,000' by CBL Plug @ 1,500' w/ 25 sx CMT
		B Salt @ 2,800'	Plug @ 2,800' w/ 25 sx CMT
3435	12 1/4"		9 5/8" 32# J-55 CSG w/ 1,000 sx CMT Plug @ 3,485' w/ 25 sx CMT
		7 Rivers @ 3,500'	
		Queen @ 4,110'	
		Perfs: 4,114' - 4,120'	
		Grayburg @ 4,490'	
		Perfs: 4,676' - 4,684'	CIPB @ 4,600' w/ 35' CMT
		San Andres @ 4,850'	
			CIPB @ 5,025' w/ 35' CMT
		Perfs: 5,121' - 5,275'	
		Glorieta @ 6,330'	5 1/2" 17# L-80 CSG w/ 1,140sx CMT Plug @ 5,511 w/ 65 sxs CMT
		Blinberry @ 6,720'	
		Tubb @ 7,840'	Plug @ 7,502 w/ 40 sxs CMT
		Drinkard @ 8,020'	
		Abo @ 8,550'	Plug @ 9,494 w/ 40 sxs CMT
		Wolfcamp @ 9,710'	
11500	8 3/4"		Plug @ 11,460 w/ 40 sxs CMT

REMARKS: Proposed PA