Do not use the	NOTICES AND REPO is form for proposals to	drill or to re-enter an HO D) for such proposals.	bbs 6.	NMNM03210 If Indian, Allottee or Tribe Name	
				If Unit or CA/Agreement, Name and/	
SUBMIT IN TRIPLICATE - Other instructions on re		ctions on reverse side.		8910084860	
1. Type of Well ☐ Gas Well ☐ Ott	her	1 dite	8.	Well Name and No. WEST CAP QUEEN SAND UNIT	
LEGACY RESERVES OPERATING E-Mail: lpina@lega 3a. Address PO BOX 10848 MIDLAND, TX 79702		3b. Phone No. (include area code) Ph: 432-689-5200 Ext: 5273		9. API Well No. 30-005-01090-00-S1	
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF	010	ORT, OR OTHER DATA	
TYPE OF SUBMISSION		RECE	FACTION	10- <u>-</u>	
Notice of Intent  Subsequent Percent	Acidize	<ul><li>Deepen</li><li>Fracture Treat</li></ul>	<ul><li>Production</li><li>Reclamation</li></ul>	n P&A NR	
<ul> <li>Subsequent Report</li> <li>Final Abandonment Notice</li> </ul>	<ul> <li>Casing Repair</li> <li>Change Plans</li> <li>Convert to Injection</li> </ul>	<ul> <li>New Construction</li> <li>Plug and Abandon</li> <li>Plug Back</li> </ul>	<ul> <li>Recomplete</li> <li>Temporaril</li> <li>Water Disp</li> </ul>	y Ab:	
Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar. NLLB0	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re bandonment Notices shall be fil inal inspection.) opment. OP ND wellbead POH w	give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- /rods & thg. BIH w/gauge rij	ing date of any proposition of the subsequence of t		
If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide doperations. If the operation re bandonment Notices shall be fil inal inspection.) opment. OP, ND wellhead. POH w 655'. Circulated hole with 5'& displaced to 2414'. W Oscar Torres w/BLM reque ured up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. Ni cement & circulated to su	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- nuclean fluid. Pressure te OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug ( @ 1097 & displaced to 856 D BOP, NU wellhead. Circul urface. WOC.	ing date of any proper sured and true vertice IA. Required subseques completion in a new unding reclamation, has the steed casing, essure tested cas held 500 psi. 0 1778'. Perf'd ca WOC. ated hole with more	besed work and approximate duration the al depths of all pertinent markers and z quent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perf'd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx o 03/14/16 ND wellhead, tagged	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide doperations. If the operation re bandonment Notices shall be fil inal inspection.) oment. OP, ND wellhead. POH w 655'. Circulated hole with 5'& displaced to 2414'. W Oscar Torres w/BLM reque ured up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. NI cement & circulated to su d plug @ 4'. Squeezed 55 strue and correct. Electronic Submission # For LEGACY RE mmitted to AFMSS for pro-	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- work and the subsurface of the subsurface OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug @ @ 1097 & displaced to 856' D BOP, NU wellhead. Circul rface. WOC. s x cement down the 5 1/2 & 334323 verified by the BLM W SERVES OPERATING, sent cessing by DAVID GLASS on	ing date of any propo- sured and true vertic: IA. Required subseq completion in a new uding reclamation, ha ng to 2700'. sted casing, essure tested cas , held 500 psi. (2) 1778'. Perf'd ca , WOC. ated hole with mu & 8 5/8 annulas a cell Information Sy to the Roswell 03/22/2016 (16DR	essed work and approximate duration the al depths of all pertinent markers and zu upent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud and completed to the operator of the operator has sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, asing ud and completed to the operator has sing, and completed to the operator has sing, and completed to the operator has sing, asing completed to the operator has sing completed to the operator has	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perf'd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx o 03/14/16 ND wellhead, tagged 14. I hereby certify that the foregoing is Name ( <i>Printed/Typed</i> ) LAURA PI	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandomment Notices shall be fil inal inspection.) oment. OP, ND wellhead. POH w 655'. Circulated hole with by & displaced to 2414'. W Oscar Torres w/BLM reque ured up on perfs. Int @ 2007 & displaced to fs. Spotted 25 sx cement . Perf d casing @ 210'. Ni cement & circulated to su d plug @ 4'. Squeezed 55 strue and correct. Electronic Submission # For LEGACY RE ommitted to AFMSS for pro- INA	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- //rods & tbg. RIH w/gauge rin mud laden fluid. Pressure te OC. Tag'd plug @ 2498'. Pro est). Pressure tested casing, 1766'. WOC. Tagged plug ( @ 1097 & displaced to 856' D BOP, NU wellhead. Circul rface. WOC. 5 sx cement down the 5 1/2 & 334323 verified by the BLM W SSERVES OPERATING, sent cessing by DAVID GLASS on Title COMF	ing date of any propo- sured and true vertic: IA. Required subseq completion in a new uding reclamation, ha ng to 2700'. steed casing, essure tested cas , held 500 psi. (2) 1778'. Perf'd ca , WOC. ated hole with mu & 8 5/8 annulas a cell Information Sy to the Roswell 03/22/2016 (16DR PLIANCE COORI	essed work and approximate duration the al depths of all pertinent markers and zu upent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud and completed to the operator of the operator has sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, sing, asing ud and completed to the operator has sing, sing, asing ud and completed to the operator has sing, and completed to the operator has sing, and completed to the operator has sing, asing completed to the operator has sing completed to the operator has	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perf'd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx o 03/14/16 ND wellhead, tagged	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide doperations. If the operation re bandonment Notices shall be fil inal inspection.) oment. OP, ND wellhead. POH w 655'. Circulated hole with 5'& displaced to 2414'. W Oscar Torres w/BLM reque irred up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. Ni cement & circulated to su d plug @ 4'. Squeezed 55 s true and correct. Electronic Submission # For LEGACY RE mmitted to AFMSS for pro- INA	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- mud laden fluid. Pressure te OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug @ @ 1097 & displaced to 856 D BOP, NU wellhead. Circul rface. WOC. 5 sx cement down the 5 1/2 & 334323 verified by the BLM W SERVES OPERATING, sent to cessing by DAVID GLASS on Title COMF	ing date of any propositive and true vertic: IA. Required subsequences of the completion in a new unding reclamation, have the cost of the	esed work and approximate duration the al depths of all pertinent markers and zo upent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud und exception of the state of the state of the state state of the state of the state of the state of the state state of the state of the state of the state of the state state of the state of the state of the state of the state state of the state of th	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perf'd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx 0 03/14/16 ND wellhead, tagged 14. Thereby certify that the foregoing is Co Name ( <i>Printed/Typed</i> ) LAURA Pl Signature (Electronic S	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandonment Notices shall be fil inal inspection.) oment. OP, ND wellhead. POH w 655'. Circulated hole with '& displaced to 2414'. W Oscar Torres w/BLM reque ured up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. NI cement & circulated to su d plug @ 4'. Squeezed 55 strue and correct. Electronic Submission # For LEGACY RE mmitted to AFMSS for pro- INA Submission)	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- mud laden fluid. Pressure te OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug @ (@ 1097 & displaced to 856 D BOP, NU wellhead. Circul rface. WOC. 5 sx cement down the 5 1/2 & 334323 verified by the BLM W SERVES OPERATING, sent f cessing by DAVID GLASS on Title COMF Date 03/22/ DR FEDERAL OR STATE	ing date of any propo- sured and true vertic: IA. Required subsequences completion in a new unding reclamation, have the steed casing, essure tested case , held 500 psi. (2) 1778'. Perf'd ca , WOC. ated hole with more & 8 5/8 annulas a cell Information Sy to the Roswell 03/22/2016 (16DR CLIANCE COORI (2016) EOFFICE USE	esed work and approximate duration the al depths of all pertinent markers and z upent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud and completed to the operator of completed to the operator of completed to the operator of stem G0136SE) DINATOR	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perfd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx 0 03/14/16 ND wellhead, tagged 14. Thereby certify that the foregoing is Co Name ( <i>Printed/Typed</i> ) LAURA PI Signature (Electronic S	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide doperations. If the operation re bandonment Notices shall be fil inal inspection.) opment. OP, ND wellhead. POH w 655'. Circulated hole with i' & displaced to 2414'. W Oscar Torres w/BLM reque ured up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. NI cement & circulated to su d plug @ 4'. Squeezed 55 strue and correct. Electronic Submission # For LEGACY RE mmitted to AFMSS for pro- INA Submission) THIS SPACE FO	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- mud laden fluid. Pressure te OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug @ @ 1097 & displaced to 856 D BOP, NU wellhead. Circul rface. WOC. 5 sx cement down the 5 1/2 & 334323 verified by the BLM W SERVES OPERATING, sent cessing by DAVID GLASS on Title COMF Date 03/22/ DR FEDERAL OR STATE	ing date of any propositive and true vertic: IA. Required subsequences of the completion in a new unding reclamation, have the cost of the	sing, and and best work and approximate duration the al depths of all pertinent markers and zo puent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud and correction co	
If the proposal is to deepen directions Attach the Bond under which the woi following completion of the involved testing has been completed. Final At determined that the site is ready for fi 03/04/16 MIRU plugging equip 03/07/16 Dug up cellar, NU BO 03/08/16 Set 5 1/2 CIBP @ 26 spotted 25 sx cement @ 2655 pressured up 300 psi. 03/09/16 Isolated holes (per C Perf'd casing @ 1940', pressu 03/10/16 Spotted 25 sx cemer @ 1040', pressured up on per 03/11/16 Tagged plug @ 876' laden fluid. Squeezed 160 sx 0 03/14/16 ND wellhead, tagged 14. Thereby certify that the foregoing is Co Name ( <i>Printed/Typed</i> ) LAURA PI Signature (Electronic S	eration (clearly state all pertiner ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandonment Notices shall be fil inal inspection.) opent. OP, ND wellhead. POH w 655'. Circulated hole with '& displaced to 2414'. W Oscar Torres w/BLM reque irred up on perfs. nt @ 2007 & displaced to fs. Spotted 25 sx cement . Perfd casing @ 210'. NI cement & circulated to su d plug @ 4'. Squeezed 55 true and correct. Electronic Submission # For LEGACY RE mmitted to AFMSS for pro- INA Submission) THIS SPACE FO	nt details, including estimated start give subsurface locations and mea the Bond No. on file with BLM/B sults in a multiple completion or re ed only after all requirements, inclu- mud laden fluid. Pressure te OC. Tag'd plug @ 2498'. Pro- est). Pressure tested casing 1766'. WOC. Tagged plug @ @ 1097 & displaced to 856 D BOP, NU wellhead. Circul rface. WOC. is x cement down the 5 1/2 & 334323 verified by the BLM W ESERVES OPERATING, sent Cessing by DAVID GLASS on Title COMF Date 03/22/ DR FEDERAL OR STATE Sant Warrant or	ing date of any propo- sured and true vertic: IA. Required subseq completion in a new uding reclamation, ha of to 2700'. ested casing, essure tested cas , held 500 psi. (a) 1778'. Perf'd ca . WOC. ated hole with mo & 8 5/8 annulas a cell Information Sy to the Roswell 03/22/2016 (16DR PLIANCE COORI (2016) E OFFICE USE	esed work and approximate duration the al depths of all pertinent markers and z upent reports shall be filed within 30 day interval, a Form 3160-4 shall be filed of ave been completed, and the operator has sing, asing ud and completed to the operator of completed to the operator of completed to the operator of stem G0136SE) DINATOR	

•

## Additional data for EC transaction #334323 that would not fit on the form

## 32. Additional remarks, continued

circulated to surface. 03/16/16 Welded on "Above Ground Dry Hole Marker". Backfilled cellar. Removed deadmen. Cleaned location and moved off. Installed Closed-Loop System with steel tanks. Hauled contents from Closed-Loop System to approved NMOCD disposal location according to Rule 19.15.17.