

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-32668
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name TRUMPETER 4 STATE
8. Well Number 1
9. OGRID Number 6137
10. Pool name or Wildcat Livingston Ridge; Delaware, East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3809' KB; 3796' GL; 13' KB to GL

HOBBS OCD

APR 21 2016

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Devon Energy Production Company, LP

3. Address of Operator
333 W. Sheridan Avenue, Oklahoma City, OK 73102

4. Well Location

Unit Letter O : 660 feet from the South line and 1980 feet from the East line
Section 04 Township 22S Range 32E NMPM Lea County, NM

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☐
CASING/CEMENT JOB ☐
OTHER: ☐
INT TO P&A ☒
P&A NR ☐
P&A R ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU. POOH w/rod pump and 2-7/8" production tubing from 7,204'.
2. Set CIBP @ 7,130'. Tag plug. Spot 25 sx (250') CI C @ 7,130' - 6,880'.
3. Spot 40 sx (400') CI C @ 4,900' - 4,500'. Tag TOC. (B.Salt/T.Delaware @ 4,853; 8-5/8" casing shoe @ 4,600')
4. Perf 5-1/2" casing @ 1,500'. Pump 120 sx (500') CI C in/out @ 1,500' - 1,000'. Tag TOC. (3000' spacer; T.Salt @ 1,080')
5. Perf 5-1/2" casing @ 660'. Pump 155 sx CI C in/out @ 660' to surface.
6. Cut wellhead off. Set dry hole marker.

Spud Date:

Rig Release

NOTIFY OCD 24 HOURS PRIOR TO BEGINNING
PLUGGING OPERATIONS

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack TITLE Production Technologist DATE 4-18-16

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com PHONE: 405-552-4615

For State Use Only

APPROVED BY: Mark Whitaker TITLE Petroleum Engr. Specialist DATE 4-21-2016

Conditions of Approval (if any):

APR 22 2016

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: TRUMPETER 4 STATE #1		Field: LIVINGSTON RIDGE EAST	
Location: 660' FSL & 1980' FEL; 04-T225-R32E		County: LEA	State: NM
Elevation: 3809' KB; 3796' GL; 13' KB to GL		Spud Date: 9/26/94	Compl Date: 11/10/94
API#: 30-025-32668	Prepared by: Ronnie Slack	Date: 4/18/16	Rev:

CURRENT WELLBORE

17-1/2" hole
13-3/8", 48#, @ 606'
 Cmt'd w/1025 sx to surface

T.Salt--1,080'
 B.Salt/T.Delaware--4,853'
 T.Bone Spring--8,802'

ETOC @ 3,350'-cbl (10/18/94)

11" hole
8-5/8", 32#, K55, @ 4,600'
 Cmt'd w/1600 sx to surface

DELAWARE (10/19/94)
 7,162' - 7,165'

7,249' - 7,250'

7,383' - 7,385'
 7,395'

7-7/8" Hole
5-1/2", 15.5# & 17#, J55 & K55 @ 7,620'
 Cmt'd w/725 sx. TOC @ 3,350'-cbl-10/18/94

2-7/8", 6.5#, J55 prod tubing. (8/21/99)

TAC @ 7,167'
 SN @ 7,168'
 Bull Plug, EOT @ 7,204'

10' cmt. 7,330' PBD. (10/29/94)
 CIBP @ 7,340' (10/29/94)

Tagged TOC @ 7,818'. (10/13/94)
 Spot 75 sx CI H @ 7,989'. (10/13/94)

8,900' MD

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: TRUMPETER 4 STATE #1		Field: LIVINGSTON RIDGE EAST	
Location: 660' FSL & 1980' FEL; 04-T22S-R32E		County: LEA	State: NM
Elevation: 3809' KB; 3796' GL; 13' KB to GL		Spud Date: 9/26/94	Compl Date: 11/10/94
API#: 30-025-32668	Prepared by: Ronnie Slack	Date: 4/18/16	Rev:

PROPOSED PLUG & ABANDONMENT

17-1/2" hole
13-3/8", 48#, @ 606'
 Cmt'd w/1025 sx to surface

Proposed:
 3. Cut wellhead off. Set dry hole marker.
 2. Pmp 155 sx CI C in/out @ 660' to surface'.
 1. Perf sqz holes @ 660'.

9# Mud

Proposed:
 3. Tag TOC.
 2. Pmp 120 sx (500') CI C in/out @ 1,500' -1,000' .
 1. Perf sqz holes @ 1,500'.
 (3000' spacer requirement; T.Salt @ 1,080')

ETOC @ 3,350'-cbl (10/18/94)

9# Mud

11" hole
8-5/8", 32#, K55, @ 4,600'
 Cmt'd w/1600 sx to surface

Proposed:
 2. Tag TOC.
 1. Spot 40 sx (400') CI C @ 4,900' - 4,500'.
 (B.Salt/T.Delaware @ 4,853')

9# Mud

Proposed:
 2. Spot 25 sx (250') CI C @ 7,130' - 6,880'
 1. Set CIBP @ 7,130'. Tag plug.

DELAWARE (10/19/94)
 7,162' - 7,165'

7,249' - 7,250'

10' cmt. 7,330' PBD. (10/29/94)
 CIBP @ 7,340' (10/29/94)

7,383' - 7,385'
 7,395'

7-7/8" Hole
5-1/2", 15.5# & 17#, J55 & K55 @ 7,620'
 Cmt'd w/725 sx. TOC @ 3,350'-cbl-10/18/94

Tagged TOC @ 7,818'. (10/13/94)
 Spot 75 sx CI H @ 7,989'. (10/13/94)

8,900' MD