SUNDRY Do not use th	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS o not use this form for proposals to drill or to re-enter an andoned well. Use form 3160-3 (APD) for such proposals.			FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010 5. Lease Serial No. NMNM02965A 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRI	IPLICATE - Other instruc	tions on reverse side.	55 OCD7. If Unit or CA/Ag NMNM135754	reement, Name and/or No.	
1. Type of Well		MAY	9 2016 8. Well Name and N	0.	
🛛 Oil Well 🔲 Gas Well 🔲 Ot			THOR 21 FED 0	COM 704H	
2. Name of Operator EOG RESOURCES INCORP	ORATEDE-Mail: stan_wagn	STAN WAGNER REC	EIVED 9. API Well No. 30-025-42816	-00-X1	
3a. Address		3b. Phone No. (include area code Ph: 432-686-3689		0. Field and Pool, or Exploratory WC-025 G09 S263327G	
MIDLAND, TX 79702	×	11. 102 000 0000	110 020 000	OEUODENO /	
Location of Well (Footage, Sec., 1	T., R., M., or Survey Description	Y	11. County or Parish	h, and State	
Sec 21 T26S R33E SWSE 17	OFSL 1670FEL		LEA COUNTY	ζ, NM	
12. CHECK APP	ROPRIATE BOX(ES) TO	DINDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	Acidize	Deepen	Production (Start/Resume)	U Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamation	□ Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	🛛 Other	
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Drilling Operation	
	Convert to Injection	Plug Back	U Water Disposal		
following completion of the involved testing has been completed. Final Al	d operations. If the operation res bandonment Notices shall be file	sults in a multiple completion or rec	A. Required subsequent reports shall b ompletion in a new interval, a Form 31 ding reclamation, have been completed	60-4 shall be filed once	
determined that the site is ready for f 4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield.				
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V				
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole.	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. true and correct. Electronic Submission #3 For EOG RESOU		Il Information System to the Hobbs n 05/03/2016 (16PP0617SE)		
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 , Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole.	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. 30 minutes. Test good. true and correct. Electronic Submission #3 For EOG RESOU mitted to AFMSS for proce	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o	II Information System to the Hobbs n 05/03/2016 (16PP0617SE) ATORY ANALYST		
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole.	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. 30 minutes. Test good. For Eog RESOU amitted to AFMSS for proce	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o Title REGUL	n 05/03/2016 (16PP0617SE) ATORY ANALYST		
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole. 4. I hereby certify that the foregoing is <b>Corr</b> Name ( <i>Printed/Typed</i> ) STAN WA Signature (Electronic S	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. 30 minutes. Test good. For Eog RESOU mitted to AFMSS for proce GNER	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o Title REGUL Date 05/03/2	n 05/03/2016 (16PP0617SE) ATORY ANALYST 016		
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole. 4. I hereby certify that the foregoing is <b>Corr</b> Name ( <i>Printed/Typed</i> ) STAN WA Signature (Electronic S	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. 30 minutes. Test good. For Eog RESOU mitted to AFMSS for proce GNER	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o Title REGUL	n 05/03/2016 (16PP0617SE) ATORY ANALYST 016		
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 , Tested casing to 1500 psi for Resumed drilling 9-7/8" hole. 4. I hereby certify that the foregoing is Corr Name ( <i>Printed/Typed</i> ) STAN WA Signature (Electronic S ACCEPTED F /S/ DAVI	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS og, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. 30 minutes. Test good. For Eog RESOU mitted to AFMSS for proce GNER	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o Title REGUL Date 05/03/2	n 05/03/2016 (16PP0617SE) ATORY ANALYST 016	Date	
4/30/16 Spud 14-3/4" hole. 5/01/16 Ran 21 jts 10-3/4", 40.5#, J55 Cemented lead w/ 345 sx Clas tail w/ 201 sx Class C, 14.8 pp Circulated 37 bbls cement to s 5/02/16 , Tested casing to 1500 psi for 3 Resumed drilling 9-7/8" hole. 4. I hereby certify that the foregoing is <b>Corr</b> Name ( <i>Printed/Typed</i> ) STAN WA Signature (Electronic S	STC casing set at 939'. ss C, 13.5 ppg, 1.79 CFS bg, 1.34 CFS yield. surface. BLM witnessed. V 30 minutes. Test good. True and correct. Electronic Submission #3 For EOG RESOU mitted to AFMSS for proce (GNER Submission) OR FRIS SPACE FO D R. CLASS 6_2016 d. Approval of this notice does intable title to those rights in the	VOC 22 hrs. 38214 verified by the BLM We RCES INCORPORATED, sent ssing by PRISCILLA PEREZ o Title REGUL Date 05/03/2 R FEDERAL OR STATE Title Title	n 05/03/2016 (16PP0617SE) ATORY ANALYST 016	Date	

Accepted for Record Only MAB/OCD 5/23/2016

ef. 656 1