Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103 Revised July 18, 2013	
District I (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II (575) 748-1283	Energy, Minerals and Natural Resources	WELL API NO. 30-025-34556 34-555	
District II (715) (745-1265) O. 811 S. First St., Artesia, NM 88210 District III (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505 O.	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.	5. Indicate Type of Lease	
	Santa Fe, NM 87505	6. State Oil & Gas Lease No.	
SUNDRY NOTICE (DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR. USE "APPLICAT	7. Lease Name or Unit Agreement Name State A-32		
PROPOSALS.) 1. Type of Well: Oil Well Ga	8. Well Number #5		
2. Name of Operator Herman L. Loeb LLC	JUN 1 5 2016	9. OGRID Number 020451 264953	
3. Address of Operator PO Box 838, Lawrenceville, Ill. 62439 RECEIVED		10. Pool name or Wildcat Jalmat, Tan, Y, 7R	
4. Well Location Unit Letter D :710)' feet from the North line and 660'	feet from the West line	
Section 32	Township 24 S Range 37 E	NMPM County Lea	
	11. Elevation (Show whether DR, RKB, RT, GR, etc. 3,243' GR	.)	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DOWNHOLE COMMINGLE	INT TO PA P&A NR P&A R	SUBSEQUENT RE REMEDIAL WORK	PORT OF: ALTERING CASING P AND A
CLOSED-LOOP SYSTEM OTHER:		OTHER:	

 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/29/2016: Set CIBP @ 2,805' instead of 2,801' due to csg col @ 2,799'.

5/2/2016: PT CiBP & csg to 500 psi. Tstd OK. Spot 30 sx Class C cmt mixed @ 14.8 ppg on top of CIBP. Spot 22 bbls 9.5 ppg salt gel spacer @ 2,365'. Perf 1,060'-1,061'. PT to 500 psi w/no leak off. Spot 25 sx Class C cmt mixed @ 14.8 ppg @ 1,119'. Spot 2.5 bbls 9.5 ppg salt gel spacer @ 746'.

5/3/2016: Tgd cmt plug @ 792'. Perf 605'-606'. PT to 500 psi w/no leak off. Spot 25 sx Class cmt mixed @ 14.8 ppg @ 684'. Spot 9.5 ppg salt gel spacer fr/311' to surface.

5/4/2016: Tgd cmt plug @ 314'. Perf 60'-61'. Estb circ up 4 1/2" csg annulus. Ppd 38 sx Class C cmt mixed @ 14.8 ppg & had good cmt to surface.

5/5/2016 Cut off all csg strings and found good cmt to surface in all of them. Welded on cap & installed dry hole marker.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
MA D' ODA		
SIGNATURE Mechan Holly_TITLE_Agent for Herman L. Loeb LLC_DAT	E_6/14/2016	
Type or print nameMichael Polley E-mail address: polleyms@gmail.com PHONE:	719-342-5600	
For State Use Only	and the second sec	
APPROVED BY: Mahuhitah TITLE P.E.S.	DATE 6/15/2016	
Conditions of Approval (if any):		m