Form 3160-5 (August 2007)		UNITED STATES EPARTMENT OF THE IN UREAU OF LAND MANAG	TERIOR Hobbs	5	FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010	
	SUNDRY	NOTICES AND REPOR	TS ON WELLS		Lease Serial No. NMLC062486	
	Do not use thi abandoned we	is form for proposals to drill or to re-enter an 1.000 2.7 2016		2 7 2016 ^{6. II}	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse STRECEIVED					 If Unit or CA/Agreement, Name and/or No. 8910063990 	
1. Type of Well				8. Well Name and No. DRICKEY QUEEN SAND UNIT 831		
2. Name of Operato		Contact:	AURA PINA ylp.com		API Well No. 80-005-00992-00-S1	
3a. Address PO BOX 1084 MIDLAND, TX			3b. Phone No. (include area cod Ph: 432-689-5200 Ext: 52		Field and Pool, or Exploratory CAPROCK-QUEEN	
4. Location of Well	(Footage, Sec., T.	, R., M., or Survey Description)	1	11.	County or Parish, and State	
Sec 4 T14S R	31E SWNW 198	BOFNL 990FWL		c	CHAVES COUNTY, NM	
12.	CHECK APPR	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, REPOR	RT, OR OTHER DATA	
TYPE OF SUI	BMISSION	4	ТҮРЕ С	OF ACTION		
□ Notice of Int	ent		Deepen	Production (S	tart/Re INT TO PA	
Subsequent F	Report	Alter Casing	Fracture Treat	Reclamation	P&A NR	
Final Abando		Casing Repair	New Construction Plug and Abandon	 Recomplete Temporarily / 	Aband P&A R PM.	
	omment rotice	Convert to Injection	Plug Back	Water Dispos		
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/24/16 MIRU 05/25/16 POH 05/26/16 POH	to deepen directiona under which the wor stion of the involved completed. Final Ab he site is ready for fin U plugging equip I w/rods, dug out I w/rods and tbg.	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed	ve subsurface locations and meas e Bond No. on file with BLM/BL Its in a multiple completion or rec only after all requirements, inclu	ured and true vertical of A. Required subseque completion in a new int ding reclamation, have	d work and approximate duration thereof. depths of all pertinent markers and zones. nt reports shall be filed within 30 days terval, a Form 3160-4 shall be filed once been completed, and the operator has	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfor casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move	to deepen directiona under which the wor stion of the involved completed. Final Ab he site is ready for fir U plugging equip I w/rods, dug out I w/rods, dug out I w/rods, dug out I w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2015 0'. Squeezed 35 ged plug @ 398'. I plug @ 326'. Pr urface. Topped c ed in welder and	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed	ve subsurface locations and meas e Bond No. on file with BLM/BI tts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tage WOC. 800-350' (approved by Kev not test. Spotted 25 sx cem wn and moved off. cut off wellhead. Welded or	cement @ 2700' 2712-680'. ged plug @ 1884'. in B ussell w/BLM). ent @ 326' and n "Above Ground D	Perfd	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfor casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move	to deepen directiona under which the wor stion of the involved completed. Final Ab he site is ready for fin U plugging equip l w/rods, dug out l w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar.	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed 00'. Circulated hole w/mud //tbg. Pressure tested casir 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 ressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n	ve subsurface locations and meas e Bond No. on file with BLM/BL ts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tag WOC. 300-350' (approved by Kev tot test. Spotted 25 sx cem wn and moved off. but off wellhead. Welded or noved off. Installed Closed	A. Required subseque completion in a new int ding reclamation, have cement @ 2700' 0 712-680'. ged plug @ 1884'. in B ussell w/BLM). ent @ 326' and n "Above Ground E -Loop System with	em	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/24/16 MIRU 05/25/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfo casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move Hole Marker."	to deepen directiona under which the wor stion of the involved completed. Final Ab he site is ready for fin U plugging equip l w/rods, dug out l w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar.	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) oment. and ND wellhead, installed 00'. Circulated hole w/mud v/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 ressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RES mmitted to AFMSS for proce	ve subsurface locations and meas e Bond No. on file with BLM/BI its in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tage WOC. 300-350' (approved by Kev iot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on 0	A. Required subseque completion in a new int ding reclamation, have cement @ 2700' 0 712-680'. ged plug @ 1884'. in B ussell w/BLM). ent @ 326' and n "Above Ground E -Loop System with	Perfd Pry Perfd Perfd Parfice Perfd Pe	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/24/16 MIRU 05/25/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfo casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move Hole Marker."	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fir U plugging equip I w/rods, dug out I w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2015 0'. Squeezed 35 ged plug @ 998'. I plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar.	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) oment. and ND wellhead, installed 00'. Circulated hole w/mud //tbg. Pressure tested casir 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 ressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RES mmitted to AFMSS for proce NA	ve subsurface locations and meas e Bond No. on file with BLM/BI its in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tage WOC. 300-350' (approved by Kev iot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on 0	cement @ 2700' 0 712-680'. ged plug @ 1884'. in B ussell w/BLM). ent @ 326' and n "Above Ground D Lianformation System o the Roswell 06/15/2016 (16DRG0 LIANCE COORDIN	Perfd Pory Loca Control Contro	
If the proposal is Attach the Bond u following completesting has been c determined that th 05/24/16 MIRL 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfor casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move Hole Marker."	to deepen directiona under which the wor stion of the involved completed. Final Ab he site is ready for fin U plugging equip l w/rods, dug out l w/rods, dug out l w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 998'. 1 plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is cor ped) LAURA Pli	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) oment. and ND wellhead, installed 00'. Circulated hole w/mud w/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 ressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RESI mmitted to AFMSS for proce NA	ve subsurface locations and meas e Bond No. on file with BLM/BI ts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tagg WOC. 300-350' (approved by Kev tot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP	cement @ 2700' @ 712-680'. ged plug @ 1884'. in Bussell w/BLM). ent @ 326' and n "Above Ground D -Loop System with ell Information Syste o the Roswell D6/15/2016 (16DRG0 LIANCE COORDIN	Perfd Perfd Pry Perfd Parsen Perfd Per	
If the proposal is Attach the Bond u following completesting has been c determined that th 05/24/16 MIRL 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfor casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to st 06/02/16 Move Hole Marker."	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fin U plugging equip l w/rods, dug out l w/rods, dug out l w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is comped) LAURA PII (Electronic S	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) oment. and ND wellhead, installed 00'. Circulated hole w/mud w/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 For Legacy RESI mmitted to AFMSS for proce NA ubmission) THIS SPACE FOR	ve subsurface locations and meas e Bond No. on file with BLM/BI tts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tagg WOC. 300-350' (approved by Kev iot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed- 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP Date 06/15/2 R FEDERAL OR STATE	cement @ 2700' @ 712-680'. ged plug @ 1884'. in Bussell w/BLM). ent @ 326' and n "Above Ground D -Loop System with ell Information Syste o the Roswell D6/15/2016 (16DRG0 LIANCE COORDIN	Perfd Perfd Pry Perfd Parsen Perfd Per	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/24/16 MIRU 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfu casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to su 06/02/16 Move Hole Marker." 14. I hereby certify to Name (Printed/Ty) Signature	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fin U plugging equip l w/rods, dug out l w/rods, dug out l w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2015 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is cor ped) LAURA PII (Electronic S (ID_R GLASS	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) oment. and ND wellhead, installed 00'. Circulated hole w/mud w/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 16 For Legacy RESI mitted to AFMSS for proce NA Ubmission) THIS SPACE FOR	ve subsurface locations and meas e Bond No. on file with BLM/BI its in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tagg WOC. 300-350' (approved by Kev iot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed- 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP Date 06/15/2 R FEDERAL OR STATE 	cement @ 2700' 2712-680'. ged plug @ 1884'. in Bussell w/BLM). ent @ 326' and n "Above Ground D -Loop System with bit Information System bit Information System Cop System with D6/15/2016 (16DRG0 LIANCE COORDIN 2016 OFFICE USE EUM ENGINEER	Perfd Perfd Perfd Particle and the operator has em 1243SE) NATOR	
If the proposal is Attach the Bond u following completesting has been c determined that the 05/24/16 MIRU 05/25/16 POH 05/26/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfuccasing @ 1110 06/01/16 Tagg WOC. Tagged circulated to su 06/02/16 Move Hole Marker." 14. I hereby certify the Name (Printed/Ty) Signature 	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fin U plugging equip w/rods, dug out i w/rods, dug out i w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is cor ped) LAURA PII (Electronic S /ID_R GLASS	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed 00'. Circulated hole w/mud //tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 Spotted 30 sx cement @ 6 off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RESI mmitted to AFMSS for proce NA ubmission) THIS SPACE FOR 1. Approval of this notice does no itable title to those rights in the st ct operations thereon.	ve subsurface locations and mease e Bond No. on file with BLM/BI tts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tage WOC. 300-350' (approved by Kev iot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed- 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP Date 06/15/2 R FEDERAL OR STATE Date 06/15/2 R FEDERAL OR STATE	cement @ 2700' 2712-680'. ged plug @ 1884'. in Bussell w/BLM). ent @ 326' and n "Above Ground D -Loop System with bil Information System of the Roswell D6/15/2016 (16DRG0 LIANCE COORDIN 2016 OFFICE USE EUM ENGINEER I d willfully to make to a	Perfd Perfd Perfd Particle and the operator has em 1243SE) NATOR	
If the proposal is Attach the Bond u following comple testing has been c determined that th 05/24/16 MIRU 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfor casing @ 1110 06/01/16 Tagg WOC. Tagged circulated to su 06/02/16 Move Hole Marker." 14. I hereby certify the Name (Printed/Typ Signature 	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fin U plugging equip I w/rods, dug out I w/rods, dug out I w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is Cor ped) LAURA PII (Electronic S I fany, are attached nt holds legal or equi e applicant to conduu a 1001 and Title 43 to tious or fraudulent s ** BLM REVI as to plug ging	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed 00'. Circulated hole w/mud w/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 6 eressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RESI mmitted to AFMSS for proce NA ubmission) THIS SPACE FOR 1. Approval of this notice does no itable title to those rights in the st ct operations thereon. U.S.C. Section 1212, make it a cri tatements or representations as to SED ** BLM REVISED * g of the	ve subsurface locations and mease e Bond No. on file with BLM/BI tts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tagg WOC. 300-350' (approved by Kev tot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed- 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP Date 06/15/2 R FEDERAL OR STATE of twarrant or ibject lease Office Roswel ime for any person knowingly and any matter within its jurisdiction ** BLM REVISED ** BLI	A. REVISED ** B	depths of all pertinent markers and zones. nt reports shall be filed within 30 days terval, a Form 3160-4 shall be filed once been completed, and the operator has Perfd Perfd Perfd pry em 2243SE) NATOR Date 06/15/2 any department or agency of the United BLM REVISED **	
If the proposal is Attach the Bond u following completesting has been c determined that the 05/24/16 MIRU 05/25/16 POH 05/26/16 POH 05/27/16 Set 4 and displaced 05/31/16 Perfuc 06/01/16 Tagg WOC. Tagged circulated to su 06/02/16 Move Hole Marker." 14. I hereby certify the Name (Printed/Typ Signature Approved By_DAV Conditions of approval certify that the applican which would entitle the Title 18 U.S.C. Section States any false, fictific Approved a well bore.	to deepen directiona under which the wor etion of the involved completed. Final Ab he site is ready for fin U plugging equip w/rods, dug out i w/rods, dug out i w/rods and tbg. 4 1/2 CIBP @ 27 to 2453'. POH w d casing @ 2016 0'. Squeezed 35 ged plug @ 326'. Pr urface. Topped c ed in welder and Backfilled cellar. that the foregoing is cor ped) LAURA PII (Electronic S /ID_R GLASS	Illy or recomplete horizontally, gi k will be performed or provide th operations. If the operation resul andonment Notices shall be filed nal inspection.) ment. and ND wellhead, installed 00'. Circulated hole w/mud w/tbg. Pressure tested casin 5'. Squeezed 35 sx cement sx cement @ 1110-1000'. Spotted 30 sx cement @ 8 eressure tested casing, did r off with cement. Rigged dow backhoe. Dug out cellar. C . Removed deadmen and n true and correct. Electronic Submission #34 For LEGACY RESI mmitted to AFMSS for proce NA ubmission) THIS SPACE FOR 1. Approval of this notice does no itable title to those rights in the st ct operations thereon. U.S.C. Section 1212, make it a cri tatements or representations as to SED ** BLM REVISED * g of the er bond	ve subsurface locations and mease e Bond No. on file with BLM/BI tts in a multiple completion or rec only after all requirements, inclu d new wellhead. NU BOP. laden fluid. Spotted 25 sx ng, found holes in casing @ @ 2015-1900. WOC. Tagg WOC. 300-350' (approved by Kev tot test. Spotted 25 sx cem wn and moved off. Cut off wellhead. Welded or noved off. Installed Closed- 2132 verified by the BLM We ERVES OPERATING, sent to ssing by DAVID GLASS on O Title COMP Date 06/15/2 R FEDERAL OR STATE office Roswel ime for any person knowingly and any matter within its jurisdiction	A. REVISED ** B	depths of all pertinent markers and zones. nt reports shall be filed within 30 days terval, a Form 3160-4 shall be filed once been completed, and the operator has Perfd Perfd Perfd pry em 2243SE) NATOR Date 06/15/2 any department or agency of the United BLM REVISED **	

Additional data for EC transaction #342132 that would not fit on the form

32. Additional remarks, continued

...

steel tanks. Hauled contents from Closed-Loop System to approved NMOCD disposal location according to Rule 19.15.17.