Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NMOCD

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

Hobbs

5. Lease Serial No.

Do not use th		a real				
Do not use this form for proposals to drill or to re-enter an BS och abandoned well. Use form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side: 0 3 2016			7. If Unit or CA/Agre	eement, Name and/or No.		
Type of Well	RECE	IVED	8. Well Name and No. ENDURANCE 36 STATE COM 704H			
2. Name of Operator Contact: STAN WAGNER EOG RESOURCES INCORPORATEDE-Mail: stan_wagner@eogresources.com			9. API Well No. 30-025-43015-00-X1			
3a. Address MIDLAND, TX 79702		3b. Phone No. (include area code) Ph: 432-686-3689		10. Field and Pool, or Exploratory WC-025 G09 S263327G		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State		
Sec 36 T26S R33E Lot 4 360FSL 1020FWL				LEA COUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, RE	PORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION		ТҮРЕ С	TYPE OF ACTION			
□ Notice of Intent	☐ Acidize	□ Deepen	☐ Producti	on (Start/Resume)	☐ Water Shut-Off	
The figure 1 and 1	☐ Alter Casing	☐ Fracture Treat	☐ Reclama	tion	☐ Well Integrity	
Subsequent Report	☐ Casing Repair	■ New Construction	☐ Recomp	lete	Other .	
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon ☐ Tempe		arily Abandon Drilling Operatio		
	☐ Convert to Injection	☐ Plug Back	☐ Water D	isposal		
testing has been completed. Final Abdetermined that the site is ready for final 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105	alts in a multiple completion or red only after all requirements, inclu d'.	completion in a n		50-4 shall be filed once	
testing has been completed. Final Ab determined that the site is ready for fi	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield opg, 1.34 CFS yield. Surface. WOC 25 hrs. 0 psi for 30 minutes. Test operations. Test operations are set of the surface. WOC 25 hrs. 0.7#, HCP-110, (172) LTC ass H POZ, 14.4 ppg, 1.26 ass H POZ, 14.4 ppg, 1.26 ass Class C. 14.8 ppg. 1.	alts in a multiple completion or red only after all requirements, inclu 4'. d; good. & (75) Flushmax III set at 1 CFS yield; WOC 4 hrs; .39 CFS yield; WOC 4 hrs;	completion in a n	ew interval, a Form 316	50-4 shall be filed once	
testing has been completed. Final Abdetermined that the site is ready for final Abdetermined that the site is ready for final 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Class Cement via bradenhead w/ 20 Top out cement w/ 845 sx Class Complete the foregoing is 150 class control of the foregoing is 150 cl	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yields on the control of the co	alts in a multiple completion or red only after all requirements, incluid- 4'. d; d; d; d(75) Flushmax III set at 1 CFS yield; WOC 4 hrs; .39 CFS yield; WOC 4 hrs. //ield. WOC 4.75 hrs.	completion in a n ding reclamation	ew interval, a Form 316, have been completed,	50-4 shall be filed once	
testing has been completed. Final Abdetermined that the site is ready for final Abdetermined that the site is ready for final 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp. Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Class Cement via bradenhead w/ 20 Top out cement w/ 845 sx Class Complete the state of the state of the site of the state of the site of the s	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield on the control of the con	alts in a multiple completion or red only after all requirements, included only after all requirements, included on the second of the second o	completion in a n ding reclamation	System (16JAS0450SE)	50-4 shall be filed once	
testing has been completed. Final Abdetermined that the site is ready for fit 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Clast Cement via bradenhead w/ 20 Top out cement w/ 845 sx Clast Common temperature of the foregoing is Common Name (Printed/Typed) STAN WA	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yields of the control of the co	alts in a multiple completion or red only after all requirements, included only after all requirements, included on the second of the second o	ompletion in a noding reclamation 1186'. 1186'. 1186'. 1186'. 1186'. 1186'. 1186'. 1186'. 1186'.	System (16JAS0450SE)	50-4 shall be filed once	
testing has been completed. Final Abdetermined that the site is ready for fit 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Cla Cement via bradenhead w/ 20 Top out cement w/ 845 sx Class 24. I hereby certify that the foregoing is	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield surface. WOC 25 hrs. 0 psi for 30 minutes. Test of the surface. WOC 25 hrs. 0.7#, HCP-110, (172) LTC ass H POZ, 14.4 ppg, 1.26 hrs. 100 sx Class C, 14.8 ppg, 1 ss C, 14.8 p	alts in a multiple completion or red only after all requirements, included only after all requirements and after all requirements only after all requirements, included only after all requirements and all requirements all requirements and all requirements all requirements and all r	and the Hobbs on 07/18/2016 ACCEL 2016	System (16JAS0450SE)	50-4 shall be filed once	
testing has been completed. Final Abdetermined that the site is ready for fit 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Clast Cement via bradenhead w/ 20 Top out cement w/ 845 sx Clast Common temperature of the foregoing is Common Name (Printed/Typed) STAN WA	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield surface. WOC 25 hrs. 0 psi for 30 minutes. Test of the surface. WOC 25 hrs. 0.7#, HCP-110, (172) LTC ass H POZ, 14.4 ppg, 1.26 hrs. 100 sx Class C, 14.8 ppg, 1 ss C, 14.8 p	alts in a multiple completion or red only after all requirements, included only after all requirements, included on the second of the second o	and the Hobbs on 07/18/2016 ACCEL 2016	System (16JAS0450SE)	ECORD	
testing has been completed. Final Abdetermined that the site is ready for fit 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Cla Cement via bradenhead w/ 20 Top out cement w/ 845 sx Class Comment	d operations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield surface. WOC 25 hrs. 0 psi for 30 minutes. Test of the surface. WOC 25 hrs. 0.7#, HCP-110, (172) LTC ass H POZ, 14.4 ppg, 1.26 hrs. 100 sx Class C, 14.8 ppg, 1 ss C, 14.8 p	alts in a multiple completion or red only after all requirements, included only after all requirements and after all requirements only after all requirements, included only after all requirements and all requirements all requirements and all requirements all requirements and all r	and the Hobbs on 07/18/2016 ACCEL 2016	System (16JAS0450SE)	ECORD	
testing has been completed. Final Abdetermined that the site is ready for fit 7/06/16 Spud 14-3/4" hole. 7/07/16 Ran 26 jts 10-3/4", 40 Cement lead w/ 370 sx Class tail w/ 200 sx Class C, 14.8 pp Circulated 29 bbls cement to s 7/08/16 Tested casing to 1500 Resumed drilling 9-7/8" hole. 7/14/16 Ran 247 jts 7-5/8", 29 Cemented w/ 550 sx 50/50 Clast Cement via bradenhead w/ 20 Top out cement w/ 845 sx Clast Composition of the com	doperations. If the operation resupandonment Notices shall be filed in all inspection.) 0.5#, J55 casing set at 105 C, 13.5 ppg, 1.74 CFS yield by 1.34 CFS yield surface. WOC 25 hrs. 0 psi for 30 minutes. Test of 2.7#, HCP-110, (172) LTC ass H POZ, 14.4 ppg, 1.26 and set Class C, 14.8 ppg, 1 ss C, 14.8 ppg, 1 ss C, 14.8 ppg, 1.39 CFS yield surface. WOC 25 hrs. True and correct. Electronic Submission #34 For EOG RESOUR intended to AFMSS for processing GNER THIS SPACE FOR additional control of this notice does not intable title to those rights in the single part of the submission in the single part of the submission.	alts in a multiple completion or red only after all requirements, included only after all requirements, included on the second of the second o	and the Hobbs on 07/18/2016 ATORY ANA ACCES OFFICE US	System (16JAS0450SE)	ECORD	

Additional data for EC transaction #344879 that would not fit on the form

32. Additional remarks, continued

7/15/16 WOC 7 hrs. Top off cement w/ 481 sx Class C, 14.8 ppg, 1.39 CFS yield. Released rig to skid to well 701H.